TRIPP LITE • Infrastructure Technical Submittal

SKU: BP72V18-2US

2U 19" EIA Rackmount / Tower

Tripp Lite BP72V18-2US External 72V Rack/Tower Battery Pack

External 72VDC 2U battery pack for select Tripp Lite SmartOnline UPS systems (SU3000RT, SU3000LCD2UHV). Extends battery runtime for critical network operations with simple plug-in daisy-chain DC cabling.

Electrical Specifications & Power Distribution

DC System Voltage	72V DC	**Battery Chemistry**	Sealed Lead Acid (VRLA) AGM
Compatibility	SU3000RT, SU3000LCD2UHV	**DC Connector**	Heavy-duty molded DC plug and socket
Daisy-Chain Capable	Yes, supports daisy-chaining	**DC Bus Circuit Breaker**	Internal fused overcurrent protection

Battery Runtime, Extended Packs & Communications

Internal Battery Quantity	12x 12V 9Ah sealed batteries	**Battery Lifespan**	3-5 years under normal float charge
Runtime Extension (SU3000RT)	+35 min @ half load, +14 min @ full load	**Runtime Extension (SU3000HV)**	+35 min @ half load, +14 min @ full load
Hot-Swappable	Yes, hot-pluggable DC connectors	**Recharge Time**	Typically 6-8 hours to 90% capacity

Physical Dimensions, Mounting & Compliance

Form Factor	2U Rackmount / Tower	**Dimensions (H x W x D)**	3.5" (89mm) x 17.5" (444mm) x 24.8" (630mm)
Net Weight	98.0 lbs (44.5 kg)	**Included Rails**	4-Post adjustable rack slide rails included
Enclosure	Steel chassis with front bezel	**Warranty**	2-Year Limited Product Warranty

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
SU3000RT	Tripp Lite 3000VA Online Double-Conversion UPS	Host UPS System
SU3000LCD2UHV	Tripp Lite 3000VA 208V Online UPS	Host UPS System