TRIPP LITE • Infrastructure Technical Submittal

SKU: OMNIVSX1500

Tower Form Factor

Tripp Lite OmniVS 1500VA 940W Line-Interactive Tower UPS

Cost-effective 1500VA / 940W line-interactive tower UPS providing battery backup and Automatic Voltage Regulation (AVR) for desktop workstations, surveillance recorders (NVR), and telecom equipment closets.

Electrical Specifications & Power Distribution

Power Rating (VA / Watts)	1500 VA / 940 Watts	**Topology**	Line-Interactive with AVR
Nominal Input Voltage	120V AC (NEMA 5-15P, 6 ft cord)	**Output Receptacles**	8x NEMA 5-15R (6 battery + 2 surge only)
Voltage Regulation	Boosts brownouts as low as 89V without battery drain	**Circuit Protection**	Resettable 15A circuit breaker

Battery Runtime, Extended Packs & Communications

Battery Chemistry	Sealed Lead Acid (VRLA)	**Full Load Runtime (940W)**	4.0 Minutes
Half Load Runtime (470W)	11.5 Minutes	**Recharge Time**	Typically 8 hours to 90%
Communication Ports	USB and DB9 serial ports	**PowerAlert Support**	Free PowerAlert Local software download

Physical Dimensions, Mounting & Compliance

Form Factor	Tower	**Dimensions (H x W x D)**	11.8" (300mm) x 7.2" (183mm) x 7.5" (191mm)
Net Weight	29.8 lbs (13.5 kg)	**Operating Temp**	0°C to 40°C (32°F to 104°F)
Certifications	Tested to UL 1778, CSA, RoHS	**Warranty**	3-Year Limited Product Warranty

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
PDUB15	Tripp Lite 1.44kW Maintenance Bypass PDU	Optional Bypass PDU