TRIPP LITE • Infrastructure Technical Submittal

SKU: PDU1215

1U 19" EIA Rackmount

Tripp Lite Basic Rack PDU 1U 15A 120V (13) 5-15R, 15ft Cord

Cost-effective, highly reliable basic 1U rackmount power distribution unit featuring 13x NEMA 5-15R outlets (1 front, 12 rear) and an extra-long 15 ft power cord. Reversible mounting flange enables front or rear outlet orientation.

Electrical Specifications & Power Distribution

Input Voltage / Current	120V AC, 15A (12A Derated)	**Input Connection (Plug)**	NEMA 5-15P (15 ft attached cord)
Output Receptacles	13x NEMA 5-15R (1 Front, 12 Rear)	**Power Capacity**	1.44 kW Continuous Load
Circuit Protection	15A thermal circuit breaker	**Frequency**	50/60 Hz pass-through
Reversible Housing	Supports front or rear outlet facing	**Chassis**	Rugged all-steel construction

Physical Dimensions, Mounting & Compliance

Form Factor	1U 19" Rackmount	**Dimensions (H x W x D)**	1.75" (44mm) x 17.5" (444mm) x 4.25" (108mm)
Net Weight	4.6 lbs (2.1 kg)	**Operating Temp**	0°C to 50°C (32°F to 122°F)
Certifications	Tested to UL 60950-1, CSA, RoHS	**Warranty**	5-Year Limited Product Warranty
Mounting Options	1U rack, wall-mount, or under-counter	**Cord Length**	15 ft (4.57 m) heavy-duty cord