TRIPP LITE • Infrastructure Technical Submittal

SKU: PDUB20

2U 19" EIA Rackmount

Tripp Lite 120V 20A Hot-Swap Maintenance Bypass PDU (8) 5-15/20R

Tripp Lite PDUB20 enables seamless hot-swap replacement or servicing of 120V 20A UPS systems without dropping power to connected critical equipment. Features manual rotary bypass switch, dual 5-20P input cords, and 8x NEMA 5-15/20R outlets.

Electrical Specifications & Power Distribution

Input Voltage / Current	120V AC, 20A (16A Derated)	**Dual Input Plugs**	2x NEMA 5-20P (UPS Input + Utility Input cords)
Output Receptacles	8x NEMA 5-15/20R T-Slot Outlets	**Bypass Switch**	Manual rotary switch (UPS Mode / Bypass Mode)
Transfer Operation	Make-before-break zero interruption transfer	**Power Capacity**	1.92 kW Continuous Load

Physical Dimensions, Mounting & Compliance

Form Factor	2U 19" Rackmount	**Dimensions (H x W x D)**	3.5" (89mm) x 17.5" (444mm) x 6.5" (165mm)
Net Weight	7.5 lbs (3.4 kg)	**Warranty**	5-Year Limited Product Warranty