TRIPP LITE • Infrastructure Technical Submittal

SKU: PDUMH20NET2

1U 19" EIA Rackmount

Tripp Lite Single-Phase Switched PDU 1U 20A 120V (8) 5-15/20R

Tripp Lite PDUMH20NET2 offers 20A switched power distribution with individual outlet control, digital current ammeter, and pre-installed LX Platform network card. Includes NEMA L5-20P locking plug with 5-20P adapter for maximum deployment flexibility.

Electrical Specifications & Power Distribution

Input Voltage / Current	120V AC, 20A (16A Derated)	**Input Connection (Plug)**	NEMA L5-20P Twist-Lock with 5-20P adapter (12 ft cord)
Output Receptacles	8x NEMA 5-15/20R T-Slot Outlets	**Outlet Switching Capability**	Individual on/off/reboot per outlet
Power Capacity	1.92 kW Continuous Load	**Metering**	Digital LED ammeter reports total load in amps
Management Interface	Pre-installed WEBCARDLX HTML5	**Protocols**	SNMPv1/v2c/v3, HTTP, HTTPS, SSH, Modbus-TCP

Physical Dimensions, Mounting & Compliance

Form Factor	1U 19" Rackmount (Reversible)	**Dimensions (H x W x D)**	1.75" (44mm) x 17.5" (444mm) x 8.5" (216mm)
Net Weight	8.5 lbs (3.9 kg)	**Operating Temp**	0°C to 40°C (32°F to 104°F)
Certifications	Tested to UL 60950-1, CSA, FCC Class A	**Warranty**	2-Year Limited Product Warranty
Cord Retention	Cord retention bracket kit included	**Enclosure**	Rugged all-metal steel chassis

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
E2MT	Tripp Lite EnviroSense2 Environmental Sensor Module	Monitors temperature, humidity, dry contacts