TRIPP LITE • Infrastructure Technical Submittal

SKU: PDUMH30HVNET

2U 19" EIA Rackmount

Tripp Lite Switched PDU 2U 30A 208/240V (16) C13 & (4) C19

High-voltage 2U switched PDU providing 30A 208/240V distribution with 16x C13 and 4x C19 outlets. Features individual outlet reboot, digital load ammeter, and pre-installed WEBCARDLX network interface.

Electrical Specifications & Power Distribution

Input Voltage / Current	208V / 240V AC, 30A (24A Derated)	**Input Connection (Plug)**	NEMA L6-30P Twist-Lock (10 ft cord)
Output Receptacles	16x IEC C13, 4x IEC C19 (20 Outlets Total)	**Outlet Switching Capability**	Individual on/off/reboot per outlet
Power Capacity	5.0 kW Continuous Load	**Metering**	Digital LED ammeter reports load per bank
Management Interface	Pre-installed WEBCARDLX HTML5	**Protocols**	SNMPv1/v2c/v3, HTTP, HTTPS, SSH, Modbus-TCP

Physical Dimensions, Mounting & Compliance

Form Factor	2U 19" Rackmount	**Dimensions (H x W x D)**	3.5" (89mm) x 17.5" (444mm) x 11.9" (302mm)
Net Weight	13.2 lbs (6.0 kg)	**Operating Temp**	0°C to 40°C (32°F to 104°F)
Certifications	Tested to UL 60950-1, CSA, FCC Class A	**Warranty**	2-Year Limited Product Warranty

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
E2MT	Tripp Lite EnviroSense2 Environmental Sensor Module	Monitors temperature, humidity, dry contacts