TRIPP LITE • Infrastructure Technical Submittal

SKU: PDUMV20HV

0U Vertical Rackmount (70" Length)

Tripp Lite Metered PDU 0U Vertical 20A 208/240V (32) C13 & (6) C19

High-density 0U vertical metered PDU providing 20A 208/240V distribution with 32x IEC C13 and 6x IEC C19 outlets. Built with dual digital load meters and toolless button mounting.

Electrical Specifications & Power Distribution

Input Voltage / Current	208V / 240V AC, 20A (16A Derated)	**Input Connection (Plug)**	NEMA L6-20P Twist-Lock (10 ft cord)
Output Receptacles	32x IEC C13, 6x IEC C19 (38 Outlets Total)	**Metering**	Dual digital LED ammeters for Bank 1 & 2
Power Capacity	3.33 kW Continuous Load	**Circuit Protection**	2x 20A branch circuit breakers
Frequency	50/60 Hz pass-through	**Chassis**	Rugged all-metal extruded aluminum

Physical Dimensions, Mounting & Compliance

Form Factor	0U Vertical (Toolless button mount)	**Dimensions (H x W x D)**	70.0" (1778mm) x 2.19" (56mm) x 2.05" (52mm)
Net Weight	12.8 lbs (5.8 kg)	**Operating Temp**	0°C to 40°C (32°F to 104°F)
Certifications	Tested to UL 60950-1, CSA, RoHS	**Warranty**	2-Year Limited Product Warranty