TRIPP LITE • Infrastructure Technical Submittal

SKU: PDUMV20NET

0U Vertical Rackmount (70" Length)

Tripp Lite Single-Phase Switched PDU 0U Vertical 20A 120V (24) 5-15/20R

High-density 0U vertical switched PDU with 24x independently controllable NEMA 5-15/20R outlets. Features toolless zero-U mounting, digital current ammeter, and pre-installed WEBCARDLX network management card for remote outlet power cycling and energy management.

Electrical Specifications & Power Distribution

Input Voltage / Current	120V AC, 20A (16A Derated)	**Input Connection (Plug)**	NEMA L5-20P Twist-Lock with 5-20P adapter (10 ft cord)
Output Receptacles	24x NEMA 5-15/20R T-Slot Outlets	**Outlet Switching Capability**	Individual on/off/reboot per outlet
Power Capacity	1.92 kW Continuous Load	**Metering**	Digital LED ammeter reports total load in amps
Management Interface	Pre-installed WEBCARDLX HTML5	**Protocols**	SNMPv1/v2c/v3, HTTP, HTTPS, SSH, Modbus-TCP

Physical Dimensions, Mounting & Compliance

Form Factor	0U Vertical (Toolless button mount)	**Dimensions (H x W x D)**	70.0" (1778mm) x 2.19" (56mm) x 2.05" (52mm)
Net Weight	15.0 lbs (6.8 kg)	**Operating Temp**	0°C to 40°C (32°F to 104°F)
Certifications	Tested to UL 60950-1, CSA, FCC Class A	**Warranty**	2-Year Limited Product Warranty
Toolless Mounting	Pre-installed mounting buttons included	**Enclosure**	Rugged all-metal steel chassis

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
E2MT	Tripp Lite EnviroSense2 Environmental Sensor Module	Monitors temperature, humidity, dry contacts