TRIPP LITE • Infrastructure Technical Submittal

SKU: SMART1000RM2UN

2U 19" EIA Rackmount / Tower

Tripp Lite SmartPro 1000VA 600W Line-Interactive UPS (WEBCARDLX)

Tripp Lite SMART1000RM2UN 120V 1kVA 600W line-interactive rackmount UPS with pre-installed WEBCARDLX network management card. Features automatic voltage regulation (AVR), 8x NEMA 5-15R outlets arranged in two switchable load banks, and compact 13.5" shallow depth.

Electrical Specifications & Power Distribution

Power Rating (VA / Watts)	1000 VA / 600 Watts	**Nominal Input Voltage**	120V AC (83V – 147V AVR range)
Input Connection (Plug)	NEMA 5-15P (10 ft attached cord)	**Output Receptacles**	8x NEMA 5-15R (8 Outlets Total)
Output Waveform	PWM Sine Wave on battery / Pure AC	**Switchable Load Banks**	2x Independently switchable 4-outlet banks
Input Circuit Rating	15A Dedicated Branch Circuit	**Output Frequency**	50/60 Hz auto-detection

Battery Runtime, Extended Packs & Communications

Battery Chemistry	Sealed Lead Acid (VRLA) Hot-Swappable	**Full Load Runtime (600W)**	7.0 Minutes (Internal Battery)
Half Load Runtime (300W)	18.0 Minutes (Internal Battery)	**Recharge Rate**	<4 hours to 90% capacity
Pre-Installed Network Card	WEBCARDLX Network Interface Card	**Protocols**	HTML5 Web, SNMPv1/v2c/v3, SMTP, Modbus
Local Indicators	Front panel LED status array & audible alarm	**Environmental Sensor**	Supports E2M / E2MT EnviroSense2

Physical Dimensions, Mounting & Compliance

Form Factor	2U Rack/Tower (13.5" shallow depth)	**Dimensions (H x W x D)**	3.5" (89mm) x 17.5" (444mm) x 13.5" (343mm)
Net Weight	34.8 lbs (15.8 kg)	**Mounting Hardware**	4-Post mounting brackets included (4POSTRAILKIT opt.)
Certifications	Tested to UL 1778, CSA, FCC Class A, RoHS	**Warranty**	2-Year Limited Product Warranty
Connected Equipment	$250,000 Ultimate Lifetime Insurance	**Operating Temp**	0°C to 40°C (32°F to 104°F)

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
E2MT	Tripp Lite EnviroSense2 Environmental Sensor Module	Monitors temperature, humidity, dry contacts
4POSTRAILKIT	Tripp Lite 4-Post Adjustable Rack Rail Kit	Adjustable 4-post depth slide rails
2POSTRMKITHD	Tripp Lite 2-Post Heavy-Duty Rackmount Kit	Supports installation in 2-post relay racks
PDUB15	Tripp Lite 120V 15A Hot-Swap Maintenance Bypass PDU	Zero-downtime UPS maintenance