TRIPP LITE • Infrastructure Technical Submittal

SKU: SMART1500LCD

2U 19" EIA Rackmount / Tower

Tripp Lite SmartPro 1500VA 900W Line-Interactive UPS

Tripp Lite SMART1500LCD provides 1500VA / 900W power protection with rotatable digital LCD status screen and Automatic Voltage Regulation. Corrects brownouts down to 75V and overvoltages up to 147V without discharging internal batteries.

Electrical Specifications & Power Distribution

Power Rating (VA / Watts)	1500 VA / 900 Watts	**Nominal Input Voltage**	120V AC (75V – 147V AVR range)
Input Connection (Plug)	NEMA 5-15P (6 ft attached cord)	**Output Receptacles**	8x NEMA 5-15R (8 Outlets Total)
Output Waveform	PWM Sine Wave on battery / Pure AC	**Switchable Load Banks**	4x Battery/Surge + 4x Surge-Only outlets
Input Circuit Rating	15A Dedicated Branch Circuit	**Output Frequency**	60 Hz ±3 Hz

Battery Runtime, Extended Packs & Communications

Battery Chemistry	Sealed Lead Acid (VRLA) Hot-Swappable	**Full Load Runtime (900W)**	3.5 Minutes (Internal Battery)
Half Load Runtime (450W)	11.8 Minutes (Internal Battery)	**Recharge Rate**	<8 hours to 90% capacity
Communication Ports	USB and DB9 serial ports (HID compliant)	**Local Interface**	Multi-function interactive LCD screen

Physical Dimensions, Mounting & Compliance

Form Factor	2U Rack/Tower (Stands included)	**Dimensions (H x W x D)**	3.5" (89mm) x 17.3" (439mm) x 10.5" (267mm)
Net Weight	29.4 lbs (13.3 kg)	**Mounting Hardware**	2U rackmount brackets included
Certifications	Tested to UL 1778, CSA, FCC Class A, RoHS	**Warranty**	3-Year Limited Product Warranty
Connected Equipment	$250,000 Ultimate Lifetime Insurance	**Operating Temp**	0°C to 40°C (32°F to 104°F)

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
4POSTRAILKIT	Tripp Lite 4-Post Adjustable Rack Rail Kit	Adjustable 4-post depth slide rails
PDUB15	Tripp Lite 120V 15A Hot-Swap Maintenance Bypass PDU	Zero-downtime UPS maintenance