TRIPP LITE • Infrastructure Technical Submittal

SKU: SMART2200RMXL2U

2U 19" EIA Rackmount / Tower

Tripp Lite SmartPro 2200VA 1920W Extended Run UPS

Line-interactive pure sine wave UPS with external battery connection port for scalable runtime expansion (compatible with BP48V24-2U). Features 2200VA / 1920W capacity, NEMA 5-20P input, open WEBCARDLXE expansion slot, and two switchable load banks.

Electrical Specifications & Power Distribution

Power Rating (VA / Watts)	2200 VA / 1920 Watts (0.87 PF)	**Nominal Input Voltage**	120V AC (83V – 145V AVR range)
Input Connection (Plug)	NEMA 5-20P (10 ft attached cord)	**Output Receptacles**	4x NEMA 5-15R, 4x NEMA 5-20R (8 Total)
Output Waveform	Pure Sine Wave Output (<5% THD)	**Switchable Load Banks**	2x Independently switchable 4-outlet banks
Input Circuit Rating	20A Dedicated Branch Circuit	**Output Frequency**	50/60 Hz auto-detection

Battery Runtime, Extended Packs & Communications

Battery Chemistry	Sealed Lead Acid (VRLA) Hot-Swappable	**Full Load Runtime (1920W)**	4.5 Minutes (Internal Battery)
Half Load Runtime (960W)	12.0 Minutes (Internal Battery)	**Extended Battery Module**	Supports BP48V24-2U external battery pack
Expansion Card Slot	Open slot for WEBCARDLXE Card	**Protocols**	SNMP, Web, Modbus via optional card
Local Indicators	Front panel LED display with load percentage	**Environmental Sensor**	Supports E2MT via WEBCARDLXE

Physical Dimensions, Mounting & Compliance

Form Factor	2U Rack/Tower (Stands included)	**Dimensions (H x W x D)**	3.5" (89mm) x 17.5" (444mm) x 19.0" (483mm)
Net Weight	54.6 lbs (24.8 kg)	**Mounting Hardware**	4-Post adjustable rack slide rails included
Certifications	Tested to UL 1778, CSA, FCC Class A, RoHS	**Warranty**	2-Year Limited Product Warranty
Connected Equipment	$250,000 Ultimate Lifetime Insurance	**Operating Temp**	0°C to 40°C (32°F to 104°F)

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
BP48V24-2U	Tripp Lite 48VDC 2U External Battery Pack	Extended Battery Module
WEBCARDLXE	Tripp Lite HTML5 Web/SNMP Network Management Card	Network Management Expansion Card
E2MT	Tripp Lite EnviroSense2 Environmental Sensor Module	Monitors temperature, humidity, dry contacts
PDUB20	Tripp Lite 120V 20A Hot-Swap Maintenance Bypass PDU	Zero-downtime UPS maintenance