TRIPP LITE • Infrastructure Technical Submittal

SKU: SMART3000RM2U

2U 19" EIA Rackmount / Tower

Tripp Lite SmartPro 3000VA 2880W Line-Interactive UPS

High-capacity 3000VA / 2880W pure sine wave line-interactive UPS with NEMA L5-30P locking input plug. Features 8x NEMA 5-15/20R and 1x NEMA L5-30R locking output receptacles, open WEBCARDLXE slot, AVR brownout/overvoltage correction, and high efficiency.

Electrical Specifications & Power Distribution

Power Rating (VA / Watts)	3000 VA / 2880 Watts (0.96 PF)	**Nominal Input Voltage**	120V AC (83V – 145V AVR range)
Input Connection (Plug)	NEMA L5-30P Twist-Lock (10 ft cord)	**Output Receptacles**	8x NEMA 5-15/20R, 1x NEMA L5-30R (9 Total)
Output Waveform	Pure Sine Wave Output (<5% THD)	**Switchable Load Banks**	2x Independently switchable outlet groups
Input Circuit Rating	30A Dedicated Branch Circuit	**Output Frequency**	50/60 Hz auto-detection

Battery Runtime, Extended Packs & Communications

Battery Chemistry	Sealed Lead Acid (VRLA) Hot-Swappable	**Full Load Runtime (2880W)**	3.5 Minutes (Internal Battery)
Half Load Runtime (1440W)	10.0 Minutes (Internal Battery)	**Recharge Rate**	<4.5 hours to 90% capacity
Expansion Card Slot	Open slot for WEBCARDLXE Card	**Protocols**	SNMP, Web, Modbus via optional card
Local Indicators	Front panel LED display with load percentage	**Environmental Sensor**	Supports E2MT via WEBCARDLXE

Physical Dimensions, Mounting & Compliance

Form Factor	2U Rack/Tower (Stands included)	**Dimensions (H x W x D)**	3.5" (89mm) x 17.5" (444mm) x 19.0" (483mm)
Net Weight	71.0 lbs (32.2 kg)	**Mounting Hardware**	4-Post adjustable rack slide rails included
Certifications	Tested to UL 1778, CSA, FCC Class A, RoHS	**Warranty**	2-Year Limited Product Warranty
Connected Equipment	$250,000 Ultimate Lifetime Insurance	**Operating Temp**	0°C to 40°C (32°F to 104°F)

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
WEBCARDLXE	Tripp Lite HTML5 Web/SNMP Network Management Card	Network Management Expansion Card
E2MT	Tripp Lite EnviroSense2 Environmental Sensor Module	Monitors temperature, humidity, dry contacts
2POSTRMKITHD	Tripp Lite 2-Post Heavy-Duty Rackmount Kit	Supports installation in 2-post relay racks
PDUB30	Tripp Lite 120V 30A Hot-Swap Maintenance Bypass PDU	Zero-downtime UPS maintenance