TRIPP LITE • Infrastructure Technical Submittal

SKU: SU1500RT

2U 19" EIA Rackmount / Tower

Tripp Lite SmartOnline 1500VA 1350W Online Double-Conversion UPS

True online double-conversion UPS offering zero transfer time (0 ms) from AC to battery, pure sine wave output, and total electrical isolation. Features 1500VA / 1350W output, 6x NEMA 5-15R receptacles, external battery pack connector, and open WEBCARDLXE slot.

Electrical Specifications & Power Distribution

Power Rating (VA / Watts)	1500 VA / 1350 Watts (0.90 PF)	**Topology / Transfer Time**	Online Double-Conversion (0 ms)
Nominal Input Voltage	120V AC (100V – 150V Full Load)	**Output Receptacles**	6x NEMA 5-15R (6 Outlets Total)
Input Connection (Plug)	NEMA 5-15P (10 ft attached cord)	**Switchable Load Banks**	2x Independently switchable 3-outlet banks
Input Circuit Rating	15A Dedicated Branch Circuit	**Output Frequency**	50/60 Hz auto-regulation (±0.05 Hz)

Battery Runtime, Extended Packs & Communications

Battery Chemistry	Sealed Lead Acid (VRLA) Hot-Swappable	**Full Load Runtime (1350W)**	4.2 Minutes (Internal Battery)
Half Load Runtime (675W)	14.0 Minutes (Internal Battery)	**Extended Battery Module**	Supports BP48V24-2U external battery pack
Expansion Card Slot	Open slot for WEBCARDLXE Card	**Local Interface**	Front panel interactive LCD screen
Communication Ports	1x USB, 1x DB9 Serial, 1x EPO	**Environmental Sensor**	Supports E2MT via WEBCARDLXE

Physical Dimensions, Mounting & Compliance

Form Factor	2U Rack/Tower (Stands included)	**Dimensions (H x W x D)**	3.5" (89mm) x 17.5" (444mm) x 19.0" (483mm)
Net Weight	45.0 lbs (20.4 kg)	**Mounting Hardware**	4-Post adjustable rack slide rails included
Certifications	Tested to UL 1778, CSA, FCC Class A, RoHS	**Warranty**	2-Year Limited Product Warranty
Connected Equipment	$250,000 Ultimate Lifetime Insurance	**Operating Temp**	0°C to 40°C (32°F to 104°F)

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
BP48V24-2U	Tripp Lite 48VDC 2U External Battery Pack	Extended Battery Module
WEBCARDLXE	Tripp Lite HTML5 Web/SNMP Network Management Card	Network Management Expansion Card
E2MT	Tripp Lite EnviroSense2 Environmental Sensor Module	Monitors temperature, humidity, dry contacts
PDUB15	Tripp Lite 120V 15A Hot-Swap Maintenance Bypass PDU	Zero-downtime UPS maintenance