TRIPP LITE • Infrastructure Technical Submittal

SKU: SU3000LCD2UHV

2U 19" EIA Rackmount / Tower

Tripp Lite SmartOnline 3000VA 2700W 208/240V Online UPS

High-voltage true online double-conversion UPS for 200V-240V systems. Delivers 3000VA / 2700W pure sine wave power with zero transfer time (0 ms), NEMA L6-20P locking plug, 8x 6-15/20R and 1x L6-30R receptacles, and external battery pack support (BP72VRM2U).

Electrical Specifications & Power Distribution

Power Rating (VA / Watts)	3000 VA / 2700 Watts (0.90 PF)	**Topology / Transfer Time**	Online Double-Conversion (0 ms)
Nominal Input Voltage	208V / 230V / 240V AC	**Output Receptacles**	8x NEMA 6-15/20R, 1x NEMA L6-30R (9 Total)
Input Connection (Plug)	NEMA L6-20P Twist-Lock (10 ft cord)	**Switchable Outlet Groups**	2x Independently switchable outlet groups
Input Circuit Breaker	20A Dedicated Branch Circuit	**Output Frequency**	50/60 Hz auto-regulation (±0.05 Hz)

Battery Runtime, Extended Packs & Communications

Battery Chemistry	Sealed Lead Acid (VRLA) Hot-Swappable	**Full Load Runtime (2700W)**	3.5 Minutes (Internal Battery)
Half Load Runtime (1350W)	11.0 Minutes (Internal Battery)	**Extended Battery Module**	Supports BP72VRM2U external battery pack
Expansion Card Slot	Open slot for WEBCARDLXE Card	**Local Interface**	Front panel interactive LCD screen

Physical Dimensions, Mounting & Compliance

Form Factor	2U Rack/Tower	**Dimensions (H x W x D)**	3.5" (89mm) x 17.5" (444mm) x 24.2" (615mm)
Net Weight	72.0 lbs (32.7 kg)	**Mounting Hardware**	4-Post adjustable rack slide rails included
Certifications	Tested to UL 1778, CSA, CE, RoHS	**Warranty**	2-Year Limited Product Warranty

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
BP72VRM2U	Tripp Lite 72VDC 2U External Battery Pack	Extended Battery Module
WEBCARDLXE	Tripp Lite HTML5 Web/SNMP Network Management Card	Network Management Expansion Card