TRIPP LITE • Infrastructure Technical Submittal

SKU: SU3000RT

2U 19" EIA Rackmount / Tower

# Tripp Lite SmartOnline 3000VA 2700W Online Double-Conversion UPS

Heavy-duty 3000VA / 2700W true online double-conversion UPS with NEMA L5-30P locking plug and 0 ms transfer time. Provides clean, computer-grade AC power for dense virtualization hosts, core switches, and enterprise security operations centers.

## Electrical Specifications & Power Distribution

| | | | |
|---|---|---|---|
| **Power Rating (VA / Watts)** | 3000 VA / 2700 Watts (0.90 PF) | **Topology / Transfer Time** | Online Double-Conversion (0 ms) |
| **Nominal Input Voltage** | 120V AC (100V – 150V Full Load) | **Output Receptacles** | 6x NEMA 5-15/20R, 1x NEMA L5-30R (7 Total) |
| **Input Connection (Plug)** | NEMA L5-30P Twist-Lock (10 ft cord) | **Switchable Load Banks** | 2x Independently switchable outlet groups |
| **Input Circuit Rating** | 30A Dedicated Branch Circuit | **Output Frequency** | 50/60 Hz auto-regulation (±0.05 Hz) |

## Battery Runtime, Extended Packs & Communications

| | | | |
|---|---|---|---|
| **Battery Chemistry** | Sealed Lead Acid (VRLA) Hot-Swappable | **Full Load Runtime (2700W)** | 3.5 Minutes (Internal Battery) |
| **Half Load Runtime (1350W)** | 11.0 Minutes (Internal Battery) | **Extended Battery Module** | Supports BP72VRM2U external battery pack |
| **Expansion Card Slot** | Open slot for WEBCARDLXE Card | **Local Interface** | Front panel interactive LCD screen |
| **Communication Ports** | 1x USB, 1x DB9 Serial, 1x EPO | **Environmental Sensor** | Supports E2MT via WEBCARDLXE |

## Physical Dimensions, Mounting & Compliance

| | | | |
|---|---|---|---|
| **Form Factor** | 2U Rack/Tower (Stands included) | **Dimensions (H x W x D)** | 3.5" (89mm) x 17.5" (444mm) x 24.2" (615mm) |
| **Net Weight** | 72.0 lbs (32.7 kg) | **Mounting Hardware** | 4-Post adjustable rack slide rails included |
| **Certifications** | Tested to UL 1778, CSA, FCC Class A, RoHS | **Warranty** | 2-Year Limited Product Warranty |
| **Connected Equipment** | $250,000 Ultimate Lifetime Insurance | **Operating Temp** | 0°C to 40°C (32°F to 104°F) |

## Compatible Accessories, Mounting Rails & Field Replacement Options

| Part Number / SKU | Description | Category & Application |
|---|---|---|
| **BP72VRM2U** | Tripp Lite 72VDC 2U External Battery Pack | Extended Battery Module |
| **WEBCARDLXE** | Tripp Lite HTML5 Web/SNMP Network Management Card | Network Management Expansion Card |
| **E2MT** | Tripp Lite EnviroSense2 Environmental Sensor Module | Monitors temperature, humidity, dry contacts |
| **PDUB30** | Tripp Lite 120V 30A Hot-Swap Maintenance Bypass PDU | Zero-downtime UPS servicing |