TRIPP LITE • Infrastructure Technical Submittal

SKU: SU5000RTF

5U 19" EIA Rackmount / Tower

Tripp Lite SmartOnline 5000VA 4500W Online UPS with Step-Down Transformer

Heavy-duty 5000VA / 4500W online double-conversion UPS paired with a 2U isolation step-down transformer module. Delivers simultaneous 208V and 120V pure sine wave output with zero transfer time for enterprise data racks.

Electrical Specifications & Power Distribution

Power Rating (VA / Watts)	5000 VA / 4500 Watts (0.90 PF)	**Topology / Transfer Time**	Online Double-Conversion (0 ms)
Nominal Input Voltage	208V / 240V AC (NEMA L6-30P)	**Output Receptacles**	1x L6-30R, 2x L6-20R, 12x 5-15/20R
Step-Down Transformer	Integrated 2U step-down transformer module	**Output Voltages**	Simultaneous 208V and 120V AC
Input Circuit Breaker	30A Dedicated Branch Circuit	**Output Frequency**	50/60 Hz auto-regulation (±0.05 Hz)

Battery Runtime, Extended Packs & Communications

Battery Chemistry	Sealed Lead Acid (VRLA) Hot-Swappable	**Full Load Runtime (4500W)**	5.0 Minutes (Internal Battery)
Half Load Runtime (2250W)	13.0 Minutes (Internal Battery)	**Extended Battery Module**	Supports BP192V12-3U external battery pack
Network Management	Pre-installed WEBCARDLX Network Interface Card	**Protocols**	HTML5 Web, SNMPv1/v2c/v3, Modbus-TCP

Physical Dimensions, Mounting & Compliance

Form Factor	5U Rack/Tower (3U UPS + 2U Transformer)	**Dimensions (H x W x D)**	8.75" (222mm) x 17.5" (444mm) x 26.0" (660mm)
Net Weight	143.0 lbs (64.9 kg)	**Mounting Hardware**	4-Post adjustable heavy-duty rack rails included
Certifications	Tested to UL 1778, CSA, CE, RoHS	**Warranty**	2-Year Limited Product Warranty

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
BP192V12-3U	Tripp Lite 192VDC 3U External Battery Pack	Extended Battery Module
WEBCARDLXE	Tripp Lite HTML5 Web/SNMP Network Card	Host Network Interface