TRIPP LITE • Infrastructure Technical Submittal

SKU: SU6000RT

4U 19" EIA Rackmount / Tower

# Tripp Lite SmartOnline 6000VA 5400W 208/240V Online UPS

High-capacity 6000VA / 5400W true online double-conversion UPS for enterprise data center racks and mission-critical high-density headends. Features pre-installed WEBCARDLX network card, 2x L6-30R and 4x L6-20R receptacles, and zero transfer time.

## Electrical Specifications & Power Distribution

| | | | |
|---|---|---|---|
| **Power Rating (VA / Watts)** | 6000 VA / 5400 Watts (0.90 PF) | **Topology / Transfer Time** | Online Double-Conversion (0 ms) |
| **Nominal Input Voltage** | 208V / 240V AC | **Output Receptacles** | 2x NEMA L6-30R, 4x NEMA L6-20R (6 Total) |
| **Input Connection** | Hardwire or L6-30P Connection | **Input Circuit Breaker** | 30A Dedicated Branch Circuit |
| **Output Waveform** | Pure Sine Wave (<2% THD) | **Output Frequency** | 50/60 Hz auto-regulation (±0.05 Hz) |

## Battery Runtime, Extended Packs & Communications

| | | | |
|---|---|---|---|
| **Battery Chemistry** | Sealed Lead Acid (VRLA) Hot-Swappable | **Full Load Runtime (5400W)** | 3.5 Minutes (Internal Battery) |
| **Half Load Runtime (2700W)** | 9.5 Minutes (Internal Battery) | **Extended Battery Module** | Supports BP192V12-3U external battery pack |
| **Pre-Installed Network Card** | WEBCARDLX Network Interface Card | **Protocols** | HTML5 Web, SNMPv1/v2c/v3, Modbus-TCP |

## Physical Dimensions, Mounting & Compliance

| | | | |
|---|---|---|---|
| **Form Factor** | 4U Rack/Tower (Power module + Battery) | **Dimensions (H x W x D)** | 7.0" (178mm) x 17.5" (444mm) x 26.0" (660mm) |
| **Net Weight** | 143.0 lbs (64.9 kg) | **Mounting Hardware** | 4-Post adjustable rack slide rails included |
| **Certifications** | Tested to UL 1778, CSA, FCC Class A, RoHS | **Warranty** | 2-Year Limited Product Warranty |

## Compatible Accessories, Mounting Rails & Field Replacement Options

| Part Number / SKU | Description | Category & Application |
|---|---|---|
| **BP192V12-3U** | Tripp Lite 192VDC 3U External Battery Pack | Extended Battery Module |
| **E2MT** | Tripp Lite EnviroSense2 Environmental Sensor Module | Monitors temperature, humidity, dry contacts |