TRIPP LITE • Infrastructure Technical Submittal

SKU: WEBCARDLXE
Internal Expansion Slot

Tripp Lite HTML5 Web/SNMP Network Management Card

Tripp Lite WEBCARDLXE network interface card converts compatible Tripp Lite SmartPro and SmartOnline UPS systems into managed network devices. Features Java-free HTML5 web interface, SNMPv1/v2c/v3, Syslog, Modbus-TCP, and USB port for EnviroSense2 sensor.

Electrical Specifications & Power Distribution

Interface Speed	10/100/1000 Mbps Gigabit Ethernet (RJ45)	**Power Supply**	Powered directly from UPS internal expansion slot
Supported Protocols	HTML5 HTTPS, SNMPv1/v2c/v3, SMTP, Modbus-TCP	**Web Interface**	Full mobile-friendly HTML5 (No Java required)
USB Port	1x USB Type-A port for E2MT sensor	**Auto-Shutdown**	PowerAlert Network Shutdown Agent (PANSA)
Event Logging	Real-time event logging, email & SNMP traps	**Firmware**	Flash-upgradeable firmware via web

Physical Dimensions, Mounting & Compliance

Form Factor	Internal Expansion Card	**Dimensions (H x W x D)**	1.5" (38mm) x 2.4" (61mm) x 4.7" (120mm)
Net Weight	0.2 lbs (0.1 kg)	**Operating Temp**	0°C to 40°C (32°F to 104°F)
Certifications	Tested to UL 60950-1, CSA, FCC Class B, RoHS	**Warranty**	2-Year Limited Product Warranty

Compatible Accessories, Mounting Rails & Field Replacement Options

Part Number / SKU	Description	Category & Application
E2MT	Tripp Lite EnviroSense2 Environmental Sensor Module	Monitors temperature, humidity, dry contacts