

AMG9050G UNMANAGED SWITCHES WITH OPTIONAL POE+



Rugged Ethernet Solutions


The AMG hardened Ethernet switches have been specifically designed to meet the high reliability requirements for rugged outdoor and harsh industrial environments with extended temperature requirements.



[AMG9050G-HP-H]



[AMG9050G-HP-H-R]



/ OVERVIEW

With 5 × 100 or 1000Tx copper ports, this product provides a flexible solution for all small to medium networking applications. This product range meets all the relevant industry standards for 1000Mbit/s Ethernet, with 'plug-and-play' installation.

It is also compliant with all relevant Safety and EMC standards such as temperature shock, and vibration for traffic control equipment (see reverse for details).

Supporting 10/100/1000Mbit/s data rates, full duplex these flexible, compact and easy to use unmanaged Ethernet switches also have the benefit of auto-negotiation.

Optional PoE provides power to 802.3af/at compliant devices as well as data to edge of network devices.

/ FEATURES

- Standalone, 19" Subrack and DIN-Rail mount formats for minimum space usage
- 10/100/1000 Mbps full bandwidth Ethernet
- Compliant with all IEEE 802.3 variants (u/ab/x/z)
- Compliant with all relevant Safety and EMC Standards
- 12-15V_{DC} supply voltage (non-PoE)
- 48V_{DC} and 54V_{DC} supply voltage (PoE and PoE+ respectively)
- LED indicators
- 'Plug-and-Play' installation
- Easy to maintain
- Extended operating temperature compared with industry equivalents -40°C to +75°C
- On-board PoE on 4 ports
- AMG rack power support for non PoE applications

Specifications.

Standards.

IEEE 802.3i	10Base-T
IEEE 802.3u	100Base-TX
IEEE 802.3ab	1000Base-T
IEEE 802.3af	Power over Ethernet (15W)
IEEE 802.3at	Power over Ethernet+ (30W)

Interface.

LED Indicators Per Port:	Power (Green) 10/100/1000/Act (Yellow) PoE (Green)
-----------------------------	--

Ethernet.

Auto MDI/MDIX

RJ45 Ports	
Front:	4x PoE 10/100/1000T
Rear:	1x 10/100/1000T

Power.

Input Voltage	+12V to +15V _{DC} (+48V to +56V _{DC} for PoE) (+52V to +56V _{DC} for PoE+)
Power Consumption	2.6W @ No load 4.1W @ 10/100Mbps 6.3 Watts @ 1000Mbps (+ PoE device consumption)

PoE+.

Input Voltage	+46V to +56V _{DC}
Output Power	25.5 to 34.2W per port
Output Voltage	+50V to +57V _{DC}
Output Current	Max 600mA

General.

Operating Temp.	-40°C to +75°C
Storage Temp.	-45°C to +85°C
Ambient Relative Humidity	0% to 95% (Non-condensing)

Mechanical.

Casing	IP 30 Protection Metal case
Dimensions	
Standalone	70 × 170 × 112 mm
Rackmount	7HP x 172 mm x 3U
Weight	1kg
Installation	Wall Mount Design (Subrack & DIN-Rail mount options also available)

Regulatory.

Europe	CE
US	FCC

Part Numbers.

AMG9050G-H	5 × 10/100/1000TX, -40 to +75°C, Power: 12-15V _{DC}
AMG9050G-HP-H	4 × 10/100/1000TX with 802.3at PoE + 1 × 10/100/1000TX, -40 to +75°C, Power: 46-54V _{DC}

Recommended PSUs.

Non PoE variant	AMG2004	15V _{DC} , 24W Power Supply, DIN-Rail mounting.
PoE+ variant	AMG2019	48-55V _{DC} , 120W Power Supply, DIN-Rail mounting

Notes.

Rackmount Options are also available, just add 'R' to the end of the part number e.g. AMG9050G-H-R

Proud to be a British
Manufacturer 