

Accessories

Cables

ID	Name	Specifications	Compatible With:
STACK-T1-50CM-M Photo of the STACK-T1-50CM-M accessory.	Meraki 120G Stacking Cable (0.5 m)	- High-performance stacking cable used to daisy-chain switches to each other. - Recommended for high-performance networks - Length of 50 cm	Catalyst 9300L-M
STACK-T3A-1M-M Photo of the STACK-T3A-1M-M accessory.	C9300L Type 3A Stacking Cable (1 m)	- Enhance the functionality of your access switch - Built for Catalyst 9300L-M switches and stack kit	Catalyst 9300L-M
STACK-T3A-3M-M Photo of the STACK-T3A-3M-M accessory.	C9300L Type 3A Stacking Cable (3 m)	- Enhance the functionality of your access switch - Built for Catalyst 9300L-M switches and stack kit	Catalyst 9300L-M
STACK-T3A-50CM-M Photo of the STACK-T3A-50CM-M accessory.	C9300L Type 3A Stacking Cable (50 cm)	- C9300L Type 3A stacking cable (50 cm) - Enhance the functionality of your access switch - Built for Catalyst 9300L-M switches and stack kit	Catalyst 9300L-M
CAB-SPWR-150CM-M Photo of the CAB-SPWR-150CM-M accessory.	Meraki StackPower Cable (150 cm)	- Creates additional power capacity by pooling power sources to power more PoE devices. - Additional redundancy saves cost through efficient power distribution to stack - Length is 150 cm	MS390
CAB-SPWR-30CM-M Photo of the CAB-SPWR-30CM-M accessory.	Meraki StackPower Cable (30 cm)	- Creates additional power capacity by pooling power sources to power more PoE devices. - Additional redundancy saves cost through efficient power distribution to stack	MS390

ID	Name	Specifications	Compatible With:
		Length is 30 cm	
MA-CBL-120G-3M Photo of the MA-CBL-120G-3M accessory.	Meraki 120G Stacking Cable (3 m)	- High-performance stacking cable used to daisy-chain switches to each other. - Recommended for high-performance networks - Length of 3m	MS390
MA-CBL-120G-50CM Photo of the MA-CBL-120G-50CM accessory.	Meraki 120G Stacking Cable (0.5 m)	- High-performance stacking cable used to daisy-chain switches to each other. - Recommended for high-performance networks - Length of 50 cm	MS390
MA-CBL-SPWR-150CM Photo of the MA-CBL-SPWR-150CM accessory.	Meraki StackPower Cable (150 cm)	- Creates additional power capacity by pooling power sources to power more PoE devices. - Additional redundancy saves cost through efficient power distribution to stack - Length of 150 cm	MS390
MA-CBL-TA-1M Photo of the MA-CBL-TA-1M accessory.	Twinax Cable with SFP+ Connectors (1 m)	- A direct attach cable for use with 10 Gigabit Ethernet network hardware. - SFP+ direct attach (10GSFP+Cu) - Range of 1 m	MS390
MA-CBL-TA-3M Photo of the MA-CBL-TA-3M accessory.	Twinax Cable with SFP+ Connectors (3 m)	- A direct attach cable for use with 10 Gigabit Ethernet network hardware. - SFP+ direct attach (10GSFP+Cu) - Range of 3 m	MS390
STACK-T1-1M-M Photo of the STACK-T1-1M-M accessory.	Meraki 120G Stacking Cable (1 m)	- High-performance stacking cable used to daisy-chain switches to each other. - Recommended for high-performance networks - Length is 1 m	MS390
STACK-T1-3M-M Photo of the STACK-T1-3M-M accessory.	Meraki 120G Stacking Cable (3 m)	- High-performance stacking cable used to daisy-chain switches to each other. - Recommended for high-performance networks - Length is 3 m	MS390
MA-CBL-	Meraki StackPower Cable (150 cm)	Creates additional power capacity by pooling power	MS390

ID	Name	Specifications	Compatible With:
SPWR-150CM Photo of the MA-CBL-SPWR-150CM accessory.		sources to power more PoE devices. - Additional redundancy saves cost through efficient power distribution to stack - Length of 150 cm	

Kits

ID	Name	Specifications	Compatible With:
4PT-KIT-T2-M	Catalyst 9300-M Rack Mount Kit	Suggested mounting bracket for Catalyst 9300-M installed in standard switch racks	Catalyst 9300-M
C9300L-STAK-KIT2-M 4PT-KIT-T2-MC9300L-STAK-KIT2-M accessory.	Stack Kit for C9300L-M Switches	- Includes two stack adapters and one stack cable. - Enhance the functionality of your access switch	Catalyst 9300L-M

Power

ID	Name	Specifications	Compatible With:
PWR-C1-1900WAC-P-M Photo of a PWR-C1-1900WAC-P-M accessory.	1900W AC Power Supply	- Field-replaceable and hot-swappable for power where and when you need it. - Redundant power supply - Supplies up to 1900W of power	Catalyst 9300X-M Catalyst 9300-M
MA-PWR-1100WAC Photo of the MA-PWR-1100WAC accessory.	1100W AC Power Supply	- Field-replaceable and hot-swappable for power where and when you need it. - Redundant power supply - Supplies up to 1100W of power	MS390-24 MS390-48
MA-PWR-350WAC	350W AC Power Supply	Field-replaceable and hot-swappable for power where and when you need it.	MS390-24

ID	Name	Specifications	Compatible With:
Photo of the MA-PWR-350WAC accessory.		- Redundant power supply - Supplies up to 350W of power	MS390-48
MA-PWR-715WAC	715W AC Power Supply	- Field-replaceable and hot-swappable for power where and when you need it. - Redundant power supply - Supplies up to 715W of power	MS390-24
Photo of the MA-PWR-715WAC accessory.			MS390-48
PWR-C1-1100WAC-P-M	1100W AC Power Supply	- Field-replaceable and hot-swappable for power where and when you need it. - Redundant power supply - Supplies up to 1100W of power	MS390-24
Photo of the PWR-C1-1100WAC-P-M accessory.			MS390-48
PWR-C1-350WAC-P-M	350W AC Power Supply	- Field-replaceable and hot-swappable for power where and when you need it. - Redundant power supply - Supplies up to 350W of power	MS390-24
Photo of the PWR-C1-350WAC-P-M accessory.			MS390-48
PWR-C1-715WAC-P-M	715W AC Power Supply	- Field-replaceable and hot-swappable for power where and when you need it. - Redundant power supply - Supplies up to 715W of power	MS390-24
Photo of the PWR-C1-715WAC-P-M accessory.			MS390-48

Transceivers

ID	Name	Specifications	Compatible With:
C9300-NM-2C-M	Two 100G Uplink Module	- Provides 2 ports of 100 Gigabit Ethernet and supports QSFP28 transceivers. - Support for QSFP28 transceivers - Enhance the functionality of your access switch	Catalyst 9300X-M
Photo of a C9300-NM-2C-M accessory.			
C9300-NM-2Q-M	Two 40G Uplink Module	Provides 2 ports of 40 Gigabit Ethernet and supports QSFP+ transceivers.	Catalyst 9300-M
Photo of a			

ID	Name	Specifications	Compatible With:
C9300-NM-2Q-M accessory.		- Support for QSFP+ transceivers - Enhance the functionality of your access switch	
C9300-NM-2Y-M Photo of a C9300-NM-2Y-M accessory.	Two 25G SFP+ Uplink Module	- Provides two ports of up to 25 Gigabit Ethernet and supports SFP+ transceivers. - Support for SFP+ uplink module - Enhance the functionality of your access switch	Catalyst 9300-M
C9300-NM-8X-M Photo of a C9300-NM-8X-M accessory.	Eight 10G Uplink Module	- Provides 8 ports of 10 Gigabit Ethernet and supports SFP+ transceivers. - Support for SFP+ transceivers - Enhance the functionality of your access switch	Catalyst 9300-M
C9300X-NM-8Y-M Photo of a C9300X- NM-8Y-M accessory.	Eight 25G Uplink Module	- Provides 8 ports of 25 Gigabit Ethernet and supports SFP28 transceivers. - Support for SFP28 transceivers - Enhance the functionality of your access switch	Catalyst 9300X-M
MA-QSFP-40G-CSR4 Photo of the MA- QSFP-40G-CSR4 accessory.	40 GbE QSFP+ CSR4 Fiber Transceiver	- A small form-factor transceiver that provides faster communication between switches and other networking components. - Compact, hot-swappable transceiver - Standard 40GBASE-CSR4 with a range of 400 m	MS390
MA-QSFP-40G-LR4 Photo of the MA- QSFP-40G-LR4 accessory.	40 GbE QSFP+ LR4 Fiber Transceiver	- A small form-factor transceiver that provides faster communication between switches and other networking components. - Compact, hot-swappable transceiver - Standard 40GBASE-LR4 with a range of 10 km	MS390
MA-QSFP-40G-SR-BD Photo of the MA- QSFP-40G-SR-BD accessory.	40 GbE QSFP+ SR-BD Fiber Transceiver	- A small form-factor transceiver that provides faster communication between switches and other networking components. - Compact, hot-swappable transceiver - Standard 40GBASE-SR-BD with a range of 150 m	MS390
MA-QSFP-40G-SR4 Photo of the MA- QSFP-40G-SR4 accessory.	40 GbE QSFP+ SR4 Fiber Transceiver	- A small form-factor transceiver that provides faster communication between switches and other networking components. - Compact, hot-swappable transceiver - Standard 40GBASE-SR4 with a range of 150 m	MS390

ID	Name	Specifications	Compatible With:
MA-SFP-10GB-LR	10 GbE SFP+ LR Fiber Transceiver	- A transceiver that provides fast communication between switches and other networking components. - Standard 10GBASE-LR - Range of 10 km	MS390
Photo of the MA-SFP-10GB-LR accessory.			
MA-SFP-10GB-LRM	10 GbE SFP+ LRM Fiber Transceiver	- A transceiver that provides 10x faster communication between switches and other networking components. - Ethernet standard 10GBASE-LRM - Range 220 m	MS390
Photo of the MA-SFP-10GB-LRM accessory.			
MA-QSFP-40G-CSR4	40 GbE QSFP+ CSR4 Fiber Transceiver	- A small form-factor transceiver that provides faster communication between switches and other networking components. - Compact, hot-swappable transceiver - Standard 40GBASE-CSR4 with a range of 400 m	MS390
Photo of the MA-QSFP-40G-CSR4 accessory.			
MA-QSFP-40G-LR4	40 GbE QSFP+ LR4 Fiber Transceiver	- A small form-factor transceiver that provides faster communication between switches and other networking components. - Compact, hot-swappable transceiver - Standard 40GBASE-LR4 with a range of 10 km	MS390
Photo of the MA-QSFP-40G-LR4 accessory.			

Fans

FAN-T2-M	16K2 System Fan	- Keep your switches cool even when your network heats up. - Front-to-back system fan - Speeds of 16K RPM	MS390
Photo of the FAN-T2-M accessory.			
MA-FAN-16K	16K RPM Fan	- Keep your switches cool even when your network heats up. - Front-to-back fan - Speeds of 16K RPM	MS390
Photo of the MA-FAN-16K accessory.			

Modules

MA-MOD-2X40G	Two 40G Uplink Modules	Provides two ports of 40 Gigabit Ethernet and supports QSFP+ transceivers.	MS390
Photo of the MA-MOD-2X40G accessory.			

MA-MOD-8X10G
Photo of the MA-MOD-8X10G accessory.

Eight
10G Uplink Module

- Support for QSFP+ transceivers
 - Enhance the functionality of your access switch
-
- Provides 8 ports of 10 Gigabit Ethernet and supports SFP+ transceivers.
 - Support for SFP+ transceivers
 - Enhance the functionality of your access switch

MS390