

Accessories

Cables

ID	Name	Specifications	Compatible With:
MA-CBL-100G-1M Photo of the MA-CBL-100G-1M accessory.	Meraki 100G Stacking Cable (1 m)	- High-performance stacking cable used to daisy-chain switches to each other. - Recommended for high-performance networks - Length is 1 m	MS355 MS450 MS450-12
MA-CBL-100G-3M Photo of the MA-CBL-100G-3M accessory.	Meraki 100G Stacking Cable (3 m)	- High-performance stacking cable used to daisy-chain switches to each other. - Recommended for high-performance networks - Length of 3m	MS355 MS450 MS450-12
MA-CBL-100G-50CM Photo of the MA-CBL-100G-50CM accessory.	Meraki 100G Stacking Cable (50 cm)	- High-performance stacking cable used to daisy-chain switches to each other. - Recommended for high-performance networks - Length of 50cm	MS355 MS450 MS450-12
MA-CBL-40G-1M Photo of the MA-CBL-40G-1M accessory.	Stacking Cable (1 m)	- High-performance stacking cable used to daisy-chain switches to each other. - Recommended for physical stacking in high-performance networks - Length of 1m	MS210 MS225 MS250 MS350 MS410

ID	Name	Specifications	Compatible With:
MA-CBL-40G-3M Photo of the MA-CBL-40G-3M accessory.	Stacking Cable (3 m)	- High-performance stacking cable used to daisy-chain switches to each other. - Recommended for physical stacking in high-performance networks - Length of 3m	MS210
			MS225
			MS250
			MS350
			MS410
			MS425
MA-CBL-40G-50CM Photo of the MA-CBL-40G-50CM accessory.	Stacking Cable (0.5 m)	- High-performance stacking cable used to daisy-chain switches to each other. - Recommended for physical stacking - Length of 0.5 m	MS210
			MS225
			MS250
			MS350
			MS410
			MS425
MA-CBL-TA-1M Photo of the MA-CBL-TA-1M accessory.	Twinax Cable with SFP+ Connectors (1 m)	- A direct attach cable for use with 10 Gigabit Ethernet network hardware. - SFP+ direct attach (10GSFP+Cu) - Range of 1 m	MS125
			MS225
			MS250
			MS350
			MS355
			MS410
MA-CBL-TA-3M Photo of the MA-CBL-TA-3M accessory.	Twinax Cable with SFP+ Connectors (3 m)	- A direct attach cable for use with 10 Gigabit Ethernet network hardware. - SFP+ direct attach (10GSFP+Cu) - Range of 3 m	MS425
			MS125
			MS225
			MS250
			MS350
			MS355
			MS410
			MS425

Fans

ID	Name	Specifications	Compatible With:
MA-FAN-16K	16K RPM Fan	- Keep your switches cool even when your network heats up. - Front-to-back fan - Speeds of 16K RPM	MS410-16
Photo of the MA-FAN-16K accessory.			

Mounts

ID	Name	Specifications	Compatible With:
MA-MNT-MID-1	Mid-Mount Mounting Bracket	- Suggested for shallow switch racks or racks that mount switches on both sides with their rear sides facing each other. - Easy to install - Screws included	MS225
Photo of the MA-MNT-MID-1 accessory.			
MA-MNT-MID-1	Mid-Mount Mounting Bracket		MS250
MA-MNT-MID-1	Mid-Mount Mounting Bracket		MS225-24
MA-MNT-MID-1	Mid-Mount Mounting Bracket		MS225-48
MA-RCKMNT	Mounting Brackets	- Easy to install - Screws included	MS250-48
Photo of the MA-RCKMNT accessory.			
MA-RCKMNT	Mounting Brackets		MS225-48
MA-RCKMNT	Mounting Brackets		MS250-24
MA-WMNTBR-PWR-ADP	Meraki Wall Mount Bracket for External Power Adapter	- Steel Wall Mount Bracket Compatible with Meraki External Power Adapter - Durable steel bracket wall mount - Flexible fitting with	MA-PWR-150WAC-ADP
Photo of the MA-WMNTBR-PWR-ADP accessory.			
MA-WMNTBR-PWR-ADP	Meraki Wall Mount Bracket for External Power Adapter		MA-PWR-300WAC-ADP

ID	Name	Specifications	Compatible With:
		adjustable clamps Compatible with 150W and 300W Meraki power adapters	

Power

ID	Name	Specifications	Compatible With:
MA-PWR-150WAC-ADP Photo of the MA-PWR-150WAC-ADP accessory.	Replacement 150 W Power Adapter		MS130-8X
MA-PWR-300W-INDADP Photo of the MA-PWR-300W-INDADP accessory.	Meraki MS130R-8P Power Adapter (300 W)	- For the Meraki MS130R cloud-managed ruggedized switch - Compatible with Meraki Wall Mount Bracket for External Power Adapter	MS130R
MA-PWR-300WAC-ADP Photo of the MA-PWR-300WAC-ADP accessory.	Replacement Power Adapter (300 WAC)		MS130-12X
MA-PWR-640WAC Photo of the MA-PWR-640WAC accessory,	640W Power Supply	- Field-replaceable and hot-swappable for power where and when you need it. - Redundant	MS250-24 MS250-48 MS350-24 MS350-48

ID	Name	Specifications	Compatible With:
		- power supply - Supplies up to 640W of power	
PWR-MS320-1025WAC	1025W Power Supply	- Designed for Meraki's cloud-managed networks. - Redundant power and hot-swappable for power where and when you need it - Supplies up to 1025W of power	MS320-48 MS350-48
Photo of the PWR-MS320-1025WAC accessory.			

Transceivers

ID	Name	Specifications	Compatible With:
MA-QSFP-100G-LR4	100 GbE QSFP+ LR4 Fiber Transceiver	- Hot-swappable transceiver that provides fast communication between switches and other networking components. - Quad small form factor 100GBASE-LR4 - Range of 10 km	MS450-12
Photo of the MA-QSFP-100G-LR4 accessory.			
MA-QSFP-100G-SR5	100 GbE QSFP+ SR4 Fiber Transceiver	A small form-factor transceiver that provides faster communication between switches and	MS450-12
Photo of the MA-QSFP-100G-SR5 accessory.			

ID	Name	Specifications	Compatible With:
		- other networking components. • Compact, hot-swappable transceiver • Range of 100 m	
MA-QSFP-40G-CSR4	40 GbE QSFP+ CSR4 Fiber Transceiver	• A small form-factor transceiver that provides faster communication between switches and other networking components. • Compact, hot-swappable transceiver • Standard 40GBASE-CSR4 with a range of 400 m	MS355 MS425
Photo of the MA-QSFP-40G-CSR4 accessory.			
MA-QSFP-40G-LR4	40 GbE QSFP+ LR4 Fiber Transceiver	• A small form-factor transceiver that provides faster communication between switches and other networking components. • Compact, hot-swappable transceiver • Standard 40GBASE-LR4 with a range of 10 km	MS450-12 MS355 MS425 MS450
Photo of the MA-QSFP-40G-LR4 accessory.			
MA-QSFP-40G-SR-BD	40 GbE QSFP+ SR-BD Fiber Transceiver	• A small form-factor transceiver that provides faster communication between switches and	MS355 MS425
Photo of the MA-QSFP-40G-SR-BD accessory.			

ID	Name	Specifications	Compatible With:
		- other networking components. • Compact, hot-swappable transceiver • Standard 40GBASE-SR-BD with a range of 150 m	
MA-QSFP-40G-SR4	40 GbE QSFP+ SR4 Fiber Transceiver	• A small form-factor transceiver that provides faster communication between switches and other networking components. • Compact, hot-swappable transceiver • Standard 40GBASE-SR4 with a range of 150 m	MS355
Photo of the MA-QSFP-40G-SR4 accessory.			MS425
			MS225-24
			MS225-48
			MS410-16
			MS410-32
		• Hot-swappable transceiver that provides fast data transfer. • Standard 10GBASE-ER • Range of 40 km	MS125
MA-SFP-10GB-ER	10 GbE SFP+ ER Fiber Transceiver		MS225
Photo of the MA-SFP-10GB-ER accessory.			MS250
			MS350
			MS355
			MS410
			MS425
			MX250
			MX450

ID	Name	Specifications	Compatible With:
MA-SFP-10GB-LR Photo of the MA-SFP-10GB-LR accessory.	10 GbE SFP+ LR Fiber Transceiver	- A transceiver that provides fast communication between switches and other networking components. - Standard 10GBASE-LR - Range of 10 km	MS225-24,
			MS225-48
			MS410-16
			MS410-32
			MS225
			MS250
			MS350
			MS355
			MS410
			MS425
MA-SFP-10GB-LRM Photo of the MA-SFP-10GB-LRM accessory.	10 GbE SFP+ LRM Fiber Transceiver	- A transceiver that provides 10x faster communication between switches and other networking components. - Ethernet standard 10GBASE-LRM - Range 220 m	MS225-24
			MS225-48
			MS410-16
			MS410-32
			MS225
			MS250
			MS350
			MS355
			MS410
			MS425
MA-SFP-10GB-ZR Photo of the MA-SFP-10GB-ZR accessory.	10 GbE SFP+ ZR Fiber Transceiver	- A transceiver that provides 10x faster communication between switches and other networking components. - Standard 10GBASE-ZR - Range of 80 km	MS225
			MS250
			MS350
			MS355
			MS410
			MS425
			MX250
			MX450

ID	Name	Specifications	Compatible With:
MA-SFP-1GB-LX10	1 GbE SFP LX Fiber Transceiver	- Hot-swappable transceiver that provides fast communication between switches and other networking components. - Standard 1000BASE-LX10 - Range of 10 km - For use with all MS series switches	MS210-24 MS210-48 MS225-24 MS225-48 MS410-16 MS410-32 MS450-12
Photo of the MA-SFP-1GB-LX10 accessory.			