



UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Accessories

SFP & Fiber > CWDM Mux Demux 8



CWDM Mux Demux 8

UACC-CWDM-8

Datasheet

Marketing Images

Installation Guide

^ Overview

Dimensions	442 x 120 x 43.7 mm (17.4 x 4.7 x 1.7")
Enclosure Material	SGCC steel
Weight	1.4 kg (3.2 lb)
Pigtail and Connector Type	COM: 0.9 mm black LC/UPC Other ports: 0.9 mm white LC/UPC
Connector	(1) COM (LC/UPC) (1) MON (LC/UPC) (1) EXP (LC/UPC) (8) 1450/1470/1490/1510/1530/1550/1570/1590 nm (LC/UPC)
Fiber	
Type	SMF-28e
Length	≥0.5 to 1 m

Channel Count	8 CH Mux/Demux
Channel Center Wavelength	1450/1470/1490/1510/1530/1550/1570/1590 nm
Min. Channel Passband	±6.5 nm
Insertion Loss	<2.5 dB (Max.)
Return Loss	50 dB (Min.)
Max. Power Handling	500 mW
Max. Passband Ripple	0.3 dB
Max. Polarization Dependent Loss	0.1 dB
Max. Polarization Mode Dispersion	0.1 ps
Min. Directivity	55 dB
Ambient Storage Temperature	-40 to 90° C (-40 to 194° F)
Ambient Operating Temperature	-30 to 75° C (-22 to 167° F)

Stay in Touch

Email

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2026 Ubiquiti, Inc. All rights reserved.