

UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Access

Bridging > [Device Bridge Pro](#)



Device Bridge Pro

UDB-Pro

Datasheet

In The Box

Marketing Images

Accessories

Installation Guide



^ Overview

Dimensions	ø189.5 x 64.3 mm (ø7.4 x 2.5")
WiFi Standard	WiFi 5
Spatial Streams	2
Coverage Area	5 km (3.1 mi)
Mounting Locations	Wall, pole
Mounting	Pole (Included)
Weatherproofing	IPX6

Power Supply	48V, 0.32A PoE adapter (Included)
^ Performance	
MIMO	
5 GHz	2 x 2
Max. Data Rate	
5 GHz	867 Mbps (BW80)
Antenna Gain	
5 GHz	19 dBi
Max. TX Power	
5 GHz	25 dBm
Max. Conducted TX Power	25 dBm (Combined)
Supported Data Rates	
802.11ac (WiFi 5)	6.5 Mbps to 866.7 Mbps (MCS0 - MCS9 NSS1/2, VHT 20/40/80)
802.11n	6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40)
802.11a	6, 9, 12, 18, 24, 36, 48, 54 Mbps
Wireless Security	WPA2 AES
^ Hardware	
Max. Power Consumption	9W
Supported Voltage Range	42.5-57V DC
Networking Interface	(2) GbE RJ45 ports
Antennas	Internal
Management	(1) PoE in (PoE output not used) (1) Passive PoE output
Channel Bandwidth	20/40/80 (MHz)
Wind Loading	69 N at 200 km/h (15.5 lbf at 125 mph)



Enclosure Material	UV-resistant polycarbonate
Mount Material	UV-stabilized polycarbonate, stainless steel
Pole Mount Diameter	0.8-2.1" (20-53.1 mm)
Button	(1) Factory reset
LEDs	
System	Power, (2) Ethernet status - main port/PoE out port, (4) signal strength
NDAA Compliant	✓
Certifications	CE, FCC, IC
Operating Frequency	US/CA: U-NII-1 5150 - 5250 MHz U-NII-2A 5250 - 5350 MHz U-NII-2C 5470 - 5725 MHz U-NII-3 5725 - 5850 MHz Worldwide: 5150 - 5875 MHz 
Ambient Operating Temperature	-40 to 60° C (-40 to 140° F)
Ambient Operating Humidity	5 to 95% noncondensing

Stay in Touch

Email

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)