

UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Access

Large Scale > [Dream Machine Pro Max](#)



Dream Machine Pro Max

UDM-Pro-Max


Datasheet

In The Box

Marketing Images

Accessories

Installation Guide



^ Overview

Dimensions

442.4 x 43.7 x 285.6 mm
(17.4 x 1.7 x 11.2")

UniFi Application Suite

Network <i>i</i>	✓
Protect <i>i</i>	✓
Access <i>i</i>	✓
Talk <i>i</i>	✓
Connect <i>i</i>	✓

Managed Cameras	(50) HD (25) 2K (15) 4K
Managed Access Hubs i	150
Simultaneous Users Connected	2,000+
Max. WAN Port Count	8
Default WAN Ports	(1) 10G SFP+ (1) 2.5 GbE RJ45
Port Layout	
1 GbE RJ45	8 (1G/100M/10M)
2.5 GbE RJ45	1 (2.5G/1G/100M/10M)
10G SFP+	2 (10G/1G)
IDS/IPS Throughput	5 Gbps
Form Factor	Rack mount (1U)
Redundancy	Shadow Mode (VRRP) Gateway Failover DC Power Backup i
^ Security	
Stateful Firewall	✓
Application-Aware Layer 7 Firewall	✓
DPI & Traffic Identification	✓
Zone-Based Firewall Advanced Filtering (Regions, Domains, Apps)	✓
Content Filtering	✓
Intrusion Prevention (IPS/IDS)	✓
Ad Blocking	✓
IDS/IPS Signatures	55,000+ with CyberSecure

^ VPN & SD-WAN

License-Free SD-WAN ✓

Site-to-Site VPN

Site Magic ✓

IPsec ✓

OpenVPN ✓

VPN Server

Identity Endpoint One-Click VPN ✓

Teleport Zero-Configuration VPN ✓

WireGuard ✓

OpenVPN ✓

L2TP ✓

VPN Client

OpenVPN ✓

WireGuard ✓

^ Networking

Multi-WAN Load Balancing ✓

Shadow Mode (VRRP) High Availability ✓

LACP Port Aggregation ✓ ⓘ

Dynamic Routing

OSPF ✓

BGP ✓

Advanced QoS ✓

Multicast DNS (mDNS) ✓

Integrated RADIUS Server	✓
RADIUS over TLS (RadSec)	✓
Additional Internet Failover with UniFi LTE Backup	✓
Internet Quality and Outage Reporting	✓
MAC Address Table Size	4,000
Policy-based WAN and VPN Routing	✓
Customizable DHCP Server	✓
IPv6 ISP Support	✓
IGMP Proxy	✓
Virtual Network Override	✓
All Traffic Flows	✓

^ **Hardware**

NVR Storage	(2) 3.5" NVR HDD bays Built-in 128 GB SSD for Faster Experience
Max. Power Consumption	60W
Power Method	(1) Universal AC input, 100-240V AC, 2A Max., 50/60 Hz (1) USP-RPS DC input, 11.5V DC, 8.7A
Power Supply	AC/DC, internal, 100W
Supported Voltage Range	100-240V AC
Heat Dissipation	205 BTU/hr
Processor	Quad-core ARM® Cortex®-A57 at 2.0 GHz
System Memory	8 GB
On-board Storage	32 GB eMMC 128 GB SSD (Integrated)
Weight	4.7 kg (10.4 lb)
Enclosure Material	Aluminium CNC, SGCC steel



LCM Display	1.3" touchscreen
Management	Ethernet Bluetooth
LEDs	
Ethernet	✓
SFP+	✓
RPS	✓
PSU	✓
HDD	✓
Button	(1) Factory reset
ESD/EMP Protection	Air: ± 15kV, contact: ± 8kV
Ambient Operating Temperature	-10 to 40° C (14 to 104° F)
Ambient Operating Humidity	5 to 95% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC, Anatel: 06369-24-08356, SRRC

Stay in Touch

Email

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2026 Ubiquiti, Inc. All rights reserved.