

UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Access

Aggregation > Enterprise Campus Aggregation



Enterprise Campus Aggregation

ECS-Aggregation




Datasheet

In The Box

Marketing Images

Accessories

Installation Guide



Overview

Dimensions

442.4 x 43.7 x 496 mm
(17.4 x 1.7 x 19.5")

Port Layout

25G SFP28

48
(25G/10G)

100G QSFP28

6
(100G/40G) ⓘ

Redundancy

Multi-Chassis Link Aggregation (MC-LAG)
(2) Hot-Swappable PSUs
(5) Hot-Swappable Fans

Layer 3

✓

Etherlighting™	✓
----------------	---

^ Performance

Switching Capacity	3.6 Tbps
--------------------	----------

Total Non-Blocking Throughput	1.8 Tbps
-------------------------------	----------

Forwarding Rate	2.4 Bpps
-----------------	----------

Supported VLANs	1,000
-----------------	-------

MAC Address Table Size	128,000
------------------------	---------

IPv4 Static Routes	256
--------------------	-----

Packet Buffer Size	24 MB
--------------------	-------

Access Lists

IPv4	512
------	-----

MAC	512
-----	-----

^ Layer 3 Features

DHCP Server (Local Networks)	✓
------------------------------	---

DHCP Relay	✓
------------	---

Inter-VLAN Routing (Local Networks)	✓
-------------------------------------	---

Static Routing (Local Networks)	✓
---------------------------------	---

^ Layer 2 Features

LACP Port Aggregation	✓
-----------------------	---

MC-LAG	✓ ⓘ
--------	-----

STP & RSTP	✓
------------	---

Advanced IGMP Configuration (Querier, Fast Leave, Router Port)	✓
--	---

IGMP Snooping	✓
---------------	---

MAC-Based ACLs & Device Isolation	✓
-----------------------------------	---

DHCP Snooping & Guarding	✓
--------------------------	---

Flow Control	✓
MAC Address Blocking	✓
IP-Based ACLs & Network Isolation	✓
MAC-Based Port Restriction	✓
Port Isolation	✓
Port Mirroring	✓
Jumbo Frames	✓
LLDP-MED	✓
Voice VLAN	✓
Loop Protection	✓
^ Hardware	
Max. Power Consumption	340W
Power Method	(2) Universal input, 100–240V AC, 50/60 Hz
Power Input Method	(2) AC input, Hot-swappable power modules
Power Supply	(2) Hot-swappable AC/DC 550W power modules
Supported Voltage Range	100–240V AC
Management	Ethernet AR
Heat Dissipation	1160 BTU/hr
Weight	Without mounting brackets: 9.9 kg (21.8 lb) With mounting brackets: 10 kg (22 lb)
Enclosure Material	SGCC steel
Mount Material	SGCC steel
Supported Rack Depth	482.6 mm (19") four-post racks Posts depths ranging from 650 to 1,000 mm (25.6–39.4")
LCM Display	1.3" touchscreen
ESD Protection	Air: ± 12kV, contact: ± 8kV



Ambient Operating Humidity	10 to 95% noncondensing
Etherlighting™	
SFP28	✓
QSFP28	✓
LEDs	
PSU	✓
Fan	✓
NDAA Compliant	✓
Certifications	CE, FCC, IC, Anatel: 01327-25-08356
^ Software	
Application Requirements	
UniFi Network	Version 8.5.6 and later

Stay in Touch

Email

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2026 Ubiquiti, Inc. All rights reserved.