

UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Access

Enterprise > Enterprise Campus Switch Core



Enterprise Campus Switch Core




ECS-Core

Datasheet

In The Box

Marketing Images

Installation Guide



Overview

Dimensions

442.4 x 43.7 x 480 mm
(17.4 x 1.7 x 18.9")

Port Layout

1 GbE RJ45

1
(1G/100M/10M) ⓘ

100G QSFP28

32
(100G/40G) ⓘ

Console

1

Redundancy

Multi-Chassis Link Aggregation (MC-LAG)
(2) Hot-Swappable PSUs
(5) Hot-Swappable Fans

Form Factor	Rack Mount (1U, Full-Depth) ⓘ
Etherlighting™	✓
^ Performance	
Switching Capacity	6.4 Tbps
Total Non-Blocking Throughput	3.2 Tbps
Forwarding Rate	2.8 Bpps
Supported VLANs	1,000
MAC Address Table Size	128,000
IPv4 Static Routes	256
Packet Buffer Size	24 MB
Access Lists	
IPv4	512
MAC	512
^ Layer 3 Features	
DHCP Server (Local Networks)	✓
DHCP Relay	✓
Inter-VLAN Routing (Local Networks)	✓
Static Routing (Local Networks)	✓
^ Layer 2 Features	
LACP Port Aggregation	✓
MC-LAG	✓ ⓘ
STP & RSTP	✓
Advanced IGMP Configuration (Querier, Fast Leave, Router Port)	✓
IGMP Snooping	✓
MAC-Based ACLs & Device Isolation	✓

Egress Rate Limit	✓
Flow Control	✓
MAC Address Blocking	✓
IP-Based ACLs & Network Isolation	✓
MAC-Based Port Restriction	✓
Port Isolation	✓
Port Mirroring	✓
Jumbo Frames	✓
LLDP-MED	✓
Voice VLAN	✓
Loop Protection	✓
^ Hardware	
Max. Power Consumption	360W
Power Method	(2) Universal input, 100-240V AC, 50/60 Hz
Power Input Method	(2) AC input, Hot-swappable power modules
Power Supply	(2) Hot-swappable AC/DC 550W power modules
Supported Voltage Range	100-240V AC
Management	Ethernet AR Serial Console
Heat Dissipation	1,228 BTU/hr
Weight	Without mounting brackets: 9.7 kg (21.4 lb) With mounting brackets: 9.8 kg (21.6 lb)
Enclosure Material	SGCC steel
Mount Material	SGCC steel
Supported Rack Depth	482.6 mm (19") four-post racks Posts depths ranging from 650 to 1,000 mm (25.6-39.4")

Fan Method	(5) Hot-swappable fan modules
ESD Protection	Air: ± 12KV; contact: ± 8KV
Ambient Operating Temperature	-5 to 40° C (23 to 104° F)
Ambient Operating Humidity	10 to 90% noncondensing
Etherlighting™	
QSFP28	✓
LEDs	
Ethernet	✓
PSU	✓
Fan	✓
NDAA Compliant	✓
Certifications	CE, FCC, IC
^ Software	
Application Requirements	
UniFi Network	Version 10.6.101 and later

Stay in Touch

Email

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2026 Ubiquiti, Inc. All rights reserved.