

UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Accessories

WiFi Integrated > UniFi Express

UniFi Express

UX

Datasheet



In The Box

Marketing Images

FAQ

Accessories

Installation Guide



^ Overview

Dimensions

98 x 98 x 30 mm
(3.6 x 3.6 x 1.2")

UniFi Application Suite

Network ⓘ	✓
Managed UniFi Devices	4
Simultaneous Users Connected	50+
Max. WAN Port Count	1

Port Layout

1 GbE RJ45	2 (1G/100M/10M)
Form Factor	Compact desktop
Coverage Area	140 m² (1,500 ft²)

^ Security

Stateful Firewall	✓
Application-Aware Layer 7 Firewall	✓
DPI & Traffic Identification	✓
Content Filtering	✓
Ad Blocking	✓

^ VPN & SD-WAN

License-Free SD-WAN	✓
Site-to-Site VPN	
IPsec	✓
OpenVPN	✓

VPN Server

Teleport Zero-Configuration VPN	✓
WireGuard	✓
OpenVPN	✓
L2TP	✓

VPN Client

OpenVPN	✓
WireGuard	✓

^ Networking

Dynamic Routing

Advanced QoS	✓
Multicast DNS (mDNS)	✓
Advanced NAT (SNAT / DNAT / Masquerade / NAT Pooling / 1-to-1 NAT)	✓
Integrated RADIUS Server	✓
RADIUS over TLS (RadSec)	✓
Additional Internet Failover with UniFi LTE Backup	✓
Internet Quality and Outage Reporting	✓
Policy-based WAN and VPN Routing	✓
Customizable DHCP Server	✓
IPv6 ISP Support	✓
IGMP Proxy	✓
Virtual Network Override	✓
^ Integrated WiFi	
WiFi Standard	802.11a/b/g/n/ac/ax (WiFi 6)
Throughput	
5 GHz	2.4 Gbps
2.4 GHz	573.5 Mbps
MIMO	
5 GHz	2 x 2 (DL/UL MU-MIMO)
2.4 GHz	2 x 2 (DL/UL MU-MIMO)
Antenna Gain	
5 GHz	5.15 dBi
2.4 GHz	4 dBi
Max. TX Power	
5 GHz	25 dBm

Wireless Security	WPA-PSK, WPA-Enterprise (WPA/WPA2/WPA3/PPSK)
Max. BSSIDs	3 per Radio (Gateway Mode) 4 per Radio (AP Mode)
Antennas	(2) Internal 2.4G/5G WiFi dual-band antenna (1) Internal 2.4G single-band BT antenna
Supported Data Rates	
802.11ax (WiFi 6)	7.3 Mbps to 2.4 Gbps (MCS0 - MCS11 NSS1/2, HE 20/40/80/160)
802.11ac (WiFi 5)	6.5 Mbps to 1.7 Gbps (MCS0 - MCS9 NSS1/2, VHT 20/40/80/160)
802.11n	6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40)
802.11g	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11b	1, 2, 5.5, 11 Mbps
802.11a	6, 9, 12, 18, 24, 36, 48, 54 Mbps
^ Hardware	
Max. Power Consumption	10W
Power Method	USB type C (5V DC/3A)
Power Supply	USB type C (5V DC/3A) (Adapter included)
Supported Voltage Range	100-240V AC
Heat Dissipation	34 BTU/hr
Processor	Dual-core ARM® Cortex®-A53 at 1 GHz
System Memory	1 GB
Weight	302 g (10.7 oz)
Enclosure Material	Polycarbonate
LCM Display	0.96" status display
Management	Ethernet Bluetooth
Button	(1) Factory reset
Ambient Operating Temperature	-10 to 45° C (14 to 113° F)



NDAA Compliant	✓
Certifications	CE, FCC, IC, Anatel: 21391-23-08356
^ Software	
VLAN	802.1Q
Guest Traffic Isolation	✓
Application Requirements	Version 8.0 and newer.
UniFi Network	Note. UniFi Express will continue to receive updates on UniFi Network 9.0 including critical security updates and select feature enhancements. For UniFi Network 9.1 and higher, please see UniFi Express 7.

Stay in Touch

Email

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2026 Ubiquiti, Inc. All rights reserved.