

UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Access

Utility > Flex



Flex
USW-Flex




Datasheet

In The Box

Marketing Images

Accessories

Installation Guide



Overview

Dimensions	122.5 x 107.1 x 28 mm (4.8 x 4.2 x 1.1")
Port Layout	
1 GbE RJ45	5 (4 PoE+; 1 PoE++) (1G/100M/10M)
Max. PoE Output	Up to PoE+
Total PoE Availability	PoE++/60W PoE adapter input: 46W PoE+ input: 20W PoE input: 8W
Form Factor	Compact desktop, wall, pole

Performance

Total Non-Blocking Throughput	5 Gbps
Forwarding Rate	7 Mpps
Supported VLANs	1,000
MAC Address Table Size	2,000

^ Layer 2 Features

Egress Rate Limit	✓
Flow Control	✓
Port Isolation	✓
Port Mirroring	✓
Jumbo Frames	✓

^ Hardware

PoE Ports

PoE+	4
PoE++	1

Max. PoE Wattage per Port by PSE

PoE+	25W
------	-----

Max. Power Consumption	5W (Excluding PoE Output) 51W (Including PoE Output)
------------------------	---

Power Method	PoE++
--------------	-------

Power Input Method	PoE
--------------------	-----

Supported Voltage Range	50-57V PoE
-------------------------	------------

Management	Ethernet
------------	----------

Heat Dissipation	17.1 BTU/hr (Excluding PoE Output)
------------------	------------------------------------

Outdoor Ready	✓
---------------	---

Weight	230 g (8.1 oz)
--------	----------------

ESD Protection	Air/contact: ± 16kV
----------------	---------------------



Ambient Operating Humidity	5 to 95% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC, Anatel: 14502-20-08356

^ **Software**

Application Requirements

UniFi Network	Version 5.10.3 and later
---------------	--------------------------

Stay in Touch

Email

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2026 Ubiquiti, Inc. All rights reserved.