

UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Access

Aggregation > [Hi-Capacity Aggregation](#)



Hi-Capacity Aggregation

USW-Pro-Aggregation



Datasheet

In The Box

Marketing Images

Accessories

Installation Guide



Overview

Dimensions

442 x 325 x 44 mm
(17.4 x 12.8 x 1.7")

Port Layout

10G SFP+

28
(10G/1G)

25G SFP28

4
(25G/10G/1G)

Redundancy

DC Power Backup ⓘ

Layer 3

✓

^ Performance

Switching Capacity	760 Gbps
Total Non-Blocking Throughput	380 Gbps
Forwarding Rate	565 Mpps
Supported VLANs	1,000
MAC Address Table Size	32,000
IPv4 Static Routes	256
Packet Buffer Size	4 MB
Access Lists	
IPv4	128
MAC	128

^ Layer 3 Features

DHCP Server (Local Networks)	✓
DHCP Relay	✓
Inter-VLAN Routing (Local Networks)	✓
Static Routing (Local Networks)	✓

^ Layer 2 Features

LACP Port Aggregation	✓
STP & RSTP	✓
QoS (DSCP)	✓
Pro AV Profiles (Play, Dante, Q-SYS, NDI, SDVoE, Shure, AES67, Crestron)	✓
Advanced IGMP Configuration (Querier, Fast Leave, Router Port)	✓
IGMP Snooping	✓
802.1X Control	✓

DHCP Snooping & Guarding	✓
Egress Rate Limit	✓
Flow Control	✓
Storm Control	✓
Multicast & Broadcast Rate Limiting	✓
MAC Address Blocking	✓
IP-Based ACLs & Network Isolation	✓
MAC-Based Port Restriction	✓
Port Isolation	✓
Port Mirroring	✓
Jumbo Frames	✓
LLDP-MED	✓
Voice VLAN	✓
Loop Protection	✓
Virtual Network Override	✓
^ Hardware	
Max. Power Consumption	100W
Power Method	(1) Universal input, 100-240V AC, 50/60 Hz (1) USP RPS DC input
Power Input Method	AC input
Power Supply	AC/DC, internal, 100W
Supported Voltage Range	100-240V AC
Management	Ethernet AR
Heat Dissipation	341 BTU/hr
Weight	Without mounting brackets: 4.6 kg (10.1 lb) With mounting brackets: 4.7 kg (10.4 lb)

Mount Material	SGCC steel
Supported Rack Depth	400~1200 mm (15.7-47.2")
LCM Display	1.3" touchscreen
ESD Protection	Air: ± 16kV, contact: ± 12kV
Ambient Operating Temperature	-5 to 40° C (23 to 104° F)
Ambient Operating Humidity	10 to 90% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC, Anatel: 20756-22-08356
^ Software	
Application Requirements	
UniFi Network	Version 6.1.25 and later

Stay in Touch

Email

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2026 Ubiquiti, Inc. All rights reserved.