

UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Access

Utility > Lite 8 PoE



Lite 8 PoE
USW-Lite-8-PoE




Datasheet

In The Box

Marketing Images

Accessories

Installation Guide



Overview

Dimensions

99.6 x 163.7 x 31.7 mm
(4 x 6.4 x 1.3")

Port Layout

1 GbE RJ45

8 (4 PoE+)
(1G/100M/10M)

Max. PoE Output

Up to PoE+

Total PoE Availability

52W ⓘ

Form Factor

Compact desktop, wall

Switching Capacity	16 Gbps
Total Non-Blocking Throughput	8 Gbps
Forwarding Rate	12 Mpps
Supported VLANs	1,000
MAC Address Table Size	8,000
Packet Buffer Size	0.5 MB
Access Lists	
IPv4	128
MAC	128
^ Layer 2 Features	
LACP Port Aggregation	✓
STP & RSTP	✓
Advanced IGMP Configuration (Querier, Fast Leave, Router Port)	✓
IGMP Snooping	✓
802.1X Control	✓
MAC-Based ACLs & Device Isolation	✓
DHCP Snooping & Guarding	✓
Egress Rate Limit	✓
Flow Control	✓
Storm Control	✓
Multicast & Broadcast Rate Limiting	✓
MAC Address Blocking	✓
IP-Based ACLs & Network Isolation	✓
MAC-Based Port Restriction	✓
Port Isolation	✓

Jumbo Frames	✓
LLDP-MED	✓
Voice VLAN	✓
Loop Protection	✓
Virtual Network Override	✓

^ Hardware

PoE Ports

PoE+	4
------	---

Max. PoE Wattage per Port by PSE

PoE+	30W
------	-----

Max. Power Consumption	8W (Excluding PoE Output) 60W (Including PoE Output)
------------------------	---

Power Method	AC/DC Adapter (included)
--------------	--------------------------

Power Input Method	DC input
--------------------	----------

Power Supply	AC/DC, external, 60W
--------------	----------------------

Supported Voltage Range	50-57V DC
-------------------------	-----------

Management	Ethernet
------------	----------

Heat Dissipation	27.3 BTU/hr (Excluding PoE Output)
------------------	------------------------------------

Weight	295 g (10.4 oz)
--------	-----------------

Enclosure Material	Polycarbonate
--------------------	---------------

Mount Material	Polycarbonate
----------------	---------------

Ambient Operating Temperature	-15 to 40° C (5 to 104° F)
-------------------------------	----------------------------

Ambient Operating Humidity	10 to 90% noncondensing
----------------------------	-------------------------

NDAA Compliant	✓
----------------	---

Certifications	CE, FCC, IC, Anatel: 04479-21-08356
----------------	-------------------------------------

^ Software



Stay in Touch

Email

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2026 Ubiquiti, Inc. All rights reserved.