



UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Accessories

RJ45 & Copper > [Long-Range Ethernet Repeater](#)



Long-Range Ethernet Repeater

UACC-LRE

Datasheet

Marketing Images

Installation Guide

^ Overview

Dimensions

196.5 x 93.5 x 39 mm
(7.7 x 3.7 x 1.5")

^ Mechanical

Weight

350 g (12.3 oz)

Enclosure Material

UV stabilized polycarbonate

Mounting Material

Stainless steel

Weatherproofing

IPX5

^ Hardware

Power Method

PoE/PoE+ 2-pairs (Pins 1, 2+; 3, 6-)

Max. Power Consumption

1.5W (Excluding PoE output)

Networking Interface

(2) GbE RJ45 ports

PoE Interface

(1) Passthrough PoE output 2-pairs (pins 1,2+; 3,6-)



Switching Capacity	4 Gbps
Forwarding Rate	1.488 Mpps
Total Available PoE	22.5W
Voltage Range PoE Mode	37—57V DC
ESD/EMP Protection	Air/contact: ± 30kV
DC Sparkover Voltage	90V at 100V/s
Max. Impulse Sparkover Voltage	700V at 1kV/μs
Discharge Current	10kA+
Max. MTU	1,500 bytes
LEDs	
System	Blue: power ON
Ethernet	Green: 1 Gbps Amber: 10/100 Mbps
PoE	Amber: passthrough PoE out
Ambient Operating Temperature	-40 to 80° C (-40 to 176° F)
Ambient Operating Humidity	10 to 95% noncondensing

Stay in Touch

Email

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2026 Ubiquiti, Inc. All rights reserved.