



UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Accessories

SFP & Fiber > [Optical Data Transport](#)



Optical Data Transport

F-POE-G2

Datasheet

Marketing Images

Installation Guide

^ Overview

Dimensions	196.4 x 93.5 x 32.4 mm (7.7 x 3.7 x 1.3")
Enclosure Material	Polycarbonat
Weight	288 g (10.2 oz)
Weatherproofing	IPX5
Surge Protection	Built-in high-current gas discharge tube for DC terminal block and PoE port
Networking Interface	(1) 1 Gbps SFP port (1) DC terminal block (1) DC RJ45 port DC injection (1) GbE PoE port (10/100 MbE not supported)
Input DC voltage	16-57V
DC Output	Terminal block, 24V DC/50V DC, 2-wire



Power Method	DC/50V DC input) passthrough PoE RJ45 port, 2-pair (4, 5+; 7, 8-) (24V DC input), or 4-pair (24V DC/50V DC input) PoE passthrough
Power Consumption	1.5W (Typical)
ESD Protection	± 24kV Contact / Air for Ethernet
Ambient Operating Temperature	-40 to 60° C (-40 to 140° F) ⓘ
Ambient Operating Humidity	10 to 95% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC

Stay in Touch

Email

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2026 Ubiquiti, Inc. All rights reserved.