



UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Access

RJ45 & Copper > [UniFi Patch Cable](#)



UniFi Patch Cable

UACC-Cable-Patch

Datasheet

Marketing Images

^ Overview

Available Lengths	End-to-end: 0.2, 0.4, 1, 2, 3, 5, 8, 12, 15 m (0.7, 1.3, 3.3, 6.6, 9.8, 16.4, 26.2, 39.4, 49.2 ft)
Available Colors	White, Blue, Black
Pack Options	Single Unit (0.2, 0.4, 1, 2, 3, 5, 8, 12, 15 m) 10-Pack (0.2, 0.4, 1, 2, 3 m) 24-Pack (0.2, 0.4, 1, 2 m) 50-Pack (0.2, 0.4 m)
Supported Data Rate	10 GbE
Supported PoE Type	Up to PoE+++
Connector	(2) Bendable booted RJ45
Operating Environment	Indoor
Cable	
Jacket Diameter	0.2–8 m (0.7–26.2 ft): 2.5 mm (0.1") 12–15 m (39.4–49.2 ft): 2.9 mm (0.11")



Shielding Type	UTP
Conductor Type	Stranded copper
Conductor Wire Gage	0.2-8 m (0.7-26.2 ft): 34 AWG 12-15 m (39.4-49.2 ft): 32 AWG
Bendable Boot	Max. $\pm 90^{\circ}$ / $\pm 45^{\circ}$ (vertical/horizontal)
Bend Radius	0.2-8 m (0.7-26.2 ft): Min. 21 mm (0.83") 12-15 m (39.4-49.2 ft): Min. 24 mm (0.94")
Flame Rating	VW-1 (UL1581)
Standards	TIA/EIA-568-B.2 ISO/IEC 11801
Installation Temperature	-20 to 60°C (-4 to 140°F)
Ambient Storage Temperature	-20 to 75°C (-4 to 167°F)
Ambient Operating Temperature	-20 to 60°C (-4 to 140°F)
NDAA Compliant	✓

Stay in Touch

Email

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2026 Ubiquiti, Inc. All rights reserved.