

UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Access

Professional > Pro 24 PoE



Pro 24 PoE
USW-Pro-24-POE



Datasheet

In The Box

Marketing Images

Accessories

Installation Guide



Overview

Dimensions

442 x 285 x 44 mm
(17.4 x 11.2 x 1.7")

Port Layout

1 GbE RJ45

24 (16 PoE+; 8 PoE++)
(1G/100M/10M)

10G SFP+

2
(10G/1G)

Max. PoE Output

Up to PoE++

Total PoE Availability

400W

Layer 3	✓
Form Factor	Rack mount (1U)

^ Performance

Switching Capacity	88 Gbps
Total Non-Blocking Throughput	44 Gbps
Forwarding Rate	65 Mpps
Supported VLANs	1,000
MAC Address Table Size	16,000
IPv4 Static Routes	2
Packet Buffer Size	2 MB
Access Lists	
IPv4	128
MAC	128

^ Layer 3 Features

DHCP Server (Local Networks)	✓
DHCP Relay	✓
Inter-VLAN Routing (Local Networks)	✓
Static Routing (Local Networks)	✓

^ Layer 2 Features

LACP Port Aggregation	✓
STP & RSTP	✓
QoS (DSCP)	✓
Pro AV Profiles (Play, Dante, Q-SYS, NDI, SDVoE, Shure, AES67, Crestron)	✓
Advanced IGMP Configuration (Querier, Fast Leave, Router Port)	✓



802.1X Control	✓
MAC-Based ACLs & Device Isolation	✓
DHCP Snooping & Guarding	✓
Egress Rate Limit	✓
Flow Control	✓
Storm Control	✓
Multicast & Broadcast Rate Limiting	✓
MAC Address Blocking	✓
IP-Based ACLs & Network Isolation	✓
MAC-Based Port Restriction	✓
Port Isolation	✓
Port Mirroring	✓
Jumbo Frames	✓
LLDP-MED	✓
Voice VLAN	✓
Loop Protection	✓
Virtual Network Override	✓
^ Hardware	
PoE Ports	
PoE+	16
PoE++	8
Max. PoE Wattage per Port by PSE	
PoE	15.4W
PoE+	30W
PoE++	60W



Power Method	(1) Universal input, 100-240V AC, 50/60 Hz (1) USP RPS DC input
Power Input Method	AC input
Power Supply	AC/DC, internal, 450W
Supported Voltage Range	100-240V AC
Management	Ethernet AR
Heat Dissipation	170.6 BTU/hr (Excluding PoE Output)
Weight	Without mounting brackets: 4.3 kg (9.5 lb) With mounting brackets: 4.4 kg (9.7 lb)
Enclosure Material	SGCC steel
Supported Rack Depth	400~1200 mm (15.7-47.2")
LCM Display	1.3" touchscreen
ESD Protection	Air: ± 16kV, contact: ± 12kV
Ambient Operating Temperature	-5 to 40° C (23 to 104° F)
Ambient Operating Humidity	10 to 90% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC, Anatel: 13790-20-08356

^ **Software**

Application Requirements	
UniFi Network	Version 5.10.5 and later

Stay in Touch



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2026 Ubiquiti, Inc. All rights reserved.