

UniFi UISP Branding

Q

Search UniFi products

Cloud Gateways Switching WiFi Physical Security Door Access Integrations Access

Utility > Ultra 60W



Ultra 60W
USW-Ultra-60W


Datasheet

In The Box

Marketing Images

Accessories

Installation Guide



Overview

Dimensions	203 x 76 x 33 mm (8 x 3 x 1.3")
Port Layout	
1 GbE RJ45	8 (7 PoE+; 1 PoE++ input) (1G/100M/10M) ⓘ
Max. PoE Output	Up to PoE+
Total PoE Availability	PoE++ input: 42W PoE+ input: 16W 60W PoE adapter input: 42W



Form Factor	Compact desktop, wall, magnetic
^ Performance	
Switching Capacity	16 Gbps
Total Non-Blocking Throughput	8 Gbps
Forwarding Rate	12 Mpps
Supported VLANs	256
MAC Address Table Size	4,000
^ Layer 2 Features	
STP & RSTP	✓
Egress Rate Limit	✓
Flow Control	✓
Storm Control	✓
Multicast & Broadcast Rate Limiting	✓
Port Isolation	✓
Port Mirroring	✓
Jumbo Frames	✓
Loop Protection	✓
^ Hardware	
PoE Ports	
PoE+	7
PoE++	1
Max. PoE Wattage per Port by PSE	
PoE+	30W
Max. Power Consumption	9W (Excluding PoE Output) with PoE input 8W (Excluding PoE Output) with adapter input 210W (Including PoE Output) with 210W AC adapter input



Power Input Method	DC Input PoE
Power Supply	AC/DC, external, 60W
Supported Voltage Range	50-57V DC/PoE
Management	Ethernet
Heat Dissipation	31 BTU/hr (Excluding PoE Output)
Weight	Device: 320 g (11.3 oz) Wall mount: 45 g (1.6 oz) Adapter: 330 g (11.6 oz)
Enclosure Material	Polycarbonate
Ambient Operating Temperature	PoE++ input: -30 to 60° C (-22 to 140° F) 60W AC adapter input: -20 to 45° C (-4 to 113° F)
Ambient Operating Humidity	10 to 90% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC, Anatel: 06367-24-08356

^ **Software**

Application Requirements

UniFi Network	Version 8.0.7 and later
---------------	-------------------------

Stay in Touch

Email

Subscribe



