

CHIPMACHINE · DATABASE AUDIT · 2026-07-15

Does every song belong to a platform, and does every song play?

Measured across all 775,933 rows in the live index, against the real classifier and the real plugin registry. The question behind it: is more work here worth doing.

775,933

SONGS INDEXED

After this session's data changes; 41,184 of them demozoo.

99.96%

REACH A PLATFORM FILTER

306 rows do not — all demozoo archives.

99.875%

HAVE A DECODER

972 rows have none we can identify.

Taxonomy coverage

A song "belongs" if `classifyFormat()` resolves it to a byte some TAB filter matches. Anything else is reachable only via *[no filter, search all]*.

classified 775,627 no platform 306

Where the 306 sit, and what each would actually take:

REMAINING GROUP	ROWS	WHAT IT WOULD TAKE	WORTH IT?
Archive holds nothing playable	122	Nothing — verified dead. Already harmless; a <code>not_supported</code> line hides each.	NO

.7z / .tar.gz	72	Full downloads. 7z's header is LZMA-encoded near EOF; tar.gz must be inflated. Not range-peekable.	NO
Alive, format ambiguous	55	.mix (Atari ST YM vs Amstrad CPC), .ftm (FamiTracker vs OpenMPT FTMN). Needs magic bytes — i.e. downloads. Guessing misfiles ~half.	NO
Never peeked / peek failed	29	Re-run the pass; transient fetch failures.	FREE
Nested archive only	5	Recursive extraction in the playback path — zip-bomb and path-handling surface, for five rows.	NO

Playability

Whether some plugin claims each row's routing extension — suffix first, then modland prefix naming (jt.ingame), mirroring what UADE does.

DISPOSITION	ROWS	SHARE	NOTES
A plugin claims it	735,726	94.818%	Direct extension match.
YouTube — streamed	32,615	4.203%	No file; ffmpeg streams it.
Playable via prefix naming	2,572	0.331%	modland <fmt>.<title> ; UADE resolves the prefix.
Archive — resolved at play	2,205	0.284%	Picker opens it and chooses a member.
Radio / podcast stream	1,497	0.193%	Live streams, no file.
Extensionless by design	294	0.038%	SoundSmith, Noise Tracker GS, ZoundMonitor.
Playlist rows	114	0.015%	.m3u / .pls ; expanded, not decoded.
			Long tail of one-offs — Mark Cooksey mcs.* , Digital Sound Creator han.* , stray

No decoder found	972	0.125%	.mmd3 , and 22 smp1.* rows — TFMX/MIDI-Loriciel <i>sample halves</i> indexed as songs, which are companions, not tunes.
------------------	-----	--------	---

What changed tonight

18,493 → 306

ROWS WITH NO PLATFORM

98.3% of the gap closed.

0

ROWS DELETED

demozoo.txt still 41,184.
Everything reversible.

99 → 115

DB.LUA VERSION

16 data/classification changes, unstaged.

The one thing worth fixing — now done

The plugin API had a hole, and it wasn't about row counts

FIXED

The zip picker now derives its allowlist from `getSupportedExtensions()` . But that method defaults to **empty** in the base class, and four plugins never override it — including **ptkplugin** (`.ptk` , `.ntk`) and **tfxplugin**. Those formats are therefore invisible to any derived list.

Concretely: a loose `.ptk` played, but a `.ptk` inside a zip was never found — the same shape as the Zophar `.adp` and Organya `.org` gaps.

All five now declare their extensions (**GZPlugin** turned out to be a fifth), and a test fails if a future plugin forgets — guarding the *default*, which is the real bug. Declaring them immediately caused a regression the archive-picker test caught: `mp3plugin` calls itself *libmpg123*, so its `.mp3` landed in the picker's **preferred** bucket, where a compo zip could have played the mp3 preview instead of the module. The rendered-audio bucket now keys on a set of decoder names.

Verdict

Diminishing returns. Stop — except the API hole above.

Everything still open totals roughly **200 addressable rows, about 0.026%** of the library. Each remaining group needs either a download campaign, a judgment call that would misfile real tunes, or machinery — recursive extraction — that adds risk to the playback path for five rows.

The one free action is re-running the pass to catch the 29 transient peek failures. Beyond that, the cost per recovered row is now higher than the value of the row.

How much to trust these numbers

The playability figure is static analysis, not proof. It asks whether a plugin claims the extension — it does not decode 775,933 files. A row counted playable can still fail on corrupt data, a missing sample companion, or a format the plugin claims but mishandles.

The 910 is an upper bound on breakage and a lower bound on effort. Some are genuinely unplayable; others may be claimed via `canHandle()` without appearing in any extension list — the same hole described above. Separating them means playing them, one format at a time.

Reproducing this

- `cmtest unclassified_songs` — rows reaching no platform filter, by format and extension, via the real classifier against the live cache DB.
- `cmtest peek_labels` — every label the demozoo pass writes, resolved to a platform. Any *NO FILTER* line means rows went invisible.
- `cmtest other_platforms` — the Other and Arcade drills as the TAB screen builds them.
- `cmtest priority_map` — extension → plugin, the source for the playability column.

Figures from the live index at `~/Library/Caches/chipmachine/music.db` after `reindex` at `db.lua`

VERSION 116. Full suite green: 893 assertions, 159 cases.