

Rubber Article - Template Documentation


v.0.3.1

Contents

Example Usage	1
Styling functions	1
appendix	1
article	2
Constructor functions	7
ctable	7
maketitle	8

Example Usage

```
1 #import "@preview/rubber-article:0.3.1": *
2 #show: article.with()
3 #maketitle(
4   title: "The Title of the Paper",
5   authors: ("Authors Name",),
6   date: datetime.today().display("[day].[month].[year]"),
7 )
```

 Typst

Styling functions

These functions are used to style certain elements of the document. They are usually called with a `#show` statement. They do not output any content, but rather modify the appearance of the document.


- `appendix()`
- `article()`

appendix

Function to format the Appendix. This function is intended to be used after the document has been styled with the `article` function.

Example usage:

```
1 #show: article.with()
2 // A lot of content goes here...
3
4 #show: appendix.with(
5   title: "Appendix",
6   title-align: center,
7 )
```

 Typst

Parameters

```
appendix(  
    numbering: none str function ,  
    title: none str content ,  
    title-align: alignment ,  
    title-size: length ,  
    numbering-start: int ,  
    content  
) -> content
```

numbering none or str or function

The numbering of the Appendix

Default: "A.1"

title none or str or content

The title of the Appendix

Default: none

title-align alignment

The alignment of the title

Default: center

title-size length

The size of the title

Default: none

numbering-start int

Startting the appendix after this number


Default: 0

article

A Template recreating the look of the classic Article Class.

Example usage:

```
1 #show: article.with(  
2   lang: "de",  
3 )
```

 Typst

This will format the document with the specified options. For more styling options, explore the following parameters.

Parameters

```
article(  
  lang: str,  
  eq-numbering: str none,  
  eq-chapterwise: bool,  
  text-size: length,  
  page-numbering: none str function,  
  page-numbering-align: alignment,  
  heading-numbering: none str function,  
  margins: auto relative dictionary,  
  enum-indent: length,  
  list-indent: length,  
  show-header: bool,  
  alternating-header: bool,  
  first-page-header: int float,  
  header-title: str content,  
  justify: bool,  
  appendix: content,  
  appendix-numbering: none str function,  
  bibliography: content,  
  bib-title: str content,  
  fig-caption-width: relative,  
  header-line-stroke: length,  
  content: content  
) -> content
```

lang str

Set the language of the document.

Default: "de"

eq-numbering str or none

Set the equation numbering style.

Default: none

eq-chapterwise bool

Chapterwise numbering of equations.

Default: false

text-size length

Set the text size. Headings are adjusted automatically.

Default: 10pt

page-numbering `none` or `str` or `function`

Set the page numbering style.

Default: `"1"`

page-numbering-align `alignment`

Set the page numbering alignment.

Default: `center`

heading-numbering `none` or `str` or `function`

Set the heading numbering style.

Default: `"1.1"`

margins `auto` or `relative` or `dictionary`

Set the margins of the document.

Default: (left: `25mm`, right: `25mm`, top: `30mm`, bottom: `30mm`)

enum-indent `length`

Set the Enum indentation.

Default: `1.5em`

list-indent `length`

Set the List indentation.

Default: `1.5em`

show-header `bool`

Set if the default header should be used.

Default: `false`

alternating-header `bool`

Set if the default header should be alternating.

Default: `true`

first-page-header `int` or `float`

Set the first page of the header.

Default: `1`

header-title `str` or `content`

Set the Header Titel

Default: `none`

justify `bool`

Set if document should be justified.

Default: `true`

appendix `content`

Add an appendix to the document.

Default: `none`

appendix-numbering `none` or `str` or `function`

Set the appendix numbering style.

Default: `"A.1"`

bibliography `content`

Add a bibliography to the document.

Default: `none`

bib-title `str` or `content`

Set the title of the bibliography.

Default: `"Bibliography"`

fig-caption-width `relative`

Set the width of the figure captions.

Default: `75%`

header-line-stroke `length`

Set the width of the headerline.

Default: `.6pt`

Constructor functions

These functions are used to create certain elements of the document. They can be called with certain arguments and output some content.


- `ctable()`
- `maketitle()`

ctable

This function will display a custom table. The table uses the `pillar` package under the hood to interact with the table in a similar manner as in LaTeX. This means, that the columns and vertical lines can be defined with a string. Furthermore, the table automatically adds 3 horizontal lines.

Example usage:

```
1 #ctable(  
2   cols:"l|cr",  
3   [A], [B], [C],  
4   ..range(1,16).map(str),  
5 )
```

 Typst

Parameters

```
ctable(  
  ..data,  
  cols: string,  
  stroke: length,  
  middle-stroke: length,  
  vertical-stroke: length,  
  header-rows: int  
) -> content
```

cols `string`

A string that defines the columns and vertical lines of the table.

Default: `"ccc"`

stroke `length`

The linesyle of the table, especially the top and bottom horizontal lines.

Default: `.75pt`

middle-stroke `length`

The linesyle of the middle horizontal line.

Default: `.6pt`

vertical-stroke `length`

The linesyle of the vertical lines.

Default: `.75pt`

header-rows `int`

The number of header rows.


Default: `1`

maketitle

This function will display the frontmatter of the document. This includes the title, authors, and date.

Example usage:

```
1 #maketitle(  
2   title: "The Title of the Paper",  
3   authors: ("Authors Name",),  
4   date: "2025-01-01",  
5 )
```

 Typst

Parameters

```
maketitle(  
  title: string content ,  
  authors: array ,  
  date: string content datetime ,  
  metadata: bool  
) -> content
```

title `string` or `content`

The title of the document.

Default: `""`

authors `array`

The authors of the document.

Default: `()`

date `string` or `content` or `datetime`

The date of the document.

Default: `none`

metadata `bool`

Use title and author information for the document metadata.

Default: `true`