
Table of Contents

INSTRUCTIONS:	1
1) pure phase-locked sine wave	1
2) pure non-phase-locked sine wave	2
3) multisine waves	3
Question: What can you change in the code above to make the EEG	4
Question: Which of the plots look different for phase-locked vs. non-phase-locked?	4
4) nonstationary sine waves	4
5) transient oscillations w/ Gaussian	5
6) repeat #3 with white noise	6
7) repeat #5 with 1/f noise	7
1/f noise	8

Please note that this project is from a course by Mike x Cohen

INSTRUCTIONS:

The goal of this assignment is to simulate time series data that can be used to test time-series analysis methods. For each section below: 1) Complete the MATLAB code 2) Put the data into the EEG structure - Make sure all relevant fields are accurate (EEG.data, EEG.pnts, EEG.trials, EEG.srate, EEG.nbchan, EEG.times) 3) Use function plot_simEEG to plot some data

1) pure phase-locked sine wave


```
% parameters
EEG.srate = 500; % sampling rate in Hz
EEG.pnts = 1500;
EEG.trials = 30;
EEG.nbchan = 23;

sinefreq = 6.75; % in Hz

% time vector
EEG.times = (0:EEG.pnts-1)/EEG.srate;

% loop over channels and create data
for chani=1:EEG.nbchan
    for triali=1:EEG.trials
        % data as a sine wave
        EEG.data(chani,:,triali) = sin(2*pi*sinefreq*EEG.times);
    end
end

% the function below takes at least one argument (EEG),
% and optionally a second argument (channel number),
% and optionally a third argument (figure number)
plot_simEEG(EEG,2,1)
```




2) pure non-phase-locked sine wave

```
% hint: copy/paste the code above but add something inside the sine
%       function on each trial.

% loop over channels and create data
for chani=1:EEG.nbchan
    for triali=1:EEG.trials
        % data as a sine wave
        EEG.data(chani,:,triali) = sin(2*pi*sinefreq*EEG.times +
            2*pi*rand);
    end
end

% the function below takes at least one argument (EEG),
% and optionally a second argument (channel number),
% and optionally a third argument (figure number)
plot_simEEG(EEG,2,2)
```



3) multisine waves

```
% list of frequencies and corresponding amplitudes
frex = [ 3 5 16 ];
amps = [ 2 4 5 ];

% loop over channels and trials
for chani=1:EEG.nbchan
    for triali=1:EEG.trials

        % hint: copy code from video "Three important equations..."
        sinewave = zeros(1,EEG.pnts);
        for si=1:numel(frex)
            sinewave = sinewave +
            amps(si)*sin(2*pi*frex(si)*EEG.times);
        end

        % data as a sine wave
        EEG.data(chani,:,triali) = sinewave;
    end
end

plot_simEEG(EEG,2,3)
```


Question: What can you change in the code above to make the EEG

activity non-phase-locked over trials?

Question: Which of the plots look different for phase-locked vs. non-phase-locked?

(Hint: plot them in different figures to facilitate comparison.

Are you surprised about the differences?



4) nonstationary sine waves

```
% loop over channels and trials
for chani=1:EEG.nbchan
    for triali=1:EEG.trials


        % hint: instantaneous frequency via interpolated random
        numbers
        freqmod = 20*interp1(rand(1,10),linspace(1,10,EEG.pnts));
        signal = sin( 2*pi * (EEG.times + cumsum(freqmod)/
EEG.srate) );
```

```

        EEG.data(chani,:,triali) = signal;
    end
end

plot_simEEG(EEG,2,4)

```



5) transient oscillations w/ Gaussian

```

% Gaussian and sine parameters
peaktime = 1; % seconds
width    = .12;
sinefreq = 7; % for sine wave

% create Gaussian taper
gaus = exp( -(EEG.times-peaktime).^2 / (2*width^2) );

% loop over channels and trials
for chani=1:EEG.nbchan
    for triali=1:EEG.trials

        % trial-unique sine wave
        cosw = cos(2*pi*sinefreq*EEG.times);

        EEG.data(chani,:,triali) = cosw .* gaus;
    end
end


```

```

end
end

plot_simEEG(EEG,2,5)

```



6) repeat #3 with white noise

```

% list of frequencies and corresponding amplitudes
frex = [ 3 5 16 ];
amps = [ 2 4 5 ];

% loop over channels and trials
for chani=1:EEG.nbchan
    for triali=1:EEG.trials

        % hint: copy code from monday2
        sinewave = zeros(1,EEG.pnts);
        for si=1:numel(frex)
            sinewave = sinewave +
                amps(si)*sin(2*pi*frex(si)*EEG.times);
        end

        % data as a sine wave plus noise
        EEG.data(chani,:,triali) = sinewave + 5*randn(size(sinewave));
    end
end


```

```

end
end

plot_simEEG(EEG,2,6)

```



7) repeat #5 with 1/f noise

```

% amount of noise
noiseamp = .3;

peakttime = 1; % seconds
width     = .12;
sinefreq  = 7; % for sine wave

% create Gaussian taper
gaus = exp( -(EEG.times-peakttime).^2 / (2*width^2) );

% loop over channels and trials
for chani=1:EEG.nbchan
    for triali=1:EEG.trials

        % trial-unique sine wave
        cosw = cos(2*pi*sinefreq*EEG.times + 2*pi*rand);
    end
end

```

1/f noise


```
ed = 50; % exponential decay parameter
as = rand(1,floor(EEG.pnts/2)-1) .* exp(-
(1:floor(EEG.pnts/2)-1)/ed);
as = [as(1) as 0 as(:,end:-1:1)];

% Fourier coefficients
fc = as .* exp(1i*2*pi*rand(size(as)));

% inverse Fourier transform to create the noise
noise = real(ifft(fc)) * EEG.pnts;

% data as signal + noise
EEG.data(chani,:,triali) = cosw .* gaus + noiseamp*noise;
end
end

plot_simEEG(EEG,2,7)
```



Published with MATLAB® R2020b