

Node.js

From Wikipedia, the free encyclopedia

Node.js is an open source, cross-platform runtime environment for server-side and networking applications. Node.js applications are written in JavaScript, and can be run within the Node.js runtime on OS X, Microsoft Windows, Linux, FreeBSD, NonStop, IBM AIX, IBM System z and IBM i. Its work is hosted and supported by the Node.js Foundation,^[4] a Collaborative Project at Linux Foundation.^[5]

Node.js provides an event-driven architecture and a non-blocking I/O API that optimizes an application's throughput and scalability. These technologies are commonly used for real-time web applications.

Node.js uses the Google V8 JavaScript engine to execute code, and a large percentage of the basic modules are written in JavaScript. Node.js contains a built-in library to allow applications to act as a Web server without software such as Apache HTTP Server or IIS.

Node.js is gaining adoption as a server-side platform^[6] and is used by IBM,^[7] Microsoft,^{[8][9]} Yahoo!,^[10] Walmart,^[11] Groupon,^[12] SAP,^[13] LinkedIn,^{[14][15]} Rakuten, PayPal,^{[16][17]} Voxer,^[18] and GoDaddy.^[19]

node.js



Original author(s)	Ryan Dahl
Developer(s)	Node.js Developers (https://github.com/ry/node/blob/master/AUTHORS), Joyent, GitHub Contributors (https://github.com/joyent/node/graphs/contributors)
Initial release	May 27, 2009 ^[1]
Stable release	0.12.4 / May 23, 2015 ^[2]
Preview release	0.11.16 / January 29, 2015 ^[3]
Development status	Active
Written in	C, C++, JavaScript
Operating system	OS X, Linux, Solaris, FreeBSD, OpenBSD, Microsoft Windows (older versions require Cygwin), webOS, NonStop OS
Type	Event-driven networking
License	MIT
Website	nodejs.org (https://nodejs.org)

Contents

- 1 History
- 2 Overview
- 3 Technical
 - 3.1 Threading
 - 3.2 V8
 - 3.3 Package management
 - 3.4 Unified API
 - 3.5 Event loop

- 4 Tools
- 5 Alternatives
 - 5.1 io.js
 - 5.2 JXcore
 - 5.3 Other languages
- 6 See also
- 7 References
- 8 Further reading
- 9 External links

History

Node.js was invented in 2009 by Ryan Dahl, and other developers working at Joyent.^[20] Node.js was created and first published for Linux use in 2009. Its development and maintenance was spearheaded by Ryan Dahl and sponsored by Joyent, the firm where Dahl worked.^[21]

Dahl was inspired to create Node.js after seeing a file upload progress bar on Flickr. The browser did not know how much of the file had been uploaded and had to query the Web server. Dahl desired an easier way.^[22]

It garnered international attention after its debut at the inaugural European JSConf on November 8, 2009.^{[23][24][25]} Dahl presented Node.js, which combined Google's V8 JavaScript engine, an event-loop, and a low-level I/O API.^[20] The project received a standing ovation, and has since then experienced significant growth, popularity and adoption.^[20]

In 2011, a package manager was introduced for Node.js library, called *npm*. The package manager allows publishing and sharing of open-source Node.js libraries by the community, and simplifies installation, updating and uninstallation of libraries.^[20]


In June 2011, Microsoft partnered with Joyent to implement a native Windows version of Node.js.^[26] The first Node.js build to support Windows was released in July.

In January 2012, Dahl stepped aside, promoting coworker and *npm* creator Isaac Schlueter to manage the project.^[27]

In January 2014, Schlueter announced Timothy J. Fontaine would be Node.js's new project lead.^[28]

In December 2014, Fedor Indutny started io.js, a fork of Node.js. Due to internal conflict over Joyent's governance, io.js was created as an open governance alternative with a separate technical committee.^[29]

In February 2015, the intent to form a neutral Node.js Foundation was announced. By June 2015, the Node.js and io.js community voted to work together under the Node.js Foundation^[30]



Ryan Dahl, creator of Node.js

Overview

Node.js allows the creation of web servers and networking tools, using JavaScript and a collection of "modules" that handle various core functionality.^{[20][23][31][32][33]} Modules handle file system I/O, networking (HTTP, TCP, UDP, DNS, or TLS/SSL), binary data (buffers), cryptography functions, data streams, and other core functions.^{[20][32][34]} Node's modules have a simple and elegant API, reducing the complexity of writing server applications.^{[20][32]}

Frameworks can be used to accelerate the development of applications, and common frameworks are Express.js, Socket.io and Connect.^{[20][35]} Node.js applications can run on Microsoft Windows, Unix and Mac OS X servers. Node.js applications can alternatively be written with CoffeeScript^[36] (a more readable form of JavaScript), Dart or Microsoft TypeScript (strongly typed forms of JavaScript), or any language that can compile to JavaScript.^[36]

Node.js is primarily used to build network programs such as web servers, making it similar to PHP and Python.^[31] The biggest difference between PHP and Node.js is that PHP is a blocking language (commands execute only after the previous command has completed), while Node.js is a non-blocking language (commands execute in parallel, and use callbacks to signal completion).^[31]

Node.js brings event-driven programming to web servers, enabling development of fast web servers in JavaScript.^[20] Developers can create highly scalable servers without using threading, by using a simplified model of event-driven programming that uses callbacks to signal the completion of a task.^[20] Node.js was created because concurrency is difficult in many server-side programming languages, and often leads to poor performance.^[23] Node.js connects the ease of a scripting language (JavaScript) with the power of Unix network programming.^[20]

Node.js is built on the Google V8 JavaScript engine, because:^[23]

- V8 is open-source under the BSD license
- V8 is extremely fast
- V8 is focused on the web, so is proficient with internet fundamentals like HTTP, DNS, TCP
- JavaScript is a well-known language within web development, making it accessible to many web developers

Thousands of open-source libraries have been built for Node.js, and can be downloaded for free from the npm website. Node.js has a developer community centered around two mailing lists and the IRC channel #node.js on freenode. The community gathers at NodeConf (<http://nodeconf.com/>), an annual developer conference focused on Node.js.^[37]

Technical

Threading

Node.js operates on a single thread, using non-blocking I/O calls, allowing it to support tens of thousands of concurrent connections without incurring the cost of thread context-switching. The design of sharing a single thread between all the requests means it can be used to build highly concurrent applications. The design goal of a Node.js application is that any function performing I/O must use a callback.

A downside of this approach is that Node.js doesn't allow scaling with the number of CPU cores of the machine it is running on without using an additional module such as cluster (<https://nodejs.org/api/cluster.html>), StrongLoop Process Manager (<http://strong-pm.io/>), or pm2 (<https://github.com/Unitech/pm2>).

V8

V8 is the JavaScript execution engine built for Google Chrome, open-sourced by Google in 2008. Written in C++, V8 compiles JavaScript source code to native machine code instead of interpreting it in real time.

Node.js contains libuv to handle asynchronous events. V8 provides the run-time for JavaScript. Libuv is an abstraction layer for network and file system functionality on both Windows and POSIX-based systems like Linux, Mac OS X and Unix.

The core functionality of Node.js resides in a JavaScript library. The Node.js bindings, written in C++, connect these technologies to each other and to the operating system.

Package management

npm is the pre-installed package manager for the Node.js server platform. It is used to install Node.js programs from the npm registry. By organizing the installation and management of third-party Node.js programs, it helps developers build faster. npm is not to be confused with the CommonJS require() statement. It is not used to load code: instead, it is used to install code and manage code dependencies from the command line. The packages found in the npm registry can range from simple helper libraries like Underscore.js to task runners like Grunt (<http://gruntjs.com/>)..

Unified API

Node.js combined with a browser, a document DB (such as MongoDB or CouchDB) and JSON offers a unified JavaScript development stack. With the increased attention to client-side frameworks and the adaptation of what were essentially server-side development patterns like MVC, MVP, MVVM, etc., Node.js allows the reuse of the same model and service interface between client-side and server-side.

Event loop

Node.js registers itself with the operating system so that it is notified when a connection is made. When a connection is made, the operating system will issue a callback. Within the Node.js runtime, each connection is a small heap allocation. Traditionally, relatively heavyweight OS processes or threads handled each connection. Node.js, however, uses an event loop, instead of processes or threads, to scale to millions of connections happening at the same time.^[38] In contrast to other event-driven servers, Node.js's event loop does not need to be called explicitly. Instead callbacks are defined, and the server automatically enters the event loop at the end of the callback definition. Node.js exits the event loop when there are no further callbacks to be performed.

Tools

Desktop IDEs

- Atom (free open-source)
- Brackets (free open-source)
- Sublime Text (commercial)
- JetBrains IntelliJ IDEA (commercial)
- JetBrains WebStorm (commercial)
- Microsoft Visual Studio with Node.js Tools for Visual Studio^[39] (commercial)
- Microsoft Visual Studio with TypeScript (commercial)
- Nodeclipse Enide Studio (free open-source, Eclipse-based)
- NoFlo – flow-based programming environment integrated with GNOME APIs^[40]
- Visual Studio Code (cross platform, free)

Online code editors

- Koding (cloud service)
- Codenvy IDE (cloud service)
- Cloud9 IDE (cloud service)
- Codiad (<http://codiad.com/>) (Self hosted service)

Runtimes and debuggers

- Microsoft Visual Studio (commercial) with Node.js Tools for Visual Studio (free)
- Microsoft WebMatrix (free)

Application performance management

- ruxit (<https://ruxit.com/features/apm/nodejs.html>) (cloud service, commercial) – SaaS based APM solution^[41]

Frameworks

- Server frameworks : Express.js, Socket.io, Koa.js (<http://koa.js.com/>), Hapi.js (<http://hapijs.com/>), Total.js^{[42][43]}
- MVC frameworks : Meteor (<http://www.meteor.com>), Derby (<http://derbyjs.com/>), Sails (<http://sailsjs.org/>), Mean (<http://mean.io>), MeanJS (<http://meanjs.org>), Tower.js (<http://towerjs.org/>), Nombo (<http://nombo.io/>), Geddy (<http://geddyjs.org>), Compound (<http://compoundjs.com/>), Yahoo! Mojito (<https://developer.yahoo.com/cocktails/mojito/>)

Social network

- Node.js World (<http://nodejsworld.com/>) is a social networking website where Node.js developers can interact, chat, follow each other, desktop notification, share tutorials, etc.

Alternatives

io.js

io.js is a fork of Node.js, started in December 2014,^[29] by a contributor to the Node.js project.^[47] It is expected to be marked stable in March 2015.^[48] The reason for forking away from Node.js, was that the authors wanted a project outside corporate governance, and have therefore created an "open governance" system consisting of a technical committee which the authors are part of.^[47]

Like Node.js, it is an open source, cross-platform runtime environment for server-side and networking applications. io.js applications are written in JavaScript, and can be run within the io.js runtime on OS X, Microsoft Windows, and Linux. io.js provides an event-driven architecture and a non-blocking I/O API that optimizes an application's throughput and scalability.

io.js uses the Google V8 JavaScript engine to execute code, but unlike Node.js^[49] plans are to keep it up-to-date with latest releases of this engine.^[48]

As of the week of May 15, 2015, the io.js organization has voted and officially agreed to merge back with the Node.js project under the rubric of a new foundation, the Node Foundation.^[50] The combined organization will be named 'nodejs'.

JXcore

JXcore is a fork of Node.js targeting mobile devices and IoTs. Its first beta was released in January 2014. It was open sourced^[51] on February 13, 2015 and made available through a GitHub repository (<https://github.com/jxcore/jxcore>). JXcore can use both Google V8 and Mozilla SpiderMonkey as its JavaScript engine. As a result, JXcore can run Node applications on iOS devices using Mozilla SpiderMonkey.

io.js



Original author(s)	Fedor Indutny
Developer(s)	io.js Developers (https://github.com/iojs/io.js/blob/master/AUTHORS), GitHub Contributors (https://github.com/iojs/io.js/graphs/contributors)
Initial release	January 14, 2015 ^[44]
Stable release	2.0.1 / May 7, 2015 ^[45]
Preview release	2.0.2-nightly20150512c58264e58b / May 12, 2015 ^[46]
Development status	Active
Written in	C, C++, JavaScript
Operating system	OS X, Linux, Microsoft Windows
Type	Event-driven networking
License	MIT
Website	iojs.org (https://iojs.org/)



Wikimedia Commons has media related to ***io.js***.



Wikimedia Commons has media related to ***JXcore***.

Other languages

Similar environments available for other programming languages include:

- Tornado and Twisted for Python
- Perl Object Environment for Perl
- libevent for C
- Vert.x for Java, JavaScript, Groovy, Python, Scala, Clojure and Ruby
- Akka for Java and Scala
- EventMachine for Ruby
- vibe.d for D
- Luvit (<http://luvit.io/>) for Lua
- Ocsigen for OCaml
- Node-julia allows using Julia (programming language) with Node.js/io.js^[52] using no-overhead calling from either language

See also

- V8 (JavaScript engine)
- SpiderMonkey (software)
- Rhino (JavaScript engine)
- CommonJS
- MongoDB
- Server-side scripting
- MEAN (software bundle)
- Twisted (software)
- EventMachine
- Vert.x
- Online JavaScript IDE
- JavaScript
- List of JavaScript libraries

References

1. <https://github.com/joyent/node/tags?after=v0.0.4>. Retrieved 2 August 2014. Missing or empty |title= (help)
2. "v0.12.4 Stable" (<https://github.com/joyent/node/releases/tag/v0.12.4>). Retrieved 23 May 2015.
3. "v0.11.16: 2015.01.29, Version 0.11.16 (Unstable)" (<https://github.com/joyent/node/releases/tag/v0.11.16>). Retrieved 5 April 2015.
4. <https://nodejs.org/foundation/>
5. <http://collabprojects.linuxfoundation.org/>
6. Industry Usage (<http://nodejs.org/industry/>), Node.js Website
7. <http://www.ibm.com/bluemix>
8. "Here's why you should be happy that Microsoft is embracing Node.js" (<http://www.guardian.co.uk/technology/blog/2011/nov/09/programming-microsoft>). The Guardian. November 9, 2011. Retrieved May 10, 2012.
9. "WebMatrix - Front End Web Developers take note (ASP.NET, PHP, node.js and more)" (<http://www.hanselman.com/blog/WebMatrix2FrontEndWebDevelopersTakeNoteASPNETPHPNodejsAndMore.aspx>). Retrieved 2 August 2014.
10. "Yahoo! Announces Cocktails Shaken, Not Stirred" (<https://developer.yahoo.com/blogs/ydn/yahoo-announces-cocktails-shaken-not-stirred-51439/>). Retrieved 7 April 2015.

11. "Why Walmart is using Node.js" (<http://venturebeat.com/2012/01/24/why-walmart-is-using-node-js/>). VentureBeat. January 24, 2012. Retrieved May 10, 2012.
12. Geitgey, Adam (30 October 2013). "I-Tier: Dismantling the Monoliths" (<https://engineering.groupon.com/2013/misc/i-tier-dismantling-the-monoliths/>). Groupon. Retrieved 30 April 2014.
13. "SAP AppBuilder" (<http://help.sap.com/appbuilder>). SAP. March 10, 2014. Retrieved March 10, 2014.
14. "You'll never believe how LinkedIn built its new iPad app" (<http://venturebeat.com/2012/05/02/linkedin-ipad-app-engineering/>). VentureBeat. May 2, 2012. Retrieved May 10, 2012.
15. "Blazing fast node.js: 10 performance tips from LinkedIn Mobile" (<http://engineering.linkedin.com/nodejs/blazing-fast-nodejs-10-performance-tips-linkedin-mobile>). Retrieved 7 April 2015.
16. "Clash of the Titans: Releasing the Kraken, NodeJS @paypal" (<http://www.youtube.com/watch?v=tZWGb0HU2QM>). fluentconf.com. May 28, 2013. Retrieved September 11, 2013.
17. "All such companies and their products in which Node.js is used" (<https://github.com/joyent/node/wiki/Projects,-Applications,-and-Companies-Using-Node>). Retrieved 2 August 2014.
18. The Node Ahead: JavaScript leaps from browser into future (http://www.theregister.co.uk/2011/03/01/the_rise_and_rise_of_node_dot_js/), The Register, March 1, 2011
19. Why GoDaddy's Nodejitsu deal is great for Node.js (<http://venturebeat.com/2015/02/10/why-godaddys-nodejitsu-deal-is-great-for-node-js/>), VentureBeat, February 10, 2015
20. Professional Node.js: Building Javascript Based Scalable Software (<https://books.google.com/books?id=ZH6bpbcrlvYC&printsec=frontcover&dq=nodejs&hl=en&sa=X#v=onepage&q=nodejs&f=false>), John Wiley & Sons, 01-Oct-2012
21. Alex Handy (2011-06-24). "Node.js pushes JavaScript to the server-side" (http://www.sdtimes.com/NODE_JS_PUSHES_JAVASCRIPT_TO_THE_SERVER_SIDE/By_Alex_Handy/About_JAVASCRIPT_and_NODEJS/35668). SDTimes. Retrieved 2011-09-04.
22. Harris, Amber (April 1, 2012). "The Birth of Node: Where Did it Come From? Creator Ryan Dahl Shares the History" (<http://devopsangle.com/2013/04/01/the-birth-of-node-where-did-it-come-from-creator-ryan-dahl-shares-the-history/>). Devops Angle. Retrieved 26 October 2013.
23. Sams Teach Yourself Node.js in 24 Hours (<https://books.google.com/books?id=KGt-FxUEj48C&pg=PT24&dq=nodejs&hl=en&sa=X#v=onepage&q=nodejs&f=false>), Sams Publishing, 05-Sep-2012
24. "Ryan Dahl at JSConf EU 2009" (http://jsconf.eu/2009/speaker/speakers_selected.html).
25. "Ryan Dahl at JSConf EU 2009 Video" (<https://www.youtube.com/watch?v=ztspvPYyBIY>).
26. "Porting Node to Windows" (<http://blog.nodejs.org/2011/06/23/porting-node-to-windows-with-microsoft%25e2%2580%2599s-help/>). Retrieved 2 August 2014.
27. Dahl, Ryan. "New gatekeeper" (<https://groups.google.com/forum/#!topic/nodejs/hfajgpvGTLY>). Retrieved 26 October 2013.
28. Schlueter, Isaac (January 15, 2014). "The Next Phase of Node.js" (<http://blog.nodejs.org/2014/01/15/the-next-phase-of-node-js/>). Retrieved 21 January 2014.
29. Krill, Paul (Dec 4, 2014). "Why io.js Decided to Fork Node.js" (<http://www.javaworld.com/article/2855639/open-source-tools/qanda-why-io-js-decided-to-fork-node-js.html>). JavaWorld. Retrieved Dec 15, 2014.
30. <https://www.linuxfoundation.org/news-media/announcements/2015/06/nodejs-foundation-advances-community-collaboration-announces-new>
31. Node.js for PHP Developers (<https://books.google.com/books?id=KZQQA1hTOBgC&printsec=frontcover&dq=nodejs&hl=en&sa=X#v=onepage&q=nodejs&f=false>), O'Reilly Media, Inc., 2013
32. Node.js Essentials (<https://books.google.com/books?id=zl17BAAQBAJ&dq=nodejs&hl=en&sa=X>), Packt Publishing, 09-Sep-2014
33. Smashing Node.js: JavaScript Everywhere (https://books.google.com/books?id=G1y_5kpmatUC&printsec=frontcover&dq=nodejs&hl=en&sa=X#v=onepage&q=nodejs&f=false), John Wiley & Sons, 14-Aug-2012
34. Modules (<https://nodejs.org/api/>), Nodejs Website
35. Express.js Guide: The Comprehensive Book on Express.js (<https://books.google.com/books?id=5eGRAwAAQBAJ&printsec=frontcover&dq=nodejs&hl=en&sa=X#v=onepage&q=nodejs&f=false>), Azat Mardan, 28-May-2014

36. "CoffeeScript on Node.js" (<https://books.google.com/books?id=Oda-MgEACAAJ&dq=nodejs&hl=en&sa=X>). O'Reilly Media, Inc. April 15, 2013. Retrieved May 17, 2015.
37. Finley, Klint (April 7, 2011). "NodeConf Schedule Announced" (<http://www.readwriteweb.com/hack/2011/04/nodeconf-schedule-announced.php>). ReadWriteHack. Retrieved 2 August 2014.
38. About Node.js (<https://nodejs.org/about/>), Node.js Website
39. "Node.js Tools for Visual Studio" (<https://nodejstools.codeplex.com/>). Codeplex. Retrieved 2 August 2014.
40. "Bergius: Flowhub and the GNOME Developer Experience" (<https://lwn.net/Articles/597216/>). *LWN.net*. 2014-05-02. Retrieved 2014-05-24.
41. Mike Kopp (2014-11-27). "There's a new kid in town: node.js monitoring" (<http://blog.ruxit.com/new-kid-nodejs-monitoring/>). blog.ruxit.com. Retrieved 2014-11-28.
42. Node.js Framework Comparison: Express vs. Koa vs. Hapi (<https://www.airpair.com/node.js/posts/nodejs-framework-comparison-express-koa-hapi>), AirPair
43. 13 fabulous frameworks for Node.js (<http://www.infoworld.com/article/2606426/application-development/153472-13-fabulous-frameworks-for-Node.js.html>), InfoWorld
44. "Release v1.0.0-release" (<https://github.com/iojs/io.js/releases/tag/v1.0.0-release>). Retrieved 2 February 2015.
45. "Release v2.0.1" (<https://github.com/iojs/io.js/releases/tag/v2.0.1>). Retrieved 13 May 2015.
46. "Index of /download/nightly/v2.0.2-nightly20150512c58264e58b/" (<https://iojs.org/download/nightly/v2.0.2-nightly20150512c58264e58b/>). Retrieved 13 May 2015.
47. Q&A: Why io.js decided to fork Node.js (<http://www.infoworld.com/article/2855057/application-development/why-iojs-decided-to-fork-nodejs.html>), Infoworld Tech Watch
48. Mikeal, Rogers (January 28, 2015). "State of io.js" (<https://medium.com/node-js-javascript/state-of-io-js-2b3094e6f923>). Retrieved 2 February 2015.
49. Ben Noordhuis (Nov 12, 2014). "Issue 3692: function suddenly becomes undefined" (<https://code.google.com/p/v8/issues/detail?id=3692#c3>). V8 JavaScript Engine Issues. Retrieved 2 February 2015.
50. "io.js and Node.js merge" (<https://medium.com/node-js-javascript/io-js-week-of-may-15th-9ada45bd8a28>). Retrieved 27 June 2015.
51. The JXcore variant of Node.js bristles with intriguing features and aims to move Node into the mobile world (<http://www.infoworld.com/article/2886740/application-development/nodejs-variant-jxcore-goes-open-source-aims-for-mobile-developers.html>), Infoworld
52. "Limitations" (<http://node-julia.readme.io/v1.1.0/docs/limitations>). *node-julia*.

Further reading

- Hughes-Croucher, Tom; Wilson, Mike (April 2012), *Up and Running with Node.js* (First ed.), O'Reilly Media, p. 204, ISBN 978-1-4493-9858-3
- Ornbo, George (September 2012), *Sams Teach Yourself Node.js in 24 Hours* (First ed.), SAMS Publishing, p. 440, ISBN 978-0-672-33595-2
- Teixeira, Pedro (October 2012), *Professional Node.js* (<http://eu.wiley.com/WileyCDA/WileyTitle/productCd-1118185463,descCd-authorInfo.html>) (First ed.), John Wiley & Sons, p. 408, ISBN 978-1-1182-2754-1
- Randal L. Schwartz and Aaron Newcomb (9 January 2013). "Episode 237: Node.js" (<http://twit.tv/show/floss-weekly/237>). <http://twit.tv/show/floss-weekly> (Podcast). TWiT.tv. Event occurs at 1:08:13. Retrieved 9 January 2013.
- Ribeiro Pereira, Caio (July 2013), *Aplicações web real-time com Node.js* (<https://casadocodigo.refersion.com/l/630.1389>) (First ed.), Casa do Código, p. 143, ISBN 978-85-66250-14-5
- Kurniawan, Agus (July 2012), *Nodejs Programming By Example* (First ed.), PE Press, p. 67
- Gackenheim, Cory (October 2013), *Node.js Recipes: A Problem-Solution Approach* (First ed.), Apress, p. 376, ISBN 978-14-30260-58-5

External links

- Official website (<http://nodejs.org>)
- GitHub Repository (<https://github.com/joyent/node>)
- Node.js real time mailing list discussions (<http://qna1ist.com/g/nodejs>)



Wikimedia Commons has media related to *Node.js*.

Retrieved from "<https://en.wikipedia.org/w/index.php?title=Node.js&oldid=668950575>"

Categories: JavaScript libraries | Free software programmed in JavaScript
| Free software programmed in C++ | Joyent

- This page was last modified on 27 June 2015, at 20:33.
- Text is available under the Creative Commons Attribution-ShareAlike License; additional terms may apply. By using this site, you agree to the Terms of Use and Privacy Policy. Wikipedia® is a registered trademark of the Wikimedia Foundation, Inc., a non-profit organization.