OPERATING SYSTEMS ORANGE LEVEL ASSIGNMENT

NAME: NAGARAJA GARI RAM SAI GOVIND

SRN : PES1UG24CS912 SECTION: 4-A

Phase 1 :

Make test_objects and ./test_objects is ran :

```
govind@nramsaigovind-rgb :~/pes-lab/os-u4-orange-problem$ make test_objects
gcc -Wall -Wextra -O2 -c test_objects.c -o test_objects.o
gcc -Wall -Wextra -O2 -c object.c -o object.o
gcc -o test_objects test_objects.o object.o -lcrypto
govind@nramsaigovind-rgb :~/pes-lab/os-u4-orange-problem$ ./test_
-bash: ./test_: No such file or directory
govind@nramsaigovind-rgb :~/pes-lab/os-u4-orange-problem$ ./test_objects
Stored blob with hash: d58213f5dbe0629b5c2fa28e5c7d4213ea09227ed0221bbe9db5e5c4b9aafc12
Object stored at: .pes/objects/d5/8213f5dbe0629b5c2fa28e5c7d4213ea09227ed0221bbe9db5e5c4b9aafc12
PASS: blob storage
PASS: deduplication
PASS: integrity check

All Phase 1 tests passed.
govind@nramsaigovind-rgb :~/pes-lab/os-u4-orange-problem$
```

Phase 1.2 :

./pes init is ran to initialize an empty repo

gcc —o pes obJect.o tree. o In ex. o commat.o pes.o — crypto govind@nramsaigovind-rgb : /pes—Iab/os—u4—orange—probIem$. / pes init Initialized empty PES repository in . pes/ govind@nramsaxgovind-rgb : find .pes/objects —type f . pes/objects/d5/8213f5dbe0629b5c2fa28e5c7d4213ea09227ed0221bbe9db5e5c4b9aafc1 2

. pes/obj

. pes/obj b9b46a1af8e11ec4f476 govind@nramsaigovind-rgb :

Phase 2.1 :

make test_tr raan ./test_tr work anpass test

```
make: *** [Makefile:14: tree.o] Error 1
govind@nramsaigovind-rgb :~/pes-lab/os-u4-orange-problem$ make
make: 'pes' is up to date.
govind@nramsaigovind-rgb :~/pes-lab/os-u4-orange-problem$ make test_tree
make: 'test_tree' is up to date.
govind@nramsaigovind-rgb :~/pes-lab/os-u4-orange-problem$ ./test_tree
Serialized tree: 139 bytes
PASS: tree serialize/parse roundtrip
PASS: tree deterministic serialization

All Phase 2 tests passed.
```

Phase 2.2 : .

/test_tree is ran and find.pes just shows directory listings

```
govind@nramsaigovind-rgb:~/pes-lab/os-u4-orange-problem$ ./test_tree
Serialized tree: 139 bytes
PASS: tree serialize/parse roundtrip
PASS: tree deterministic serialization

All Phase 2 tests passed.
govind@nramsaigovind-rgb:~/pes-lab/os-u4-orange-problem$ find .pes
.pes
.pes/objects
.pes/refs
.pes/refs/heads
govind@nramsaigovind-rgb:~/pes-lab/os-u4-orange-problem$
```

PHASE 3.1 :

Empty repo is initialized , and 2 files are added using git-like commands. Then status is checked (with staging and unstaged and untracked files detailed view)

```
govind@nramsaigovind-rgb ~/pes-lab/os-u4-orange-problem$ ./pes init
Initialized empty PES repository in .pes/
govind@nramsaigovind-rgb ~/pes-lab/os-u4-orange-problem$ ./pes add file1.txt file2.txt
govind@nramsaigovind-rgb ~/pes-lab/os-u4-orange-problem$ ./pes status
Staged changes:
  staged:     file1.txt
  staged:     file2.txt

Unstaged changes:
  (nothing to show)

Untracked files:
  untracked:  pes.h
  untracked:  test_sequence.sh
  untracked:  pes_asan
  untracked:  Makefile
  untracked:  tree.c
  untracked:  commit.h
  untracked:  .gitignore
  untracked:  README.md
  untracked:  index.c
  untracked:  test_tree.c
  untracked:  pes.c
  untracked:  object.c
  untracked:  tree.h
  untracked:  commit.c
  untracked:  test_objects.c
  untracked:  index.h

govind@nramsaigovind-rgb:~/pes-lab/os-u4-orange-problem$ cat .pes/index
100644 ebf0f28f3e0b799ef8aa5cc9614366d92ee232896ac6337d30325c31ed8669e0 1776669252 6 file1.txt
100644 28f838ab75e7f7f020a093ce0beeb8a2d4aab8e7cef7ae3ed4c8c65c7beda6ba 1776669252 6 file2.txt
govind@nramsaigovind-rgb:~/pes-lab/os-u4-orange-problem$
```

Phase 3.2 :

Testing by adding 2 files again manually.

cd make pes
gcc —Walt —Wextra —02 —c index.c -o index .0 gcc —o pes object.o
tree.o index. o commit.o pes.o -Icrypto rm —rf . pes akshat@AkshatDev
: — / pes—lab/ cd akshat@AkshatDev : —/ pes—tab/ ./pes init
Initialized empty PES repository in . pes/ akshat@AkshatDev : — / printf "hello\n" > fitel.txt
akshat@AkshatDev : pes—lab/ printf "world\n" > fite2.txt akshat@AkshatDev : ./pes add
fitel.txt fite2.txt akshat@AkshatDev : — / ./pes status Staged changes:

staged : filel . txt
staged : file2. txt
Unstaged changes :
(nothing to show) Untracked
files:

untracked : pes . h

untracked : test_sequence . sh

untracked : pes_asan

untracked : makefile

untracked : tree . c

untracked : commit . h

untracked : . gitignore

untracked : README . md

untracked : index. c

untracked : test _tree. c

untracked : pes . c

untracked : object . c

untracked : tree . h

untracked : commit . c

untracked : test_objects . c

untracked : index . h

govind@n ramsaigovind- rob :

Phase 3.3 .

Extra step to show index file content

```
govind@nramsaigovind-rgb :~/pes-lab/os-u4-orange-problem$ cd ~/pes-lab/os-u4-orange-problem
govind@nramsaigovind-rgb :~/pes-lab/os-u4-orange-problem$ cat .pes/index
100644 2cf8d83d9ee29543b34a87727421fdecb7e3f3a183d337639025de576db9ebb4 1776669470 6 file1.txt
100644 e00c50e16a2df38f8d6bf809e181ad0248da6e6719f35f9f7e65d6f606199f7f 1776669472 6 file2.txt
govind@nramsaigovind-rgb :~/pes-lab/os-u4-orange-problem$
```

PHASE 4.1 :

WORKING FLOW by initializing an empty repo - adding files - committing changes and printing log (similar to git log —oneline or git log)

```
govind@nramsaigovind-rgb :~/pes-lab/os-u4-orange-problem$ rm -rf .pes
govind@nramsaigovind-rgb :~/pes-lab/os-u4-orange-problem$ cd ~/pes-lab/os-u4-orange-problem
govind@nramsaigovind-rgb :~/pes-lab/os-u4-orange-problem$ ./pes init
Initialized empty PES repository in .pes/
                         :~/pes-lab/os-u4-orange-problem$ printf "Hello\n" > hello.txt
govind@nramsaigovind-rgb :~/pes-lab/os-u4-orange-problem$ ./pes add hello.txt
                         :~/pes-lab/os-u4-orange-problem$ ./pes commit -m "Initial"
Committed: 5a874dcc2bfb... Initial
                         :~/pes-lab/os-u4-orange-problem$ printf "World\n" >> hello.txt
govind@nramsaigovind-rgb :~/pes-lab/os-u4-orange-problem$ ./pes add hello.txt
                         :~/pes-lab/os-u4-orange-problem$ ./pes commit -m "Add_world"
Committed: 6d489a105ccc... Add_world
                         :~/pes-lab/os-u4-orange-problem$ printf "Goodbye\n" > bye.txt
govind@nramsaigovind-rgb :~/pes-lab/os-u4-orange-problem$ ./pes add bye.txt
                         :~/pes-lab/os-u4-orange-problem$ ./pes commit -m "Add_farewell"
Committed: 43f9fbefd1cf... Add_farewell
govind@nramsaigovind-rgb :~/pes-lab/os-u4-orange-problem$ ./pes log
commit 43f9fbefd1cfbade5828e3c6aab5ac6355758f6d699c75524045c356951274a6
Author: PES User <pes@localhost>
Date:   1776670017

    Add_farewell

commit 6d489a105ccc3a799601d5f03bb9c492e53c7d41492caf57284884dc7657567a
Author: PES User <pes@localhost>
Date:   1776670011

    Add_world

commit 5a874dcc2bfb19a23ec39d603f57bfcf386e7dcd44191a1241c7e7da9e72df9b
Author: PES User <pes@localhost>
Date:   1776670003

    Initial

govind@nramsaigovind-rgb :~/pes-lab/os-u4-orange-problem$ |
```

Phase 4.2 :

akshat@AkshatDev cd find . pes —type f I sort
. pes/HEAD
. pes/index
. pe ects/e5/c8d777debe85748b6788d1b5caf7d6975ue6e68e6ec265ca21cbd6ce5e5f43
. pes/objects/43/f9fbefd1cfbade5828e3c6aab5ac6355758f6d699c7552ue45c356951274a6 .
pes/objects/5a/87Udcc2bfb19a23ec39d6e3f57bfcf386e7dcdUU191a12U1c7e7da9e72df9b
. pes/obj
. pes/objects/6d/u89a1e5ccc3a7996e1d5fe3bb9cu92e53c7du1492caf57284884dc7657567a
. pes/obj ects/a6/882eeuafdc855eaue39fueefc77d9øe73a6f72deb383e1193431ea1ea03€f6
. pes/objects/bd/9b769bbud991ec31b4fee99eu375fffea35c2e5513ec248ff131f78c626442
. pes/objects/d8/f282e3e71e1ea3bde6e5928368bc5b51871287a867d8d10382967e99dde81U
. pes/objects/e6/7ed66bcbua7e825ea89f315d4d8bb927€3343c84df83443888ee13a68652bc .
pes/refs/heads/main akshat@AkshatDev :

Phase 4.3:

Full test history

```
.pes/refs/heads/main
govind@nramsaigovind-rgb:~/pes-lab/os-u4-orange-problem$ cd ~/pes-lab/os-u4-orange-problem
govind@nramsaigovind-rgb:~/pes-lab/os-u4-orange-problem$ echo "refs/heads/main:"
refs/heads/main:
govind@nramsaigovind-rgb:~/pes-lab/os-u4-orange-problem$ cat .pes/refs/heads/main
43f9fbefd1cfbade5828e3c6aab5ac6355758f6d699c75524045c356951274a6
govind@nramsaigovind-rgb:~/pes-lab/os-u4-orange-problem$ echo "HEAD:"
HEAD:
govind@nramsaigovind-rgb:~/pes-lab/os-u4-orange-problem$ cat .pes/HEAD
ref: refs/heads/main
govind@nramsaigovind-rgb:~/pes-lab/os-u4-orange-problem$ make test-integration
=== Running integration tests ===
bash test_sequence.sh
=== PES-VCS Integration Test ===

--- Repository Initialization ---
Initialized empty PES repository in .pes/
PASS: .pes/objects exists
PASS: .pes/refs/heads exists
PASS: .pes/HEAD exists

--- Staging Files ---
Status after add:
Staged changes:
  staged:     file.txt
  staged:     hello.txt

Unstaged changes:
  (nothing to show)

Untracked files:
  (nothing to show)


--- First Commit ---
Committed: edcc94a8c274... Initial commit

Log after first commit:
commit edcc94a8c274837044b22f2c778a4a06de0e538da4846c0605392619b6f493d1
Author: PES User <pes@localhost>
Date:   1776670122

    Initial commit


--- Second Commit ---
Committed: ffe56baafdf6... Update file.txt

--- Third Commit ---
Committed: 4974dc4e1ab8... Add farewell

--- Full History ---
```

```
--- Full History ---
commit 4974dc4e1ab893b64a74d60c834d2e90093385b2276e82f29471de2d8870c08b
Author: PES User <pes@localhost>
Date:   1776670122

    Add farewell

commit ffe56baafdf6c99b28e8e23da76e4454b4da9f98c904e9e4e415a7616d9f6e37
Author: PES User <pes@localhost>
Date:   1776670122

    Update file.txt

commit edcc94a8c274837044b22f2c778a4a06de0e538da4846c0605392619b6f493d1
Author: PES User <pes@localhost>
Date:   1776670122

    Initial commit


--- Reference Chain ---
HEAD:
ref: refs/heads/main
refs/heads/main:
4974dc4e1ab893b64a74d60c834d2e90093385b2276e82f29471de2d8870c08b

--- Object Store ---
Objects created:
10
.pes/objects/0b/d69098bd9b9cc5934a610ab65da429b525361147faa7b5b922919e9a23143d
.pes/objects/10/1f28a12274233d119fd3c8d7c7216054ddb5605f3bae21c6fb6ee3c4c7cbfa
.pes/objects/49/74dc4e1ab893b64a74d60c834d2e90093385b2276e82f29471de2d8870c08b
.pes/objects/58/a67ed1c161a4e89a110968310fe31e39920ef68d4c7c7e0d6695797533f50d
.pes/objects/ab/5824a9ec1ef505b5480b3e37cd50d9c80be55012cabe0ca572dbf959788299
.pes/objects/b1/7b838c5951aa88c09635c5895ef7e08f7fa1974d901ce282f30e08de0ccd92
.pes/objects/d0/7733c25d2d137b7574be8c5542b562bf48bafeaa3829f61f75b8d10d5350f9
.pes/objects/db/07a1451ca9544dbf66d769b505377d765efae7adc6b97b75cc9d2b3b3da6ff
.pes/objects/ed/cc94a8c274837044b22f2c778a4a06de0e538da4846c0605392619b6f493d1
.pes/objects/ff/e56baafdf6c99b28e8e23da76e4454b4da9f98c904e9e4e415a7616d9f6e37

=== All integration tests completed ===
govind@nramsaigovind-rgb:~/pes-lab/os-u4-orange-problem$
```

NOTE:

COMITS MADE:



PHASE 5 AND 6 ANSWERS:

(These are already committed per subquestion in Readme.MD in the repo)

Q5.1: A branch in Git is just a file in . g it/ refs/ heads / containing a commit hash. Creating a branch is creating a file. Given this, how would you implement & pes checkout what files need to change in and what must happen to the working directory? What makes this operation complex?

Ans 5.1

To implement checkout <branch> I would do three things:

1. Validate the branch exists in .pes/refs/heads/<branch>

2. Update . pes/HEAD s to point to ref: refs/ heads/<branch>

commit hash from that branch, load its root tree, and rewrite the working directory to match that snapshot (create/update/delete files

The tricky part is not updating HEAD; it is safely changing the working directory. You have to avoid deleting user changes, handle nested trees correctly, and make sure index + working directory + HEAD all end up consistent.

When switching branches, the working directory must be updated

to match the target branch's tree. If a tracked file, the user has uncommitted changes to between and that file differs refuse. Describe how you branches, checkout must this dirty working would detect using only the index and the directory" object store.

Ans 5.2

I would detect conflicts by comparing three versions of each tracked path :

1 . Version in current HEAD tree (baseline) .

2 . Version in target branch tree (what checkout wants to write) .

3 . Current working directory state (using index metadata/ hash checks) .

If a file is modified in working directory relative to index/HEAD, and that same file would also change when moving to target branch, that is a and checkout should stop .

In short: if file is dirty locally and target branch wants a different "'on tent for that path, refuse checkout.

Q5.3: "Detached HEAD" means HEAD contains a commit hash directly instead of a branch reference. What happens if you make commits in this state? How could a user recover those commits?

Ans 5.3

In detached HEAD, new commits are still created normally, but no branch name moves forward with them. So those commits can become hard to find later .

Recovery is simple if you know the commit hash: create a new branch pointing to it, like branch rescued < hash S (or equivalent in PES) . If you realize late, ref log—style history (if implemented) helps find that commit again.

Garbage Collection and Space Reclamation

Q6.1: Over time, the object store accumulates unreachable objects — blobs, trees, or commits that no branch points to (directly or transitively) . Describe an algorithm to find and delete these obj ects .
Nhat data structure would you use to track "reachable" hashes efficiently? For a repository with 100, 000 commits and 50 branches, estimate how many objects you'd need to visit.

Ans 6.1

1 would use a classic mark—and—sweep approach:

1 . Start from all branch heads in .pes/refs/heads/* as roots .

2 . Traverse reachable commits via parent links .

3 . From each commit, mark its tree.

4 . Recursively mark all subtree and blob objects referenced by trees .

5 . After marking, scan .pes/obj ectE$ and delete anything unmarked.

For fast lookup, use a hash set of object IDs (& reachable') .

For 100, 000 commits and 50 branches, commit traversal is usually near
100, 000 unique commits (branches share history) . Total visited objects be a few hundred thousand when trees and blobs are included, depending on project size and change frequency
.

Why is it dangerous to run garbage collection concurrently with a commit operation? Describe a race condition where GC could delete an obj ect that a concurrent commit is about to reference. How does Git's real
GC avoid this?

Ans 6.2
Running GC during commit creation is risky because commit is multi—step .
Example race :

1 . Commit process writes new blob/ tree objects.

2 . Before branch ref is updated, GC scans refs and does not see these new objects as reachable .

4 . Commit then writes/ updates commit ref that points to now—missing obj ects .

Git avoids this using safety mechanisms like temporary reachability protection, conservative pruning (age—based) , and coordination/ locking so in—progress objects are not collected immediately.