

## TM Forum Model

# Intent Family Relation - Intent Extension Model

TR291F

<b>Maturity Level: Beta</b>	<b>Team Approved Date: 01-Jun-2022</b>
<b>Release Status: Pre-production</b>	<b>Approval Status: Member Evaluated</b>
<b>Version 1.1.0</b>	<b>IPR Mode: RAND</b>

## Notice

Copyright © TM Forum 2022. All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this section are included on all such copies and derivative works. However, this document itself may not be modified in any way, including by removing the copyright notice or references to TM FORUM, except as needed for the purpose of developing any document or deliverable produced by a TM FORUM Collaboration Project Team (in which case the rules applicable to copyrights, as set forth in the [TM FORUM IPR Policy](#), must be followed) or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by TM FORUM or its successors or assigns.

This document and the information contained herein is provided on an “AS IS” basis and TM FORUM DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Direct inquiries to the TM Forum office:

181 New Road, Suite 304  
Parsippany, NJ 07054, USA  
Tel No. +1 862 227 1648  
TM Forum Web Page: [www.tmforum.org](http://www.tmforum.org)

# Table of Contents

Notice .....	2
Table of Contents .....	3
List of Figures .....	4
List of Tables .....	5
Executive Summary.....	6
Introduction.....	7
1.Motivation and background.....	8
2.Notation and namespaces .....	9
3.Principles and vocabulary overview .....	10
4.Vocabulary specification .....	11
4.1.    Classes.....	11
4.2.    Instances .....	11
4.3.    Properties .....	11
5.Model usage and examples .....	13
5.1.    Communicating ancestor and sibling intents .....	13
6.Administrative Appendix .....	14
6.1.    Document History .....	14
6.1.1.  Version History.....	14
6.1.2.  Release History.....	14
6.2.    Acknowledgments.....	14
6.2.1.  Guide Lead & Author.....	14
6.2.2.  Main Contributors.....	14
6.2.3.  Additional Inputs .....	15

## List of Figures

Figure 0.1: Intent model dependencies overview .....	7
Figure 3.1: Vocabulary for expressing intent family relationships .....	10

## List of Tables

Table 2-1: Model references .....	9
-----------------------------------	---

## Executive Summary

The intent family relation model is an intent extension model that introduces vocabulary needed to provide information about relationships between intent.

## Introduction

This document describes a model in the suit of models for intent based operation.




Figure 0.1: Intent model dependencies overview

# 1. Motivation and background

An intent is often used together with other intent to achieve a requirement. For example, a first intent might require a service to be delivered and the intent handler creates a second intent that requires the network functions needed for this service and a third intent requiring a slice. In the terminology introduced here, this set of inter-dependent intents is called an intent family. Intents are related and considered to be in the same family if they are part of the solution for a common requirement. The following relationships are recognized:

## Parent and child intent

An intent is a child of another intent if it directly contributes to satisfy the requirements set by the other intent. This other intent is therefore the parent of the first. Intents can have multiple parents. In fact, every intent that has directly contributed to defining the requirements of another intent is considered to be one of its parents. In reverse, one intent can have multiple child intents. These are all the intents that set requirements in various subsequent intent handlers. This is a relationship of terminal and instrumental goals. The parent is trying to satisfy its terminal goals and its child intents are used to set and distribute the instrumental goals needed.

## Ancestors

All intent above in the parent-child hierarchy are ancestors. This refers to parent intents and all parents of parents.

## Root Intent

This is an intent without parents. It is usually the original intent coming directly from human interaction or ordering systems.

## Sibling Intent

Two intents are siblings if they have the same parents and are used together to achieve the goals of the parents. In this scenario, the intent owner has created several intents and send them to multiple handlers. This handler and this intent are therefore one of a set used to achieve the owner's goals. The intents used in this operation and siblings.

This model allows communicating intent relationships. This information can be attached to an intent using a specialization of class `icm:Information`. Intent family relationships therefore do not carry requirements the system would need or even can be compliant to. It is only used for tracking and information purposes. This information can be valuable to human technicians when they monitor the autonomous system or try to debug its processes.

Family relationships can have multiple dimensions depending on what type of relationship is relevant. For example, two intents can be related because they both contribute to the delivery of the same service. Another example would be two intents that are related, because they are both serving users from the same user group. It is therefore possible that an intent is member of multiple families and these families do not necessarily share the same members. The intent family relationship model is therefore a tool that can be used differently depending on the use case and what type of relationship would be relevant to trace and document.

The current version of this model only has the vocabulary to attach intent family relation information to intents and not to intent reports. This might be useful, because child relationships need to be communicated upwards. A future version of this model can be extended accordingly.



## 2. Notation and namespaces

The proposals of the intent family relations model is defined in a namespace under the TM Forum domain. This intent extension model depends on the following models and uses the respective namespaces.

**Table 2-1: Model references**

Model	Prefix	Namespace	Published by
Intent Family Relation	ifr	<a href="http://tio.models.tmforum.org/tio/v1.0.0/IntentFamilyRelation/">http://tio.models.tmforum.org/tio/v1.0.0/IntentFamilyRelation/</a>	TM Forum
W3C RDF version 1.1	rdf	<a href="http://www.w3.org/1999/02/22-rdf-syntax-ns#">http://www.w3.org/1999/02/22-rdf-syntax-ns#</a>	W3C
W3C RDF Schema 1.1	rdfs	<a href="http://www.w3.org/2000/01/rdf-schema#">http://www.w3.org/2000/01/rdf-schema#</a>	W3C
Intent Common Model	icm	<a href="http://tio.models.tmforum.org/tio/v2.0.0/IntentCommonModel/">http://tio.models.tmforum.org/tio/v2.0.0/IntentCommonModel/</a>	TM Forum


The proposed prefix label for the intent family relation model is "ifr".

The model has a dependency to RDF and RDFS, because they are the chosen base standards for all intent and intent report models.

The intent family relation model specializes and extends the definitions of the intent common model (TR290).

### 3. Principles and vocabulary overview

Information about the family of an intent is expressed using an object of class `ifr:IntentFamily`. It is assigned to an intent using the `ifr:hasFamily` property.



**Figure 3.1: Vocabulary for expressing intent family relationships**

Family relationships to other intents are specified with the `ifr:hasAncestor`, `ifr:hasChild`, `ifr:hasParent`, `ifr:hasRoot` and `ifr:hasSibling` properties. They refer to the intents that have the respective relationships to the intent the family is specified for.

Intents can be part of multiple families. These families are distinguished by relationship category. For example, intents might be related, because they all contribute to the delivery of a service. Or they all contribute to the same customer contract. This model defines as few examples of family relationship categories as individuals of class `ifr:RelationshipCategory`. However, this list is supposed to be extended depending on use cases that need the respective information.

## 4. Vocabulary specification

### 4.1. Classes

<b>Class:</b>	ifr:IntentFamily
<b>Definition:</b>	Instances of this class are ancestors of other intents
<b>Instance of:</b>	rdfs:Class
<b>Subclass of:</b>	icm:Information

<b>Class:</b>	ifr:RelationshipCategory
<b>Definition:</b>	Allows defining for which parameters in other expectations a proposal shall be made for
<b>Instance of:</b>	rdfs:Class

### 4.2. Instances

The following table defines individuals of class ifr: RelationshipCategory:

ifr:RelationshipCategory individual	Description
ifr:SameCustomer	All intents in the family have in common that they contribute to serving the same customer
ifr:SameContract	All intents in the family have in common that they contribute to fulfilling the same contract
ifr:SameBusinessPolicy	All intents in the family have in common that they contribute to satisfy the same business policy of the operator
ifr:SameUserGroup	All intents in the family have in common that they contribute to serving users from the same group
...	further proposals are welcome

### 4.3. Properties

<b>Property:</b>	ifr:hasAncestor
<b>Definition:</b>	Refers to an intent that is considered to be an ancestor of the intent the family is specified for
<b>Instance of:</b>	rdf:property
<b>Domain:</b>	ifr:IntentFamily
<b>Range:</b>	icm:Intent

<b>Property:</b>	ifr:hasChild
Definition:	Refers to an intent that is considered to be a child of the intent the family is specified for
Instance of:	rdf:property
Domain:	ifr:IntentFamily
Range:	icm:Intent

<b>Property:</b>	ifr:hasFamily
Definition:	Assigns a family specification to an intent
Instance of:	rdf:property
Domain:	icm:Intent
Range:	ifr:IntentFamily

<b>Property:</b>	ifr:hasParent
Definition:	Refers to an intent that is considered to be a parent of the intent the family is specified for
Instance of:	rdf:property
Domain:	ifr:IntentFamily
Range:	icm:Intent

<b>Property:</b>	ifr:hasRoot
Definition:	Refers to an intent that is considered to be a root of the intent the family is specified for
Instance of:	rdf:property
Domain:	ifr:IntentFamily
Range:	icm:Intent

<b>Property:</b>	ifr:hasSibling
Definition:	Refers to an intent that is considered to be a sibling of the intent the family is specified for
Instance of:	rdf:property
Domain:	ifr:IntentFamily
Range:	icm:Intent

<b>Property:</b>	ifr:relatedBy
Definition:	Refers to an intent that is considered to be a Child of the intent the family is specified for
Instance of:	rdf:property
Domain:	ifr:IntentFamily
Range:	ifr:RelationshipCategory

## 5. Model usage and examples

### 5.1. Communicating ancestor and sibling intents

This example demonstrates how an intent can contain information about family relationships.

#### Example 1: Family definition

```
@prefix rdfs: <http://www.w3.org/2000/01/rdf-schema#> .
@prefix ifr:
<http://tio.models.tmforum.org/tio/v1.0.0/IntentFamilyRelation/> .
@prefix icm:
<http://tio.models.tmforum.org/tio/v2.0.0/IntentCommonModel/> .
@prefix :
<http://www.operator.org/IntentNamespace/intent20220322_12345/> .

:ampleIntentXYZ
  a icm:Intent ;
  ifr:hasFamily [ a IntentFamily ;
                  ifr:relatedBy ifr:SameContract ;
                  ifr:hasRoot :Intent0001 ;
                  ifr:hasParent :Intent0005 ;
                  ifr:hasSibling :Intent0204 ;
                  ifr:hasSibling :Intent0333 ;
                ] ;
  icm:hasExpectation :Del, :Del, :Pe1, :Pe1, :Re1 ;
.
...
```

This example intent contains information of a family it is part of. This family is defined by contributing to the same contract. In this family are one root intent, which was for example the one created by the order management system in business operation after the contract was approved and its fulfillment is needed. The family relation also refers to one direct parent and two sibling intents.

## 6. Administrative Appendix

### 6.1. Document History

#### 6.1.1. Version History

Version Number	Date Modified	Modified by:	Description of changes
1.0.0	31-Mar-2022	Alan Pope	Initial Release
1.1.0	01-Jun-2022	Alan Pope	Updated to beta

#### 6.1.2. Release History

Release Status	Date Modified	Modified by:	Description of changes
Pre-production	31-Mar-2022	Alan Pope	Initial Release
Pre-production	02-May-2022	Adrienne Walcott	Updated to reflect TM Forum Member Evaluated status
Pre-production	01-Jun-2022	Alan Pope	Final edits prior to publication
Pre-production	04-Jul-2022	Adrienne Walcott	Updated to reflect TM Forum Member Evaluated status

### 6.2. Acknowledgments

#### 6.2.1. Guide Lead & Author

Member	Title	Company
Jörg Niemöller	Expert of Analytics and Customer Experience	Ericsson

#### 6.2.2. Main Contributors

Member	Title	Company
Jörg Niemöller	Expert of Analytics and Customer Experience	Ericsson
Kevin McDonnell	Senior Director, Intelligent Automation	Huawei
James O'Sullivan	Product Director, Intelligent Automation	Huawei
Dave Milham	Chief Architect	TM Forum
Vinay Devadatta	Practice Head (Innovation & Industry Relations)	Wipro Technologies
Azahar Machwe	OSS Automation	BT Group plc
Wang Lei	Systems Expert	Huawei
Tayeb Ben Meriem	Senior Standardization Manager (OSS)	Orange
Leonid Mokrushin	Principle Researcher	Ericsson

**6.2.3. Additional Inputs**

Member	Title	Company
Lester Thomas	Chief IT Systems Architect	Vodafone Group
Ankur Goyal	Lead Consultant	Infosys
Emmanuel A. Otchere	Chief Technical ExpertVP, Standards & Industry Development	Huawei
Min He	Chief Architect	Futurewei