Firmware update

Here are the steps to update the firmware:

- 1. Download firmware from here.
- 2. Insert micro SD card to your computer.
- 3. Unzip and copy "qunmk2.bin" to the root folder of micro SD card.
- 4. Unmount and insert the micro SD card to Qun mk2
- 5. Disconnect all cables other than USB for power.
- 6. Keep pressing "REC" button on the bottom base board (Located at bottom-left side of the base board, under SEQ PLAY button), and connect USB cable, or press "RST" button on base board.
- 7. "Firmware updater" message will be shown when the updater booted.
- 8. After "Updating" message, then "Done" message will be shown.
- 9. Reset the board.

History

- v3.41
- BPM factor supports 0.125 and 0.25.
- Ext MIDI scale quantize is added. Setting is available in System2 mode.
- Bug fix: Note indication in Tune mode
- New feature: Parallel sequencer pattern running. See "Running multiple sequence patterns" section in the manual for detail.
- v3.34
- Bug fix: Sequencer page copy can perform by Shift + Seq Play + (YES or NO). Previous method is still working but not recommended.
- v3.33

- Performance improvement
- Bug fix: Sequencer behavior with chord
- Bug fix: Line in channel balance and matching level with polyphonic setup
- Add an ability to select old LOOPER folder (https://github.com/raspy13 5/Qun-mk2#looper00)
- v3.32
- Bug fix: Looper playback was mixed between channels, the bug introduced by recent firmware.
- v3.31 (deleted)
- v3.30
- Effector output is now stereo. Preset was updated to get the benefit of stereo effector, so please download and install preset as well. To download preset, download ../sd_template.zip and expand it, copy them to sd card.
- MDelay(Mono delay) is added to keep backward compatibility, and use it as a resonator.
- v3.27
- Number of the recording will be indicated when you are selecting session
- v3.26 (Deleted)
- v3.25
- Performance improvement
- v3.24
- Added a dialog to confirm initializing tone
- v3.23
- Performance improvement
- v3.22
- Rewind period and Rewind steps modifier are added.
- When applying the modifier, you can choose resetting or not resetting the modifiers
- v3.21

- Bug fix: Granular's out of tune issue
- Now Sequencer tune supports up to 4 voices
- In Play:Tune, chord play from external MIDI keyboard can be captured
- Bug fix: Granular's automatic sample loading when bucket is switched (System tries to find a sample when bucket is named,
- v3.20
- Bug fix: System crush when long sample is imported
- Better WAV file compatibility (WAV file with JUNK chunk supported)
- v3.19
- (Bad firmware, deteled)
- v3.18
- Bug fix: Some modulation sources (OSC2, OSC2EG) were not working properly
- v3.17
- Performance improvement
- Longer time to activate long press
- Softer clipping at the end of the signal
- v3.16
- Bug fix: Loading scene issue with mixed length of recordings
- v3.15
- Bug fix: FM (Mix, button 2, FM between Osc1 and Osc2) was not working properly
- Bug fix: Note off was sent to MIDI OUT even if the ext sequencer midi channel is off
- v3.14
- Startup screen added
- v3.13
- Bug fix: OSC1 bypass was not working properly
- Performance improvement
- v3.12
- Improved processing time when deleting all tracks in the scene,
- A bug fix with probability for second note
- Improved clipping noise

- v3.11: Deleted
- v3.10 : Number of voice was doubled, now it supports up to 4 voices. Bit crusher effect added.
- v3.00 Initial firmware is released