


CHASSIS 1 YEAR P.M. SERVICE

All inspection criteria derived from FMCSA CFR49 Part 396 and Appendix A subpart B

UNIT NUMBER LSFZ536416	LICENSE NUMBER V905744	OWNER DCLI	DATE COMPLETED 10/29/24	FACILITY Richmond	MECHANIC'S NAME (PRINT) Giovanni	SIGNATURE OF MECHANIC 
----------------------------------	----------------------------------	----------------------	-----------------------------------	-----------------------------	--	--

CODE COLUMN AS INSPECTION IS COMPLETED		
(X) = INSPECTION	R = MINOR REPAIRS MADE	SR = SHOP REPAIRS REQUIRED

	INSPECT	CODE	REMARKS		INSPECT	CODE	REMARKS
FRAME & GOOSENECK	1. Bends	/		LIGHTS	25. Test & repair as needed	/	
	2. Cracks	/			26. Reflectors, conspicuity tape	/	
	3. Welds	/		SUSPENSION	27. U-bolts	/	
	4. Check slider & lubricate	/	GREASE		28. Radius Rods, equalizer	/	
KING PIN	5. Tap for soundness/cracks	/			29. Springs & hangers	/	
	6. Check for wear	/			AXLES	30. Bent/misaligned	/
LOCKING DEVICES	7. Twist locks	/		31. Cracks		/	
	8. Index pins	/		32. Inspect for hub leaks (Inc. inner seal)		/	
	9. Lubricate	/	GREASE	33. Add oil to proper level (Oil hubs)		/	
LANDING GEAR	10. All components in tact	/		34. Check hub cap tightness	/		
	11. Tightness of mounts	/		TIRES & WHEELS	35. INFLATE TIRES: BIAS @ 85 PSI / RADIAL @ 100 PSI	/	
	12. Operation (turn twice) both speeds	/			36. 3/32" minimum thread depth	/	
	13. Lubricate	/	GREASE		37. Duals matched within 7/16"	/	
BUMPERS	14. Rear Impact Guard	/			38. General condition (dryrot, damaged, etc.)	/	
BRAKE SYSTEM	Chock wheels before releasing brakes!	/	WEE UP BRAKES SHOCS	CREDENTIALS	39. Install metal valve caps (all tires)	/	
	15a. Manual slack adjusters: Adjust (per MFG spec) Measure & record pushrod travel: LF <u>1 1/2</u> RF <u>1 1/2</u> LR <u>1 1/2</u> RR <u>1 1/2</u>	/	ADJUST BRAKES		40. Check lug nuts for tightness	/	
	15b. Automatic Slack adjusters: Measure & record pushrod travel: LF _____ RF _____ LR _____ RR _____ (troubleshoot if past limit)	/			41. Mud flaps, general appearance	/	
	16. Lubricate cam bushing, slack adjusters	/	GREASE		42. License plate	/	
	17. Brake drums	/		43. Registration papers	/		
	18. Brake linings (1/4" minimum)	/		44. Decals/stencils & markings in place & legible ()	/		
	19. ABS system	/		a) FRONT UNIT #	/		
	20. Air hoses, air lines, fittings	/		b) 40/45 FT DECAL/STENCIL (IF EXTENDABLE)	/		
	21. Gladhands, seals (replace seals if nec.)	/		c) FMCSA DECAL	/		
	22. Relay valves, springbrakes	/		d) L.H. SIDE UNIT #	/		
23. Drain reservoirs, lubricate drain valves	/		e) VIN PLATE	/			
24. Air test (Audible leaks)	/		f) REAR UNIT #	/			
				g) R.H. SIDE UNIT #	/		
				h) WEIGHT DECAL	/		

NOTE: In the event fasteners are found to be loose, retorque per manufacturers recommended settings.