



Filamentary transport in high-power H-mode conditions and in no/small-ELM regimes  
to predict heat and particle loads on PFCs for future devices

---

N. Vianello, V. Naulin for Topic-21 Scientific Team

14 November 2017



This work has been carried out within the framework of the EUROfusion Consortium and has received funding from the Euratom research and training programme 2014-2018 under grant agreement No 633053. The views and opinions expressed herein do not necessarily reflect those of the European Commission.

**Include scientific team and logos**



Deliverables listed during the call for manning of last December

1. Provide cross-machine L-Mode shoulder dependence on current both at constant  $B_t$  and at constant  $q_{95}$
2. Establish robust scenario for density shoulder profile in H-Mode and establish dependence on fuelling/neutral profiles/divertor condition
3. Use the new HHF probe on AUG to study filamentary transport under high-power H-Mode conditions and under different plasma configurations (SN, DN)
4. Study the role of ELM regimes, neutral compression and particle density in filamentary transport and related shoulder formation
5. Identify the contribution of collisionality and seeding on filamentary transport and related shoulder formation
6. Determine the effect of filaments and shoulder formation on target heat loads in different H-mode plasmas




Deliverables listed during the call for manning of last December

1. Provide cross-machine L-Mode shoulder dependence on current both at constant  $B_t$  and at constant  $q_{95}$
2. Establish robust scenario for density shoulder profile in H-Mode and establish dependence on fuelling/neutral profiles/divertor condition
3. Use the new HHF probe on AUG to study filamentary transport under high-power H-Mode conditions and under different plasma configurations (SN, DN)
4. Study the role of ELM regimes, neutral compression and particle density in filamentary transport and related shoulder formation
5. Identify the contribution of collisionality and seeding on filamentary transport and related shoulder formation
6. Determine the effect of filaments and shoulder formation on target heat loads in different H-mode plasmas


So far H-Mode operation has been limited to AUG since no operational scenario in high-density NBH heated plasma on TCV has been established

# L-Mode analysis: $I_p$ scan at constant $q_{95}$




- ✓ AUG: All the shots were performed in the so-called Edge Optimized Configuration (EOC) shape
- ✓ AUG: We matched correctly the shape and the  $L_{\parallel}$  here shown from outer divertor plate up to X-point

# L-Mode analysis: $I_p$ scan at constant $q_{95}$




- ✓ AUG: The scan was performed with similar puffing rate (0.8-l MA) whereas we reduced it at lower current to avoid early disruption
- ✓ AUG: The total power (Ohmic plus NBI) was kept constant throughout the scan
- ✓ AUG: We have comparable edge density, divertor neutral pressure and divertor temperature

# L-Mode analysis: $I_p$ scan at constant $q_{95}$




- ✓ TCV: We repeat the same exercise at TCV with a slight difference in the profile of parallel connection length. This required operation at unusual low toroidal field (up to 0.8T)

# L-Mode analysis: $I_p$ scan at constant $q_{95}$




- ✓ TCV: no additional heating used. Nevertheless the difference in power crossing the separatrix is small
- ✓ TCV: The difference in target pressure similar to AUG behavior

# L-Mode analysis: $I_p$ scan at constant $q_{95}$




✓ AUG: At comparable edge density Upstream profiles are different with the tendency to develop shoulder easier at lower current. **We have flattening of the upstream profiles only when  $\Lambda_{div}$  is well above one on all the profile**

# L-Mode analysis: $I_p$ scan at constant $q_{95}$




- ✓ AUG: Neutrals estimated using calibrated  $D_\alpha$  images coupled with values of density and temperature at the target suggest a larger

# L-Mode analysis: $I_p$ scan at constant $q_{95}$




- ✓ AUG: At all the current a clear roll-over in peak density observed and we can also track the radiation front move away from target earlier in density at lower current

# L-Mode analysis: $I_p$ scan at constant $q_{95}$




✓ TCV: This tendency is not observed for TCV where profiles seem resilient to modification of  $B_t$  even though we reached pretty high value of  $\Lambda_{div}$  all along the profile.

# L-Mode analysis: $I_p$ scan at constant $q_{95}$




- ✓ TCV: This is due to the fact that we can't observe during the density ramp any signature of rollover or detachment, whereas upstream profile modification at TCV are only observed well after rollover

# L-Mode analysis: $I_p$ scan at constant $q_{95}$




- ✓ AUG: There is the tendency towards larger blobs at lower current

# L-Mode analysis: $I_p$ scan at constant $q_{95}$




- ✓ TCV: this is not confirmed for TCV but in line with the lack of shoulder and detachment

# L-Mode analysis: $I_p$ scan at constant $B_t$




- ✓ AUG: We matched correctly the shape the parallel connection length  $L_{\parallel}$  is modified consistently
- ✓ AUG: The scan was performed with similar puffing rate (0.8-l MA) whereas we reduced it at lower current to avoid early disruption

# L-Mode analysis: $I_p$ scan at constant $B_t$




- ✓ AUG: We have comparable edge density and divertor neutral pressure even though pressure increase earlier at higher current
- ✓ AUG: The total power (Ohmic plus NBI) was kept constant throughout the scan

# L-Mode analysis: $I_p$ scan at constant $B_t$




- ✓ TCV: We repeat the same exercise at TCV with a consistent variation of parallel connection length

# L-Mode analysis: $I_p$ scan at constant $B_t$




- ✓ TCV: no additional heating used. Nevertheless the difference in power crossing the separatrix is small
- ✓ TCV: Neutral compression is roughly constant between

# L-Mode analysis: $I_p$ scan at constant $B_t$




✓ AUG: At comparable edge density Upstream profiles are different with the tendency to develop shoulder easier at lower current. **We have flattening of the upstream profiles only when  $\Lambda_{div}$  is well above one on all the profile**

# L-Mode analysis: $I_p$ scan at constant $B_t$




- ✓ Neutrals at lower current are substantially higher even with similar edge density profiles.

# L-Mode analysis: $I_p$ scan at constant $B_t$




✓ Neutrals at lower current are substantially higher even with similar edge density profiles.

# L-Mode analysis: $I_p$ scan at constant $B_t$




✓ TCV: This tendency is substantially confirmed at TCV where profiles

# L-Mode analysis: $I_p$ scan at constant $B_t$




- ✓ TCV: This is consistent with onset of detachment (at least in intermediate and lower current)

# L-Mode analysis: $I_p$ scan at constant $B_t$




- ✓ AUG: While the general observation of increasing blob size with  $\Lambda_{div}$  is confirmed there are no differences between the current

# L-Mode analysis: $I_p$ scan at constant $B_t$




✓ TCV: confirm the observation of AUG.

# LSN vs Double null on TCV




- ✓ Comparing similar L-Mode density ramp at same current in LSN and DN with ion  $\mathbf{B} \times \nabla B$  pointing towards the floor. Lower ion flux to lower target observed in DN and profiles before rollover seem more broad in LSN. After rollover the profiles are actually similar

# LSN vs Double null on TCV




- ✓ From bolometry we can observe an unbalanced movement of the radiation front suggesting a non perfectly balanced DN

# LSN vs Double null on TCV




- ✓ This is confirmed at higher current where the more active X-point is the upper one with a consequent higher radiation from bolometry chords

# LSN vs Double null on TCV




# H-Mode investigation: puffing location




- ✓ Similar puff from Lower and Upper divertor valves (we asked for divertor/midplane valves)

# H-Mode investigation: puffing location



- ✓ Similar puff from Lower and Upper divertor valves (we asked for divertor/midplane valves)
- ✓ Discharge with a total amount 6.5 heating power with equivalent behavior also in the lower divertor independently from the puffing location


# H-Mode investigation: puffing location



- ✓ Similar puff from Lower and Upper divertor valves (we asked for divertor/midplane valves)
- ✓ Discharge with a total amount 6.5 heating power with equivalent behavior also in the lower divertor independently from the puffing location
- ✓ Edge density profiles from Li-Beam evolution are pretty similar
- ✓ Similar behavior observed from RIC Antenna 4 for the available shot




# Compare fueling with/without cryopumps




- ✓ Same fueling but with cryo-pumps
- ✓ H-5 density is different and remain constant, both divertor and midplane pressure are reduced (to 1/3 approximately)  
no sign of detachment

# Compare fueling with/without cryopumps



- ✓ Same fueling but with cryo-pumps
- ✓ H-5 density is different and remain constant, both divertor and midplane pressure are reduced (to 1/3 approximately) no sign of detachment
- ✓ Different ELM regimes reached with reduced size and increased frequency without the cryopumps


# Compare fueling with/without cryopumps



- ✓ Same fueling but with cryo-pumps
- ✓ H-5 density is different and remain constant, both divertor and midplane pressure are reduced (to 1/3 approximately)  
no sign of detachment
- ✓ Different ELMy regimes reached with reduced size and increased frequency without the cryopumps
- ✓ Also with this amount of fueling weaker indication of SOL saturation observed as confirmed by Li-Beam and by RIC (Antenna 4)




# Compare fueling with/without cryopumps



- ✓ Same fueling but with cryo-pumps
- ✓ H-5 density is different and remain constant, both divertor and midplane pressure are reduced (to 1/3 approximately) no sign of detachment
- ✓ Different ELM regimes reached with reduced size and increased frequency without the cryopumps
- ✓ Also with this amount of fueling weaker indication of SOL saturation observed as confirmed by Li-Beam and by RIC (Antenna 4)
- ✓ Inter-ELM resolved profile suggest a flattening even with the cryopumps still even though  $\Lambda_{div}$  is marginal above 1 only in the near SOL




# Matching scenarios with cryo-pumps



- ✓ To match similar edge density and divertor pressure and to reach the same level of detachment we increase the fueling by almost a factor of 3, increasing also the rate. In addition to that we also increase substantially the N puffing.  
**Degraded H-Mode reached earlier in density without the cryopumps**




# Matching scenarios with cryo-pumps



- ✓ To match similar edge density and divertor pressure and to reach the same level of detachment we increase the fueling by almost a factor of 3, increasing also the rate. In addition to that we also increase substantially the N puffing.  
Degraded H-Mode reached earlier in density without the cryopumps
- ✓ Similar ELMy behavior obtained during the density ramp




# Matching scenarios with cryo-pumps



- ✓ To match similar edge density and divertor pressure and to reach the same level of detachment we increase the fueling by almost a factor of 3, increasing also the rate. In addition to that we also increase substantially the N puffing.  
**Degraded H-Mode reached earlier in density without the cryopumps**
- ✓ Similar ELM behavior obtained during the density ramp
- ✓ Without cryopumps evidence of stronger SOL profile flattening from Li-Be. **To be compared with appropriate variation of  $\Lambda_{div}$**



# Matching scenarios with cryo-pumps



- ✓ To match similar edge density and divertor pressure and to reach the same level of detachment we increase the fueling by almost a factor of 3, increasing also the rate. In addition to that we also increase substantially the N puffing.  
**Degraded H-Mode reached earlier in density without the cryopumps**
- ✓ Similar ELM behavior obtained during the density ramp
- ✓ Without cryopumps evidence of stronger SOL profile flattening from Li-Be. **To be compared with appropriate variation of  $\Lambda_{div}$**
- ✓ Inter-ELM resolved Li-Be profiles

# Comments on difficulties for H-Mode in TCV



plored





- ✓ X-point manipulator (hopefully with NPH) triggered at the same time as MPM
- ✓ X-point vertical shift in order to have SP at different vertical height at the target
- ✓ DN discharges. With slow movement of the second X-point into the vessel to be performed at constant power/density where shoulder already exists
- ✓ USN with midplane/X-point manipulator to monitor the upstream SOL



- ✓ H-Mode ?
- ✓ Long divertor legs (probe in the lower port)
- ✓ SnowFlake to monitor the fluctuations in between the 2 separatrix to be done in high density discharges
- ✓ Try to move the second X-point in SN divertor at a different Z position while keeping the same radial distances between the points



- ✓ Influence of neutral recycling source in establishing upstream profiles and comparison between Low-RT and Vertical target. Look also at the heat loads
- ✓ Current scan at constant q95/constant Bt