EUROfusion

SOL Filamentary transport: update from joint AUG-TCV MST1 experiment

presented by N. Vianello

29 January 2018

This work has been carried out within the framework of the EUROfusion Consortium and has received funding from the Euratom research and training programme 2014-2018 under grant agreement No 633053. The views and opinions expressed herein do not necessarily reflect those of the European Commission.

Scientific team

Volker Naulin, Jiri Adamek, Matteo Agostini, Diogo Aguiam, Scott Allan, Matthias Bernert, Daniel Carralero Ortiz, Stefan Costea, Istvan Cziegler, Hugo De Oliveira, Joaquin Galdon-Quiroga, Gustavo Grenfell, Antti Hakola, Codrina Ionita-Schrittwieser, Heinz Isliker, Alexander Karpushov, Jernej Kovacic, Benoît Labit, Florian Laggner, Jens Madsen, Roberto Maurizio, Ken McClements, Fulvio Militello, Jeppe Miki Busk Olsen, Jens Juul Rasmussen, Timo Ravensbergen, Bernd Sebastian Schneider, Roman Schrittwieser, Jakub Seidl, Monica Spolaore, Christian Theiler, Cedric Kar-Wai Tsui, Kevin Verhaegh, Jose Vicente, Nickolas Walkden, Zhang Wei, Elisabeth Wolfrum, W. Vijvers j

Motivation and deliverables

- ✓ Relation between downstream divertor conditions and up-stream SOL profiles is not well understood. Influence of SOL blob structures on shoulder formation and divertor conditions is key element towards predictive capabilities. Joint effort within the EUROfusion framework to address this issue on all the MST1 devices (AUG, TCV and MAST-U)

Motivation and deliverables

✓ Relation between downstream divertor conditions and up-stream SOL profiles is not well understood. Influence of SOL blob structures on shoulder formation and divertor conditions is key element towards predictive capabilities. Joint effort within the EUROfusion framework to address this issue on all the MST1 devices (AUG, TCV and MAST-U)

A series of deliverables are foreseen for 2017-2018 program

1. Cross-machine L-Mode shoulder dependence on current both at constant B_t and at constant q_{95}. Rationale: disentangle the effect of current and parallel connection length
2. Establish robust scenario for density shoulder profile in H-Mode and establish dependence on fuelling/neutral profiles/divertor condition
3. Fluctuations mesurement on AUG to study filamentary transport under high-power H-Mode conditions and under different plasma configurations (SN, DN)
4. Study the role of ELM regimes, neutral compression and particle density in filamentary transport and related shoulder formation
5. Identify the contribution of collisionality and seeding on filamentary transport and related shoulder formation
6. Determine the effect of filaments and shoulder formation on target heat loads in different H-mode plasmas

Motivation and deliverables

✓ Relation between downstream divertor conditions and up-stream SOL profiles is not well understood. Influence of SOL blob structures on shoulder formation and divertor conditions is key element towards predictive capabilities. Joint effort within the EUROfusion framework to address this issue on all the MST1 devices (AUG, TCV and MAST-U)

A series of deliverables are foreseen for 2017-2018 program

1. Cross-machine L-Mode shoulder dependence on current both at constant B_t and at constant q_{95}. Rationale: disentangle the effect of current and parallel connection length
2. Establish robust scenario for density shoulder profile in H-Mode and establish dependence on fuelling/neutral profiles/divertor condition
3. Fluctuations mesurement on AUG to study filamentary transport under high-power H-Mode conditions and under different plasma configurations (SN, DN)
4. Study the role of ELM regimes, neutral compression and particle density in filamentary transport and related shoulder formation
5. Identify the contribution of collisionality and seeding on filamentary transport and related shoulder formation
6. Determine the effect of filaments and shoulder formation on target heat loads in different H-mode plasmas

I will report only on few of the deliverables since part of them will be studied in forthcoming campaigns. Remember this is still a work in progress

Current scan at constant B_t



- ✓ Shape matched in within the single scan done for each of the machine
- ✓ The scan implies a modification of the $L_{||}$. AUG exhibit a parallel connection length which is 5 times smaller then TCV

Current scan at constant B_t



- ✓ AUG: Fueling reduced only at smaller current to avoid earlier disruption. Similar neutral pressure in the subdivertor region reached. NBI additional power added to keep power in the SOL approximately constant

Current scan at constant B_t



✓ TCV: Ohmic heating only. Similar neutral compression reached and D_α radiation from the floor.

Current scan at constant B_t



- ✓ Divertor neutral density estimated starting from D_α calibrated camera and using electron density and temperature from LP data. Neutral density increases earlier in edge density at lower current

Current scan at constant B_t



✓ Neutrals behavior reconciled whenever comparison considered as a function of Greenwald fraction

Current scan at constant B_t



- ✓ For both AUG and TCV flattening of normalized upstream profile reached earlier in density at lower current. For both the machine the increase of λ_n reached for larger values of Λ_{div}

Current scan at constant B_t



- ✓ Quantifying profile evolution using the shoulder amplitude metric introduce by Wynn and Lipschultz for JET. Amplitude is the difference between normalized upstream density profiles

Current scan at constant B_t



- ✓ Amplitude evolve faster in density at lower current in the far SOL

Current scan at constant B_t



- ✓ Amplitude evolve faster in density at lower current in the far SOL but once evolution *vs* greenwald fraction is considered the evolution is equivalent between different current

Current scan at constant B_t



✓ Amplitude evolution still reconciled in AUG if considered as a function of local evolution of Λ_{div}

Current scan at constant B_t



- ✓ For both AUG and TCV λ_n increases with blob size without significant difference within the current explored

Current scan at constant q_{95}



- ✓ Shape matched in within the single scan even though this required for TCV operation with very low toroidal field (0.8T)
- ✓ The parallel connection length remains almost unchanged

Current scan at constant q_{95}



✓ AUG: As for the case of constant B_t we have pretty reproducible behavior matching basically the plasma condition in within the current scan

Current scan at constant q_{95}



✓ TCV: Even at such an high density at lower current (and lower B_t) no sign of target ion flux rollover/detachment

Current scan at constant q_{95}



✓ AUG: Divertor neutral density exhibits still the same behavior is considered as a function of greenwald fraction

Current scan at constant q_{95}



✓ For AUG upstream and target profiles exhibit the same behavior with flattening observed at large values of Λ_{div}. TCV actually even at high value of density no sign of upstream profile flattening even at very large values of Λ_{div}

Current scan at constant q_{95}



✓ This is due to the fact we did not reach divertor detachment which seems necessary for upstream profile modification

Current scan at constant q_{95}



✓ AUG: Amplitude evolution as a function of Λ_{div} still reconcile the explored current scan

Current scan at constant q_{95}



✓ AUG exhibit consistently an increase of λ_n with blob-size whereas for TCV the profile remains flat consistently with a small variation of δ_b

Current scan at constant q_{95}



✓ And for TCV this is true even at high value of Λ_{div}