

Topic 2 I: AUG experiment KoM

J. Madsen and N. Vianello

03 March 2017



This work has been carried out within the framework of the EUROfusion Consortium and has received funding from the Euratom research and training programme 2014-2018 under grant agreement No 633053. The views and opinions expressed herein do not necessarily reflect those of the European Commission.



- ✓ For Topic-21 on AUG 14 shots forseen, split into two blocks of 7 shot each on week 15 and week 17 respectively
- ✓ The proposed experimental plan address some of the proposed experimental plan for both the L-Mode and H-Mode part.



We will conclude the **L-Mode** part in Week 15 where we also would like to include part of the **H-Mode** scenario development. This would give us an additional week between the experiments to address possible issues in particular for the H-mode part

Week 15

We choose as reference shot # 30269 ($I_p = 0.8$ MA, $B_\phi = 2.5$ T, $q_{95} \approx 4.5$)

1. Shot at $I_p = 0.6$ MA keeping the same toroidal field $B_\phi = 2.5$ T as the reference adjust the fueling rate (*Current scan with modification of q_{95}*)
2. Shot at $I_p = 0.6$ MA reduce the toroidal field $B_\phi \approx 2$ T in order to match $q_{95} \approx 4.5$, (*Current scan at fixed q_{95}*). This would accommodate the diagnostic request of D. Aguiam
3. Density ramp with $I_p = 1$ MA and $B_\phi = 2.5$ T
4. Density ramp with $I_p = 1$ MA, increasing the toroidal field in order to match $q_{95} \approx 4.5$



Week 15

For the **H-Mode** scenario development we start from the best shot found in 2016 (# 33478) and increase the heating power

1. Start from shot # 33478 but with increased heating power (6MW). Adjust fueling rate from reference by increasing by a factor of 30 %. 1 Plunge of probe head at the end of the discharge still in a safe position and IR monitoring
2. Repeat # 1 eventually adjusting the fueling rate. Start the N seeding in feedforward starting from the level found in reference
3. Trade off between #1 and #2 Fueling/Seeding. Additional plunge of probe at the end of the discharge
4. This scenario would allow the exploitation of particle acceleration (McClements) physics as piggy-back



Week 17: This strongly depends on the achievement of H-Mode scenario obtained in Week 15

1. Repeat best H-Mode shot found in Week 15 1st Radial position of probe
2. Repeat #1, different probe position
3. Repeat #1, different probe position
4. Repeat best H-Mode shot found in week 15 and reduced the cryopumps
5. Repeat best H-Mode shot found in week 15 and puff from midplane
6. Contingency
7. Contingency



Among the contingency we propose the following 4 possibilities to be discussed

1. Reversing B_t direction and repeat one identical shot (e.g # 30269) to investigate the role of SOL flows in SOL shoulder formation and filamentary transport
2. DN discharge with similar density ramps as in reference. Possibly the two X-point should sit on the same flux surface
3. Attempt a scenario similar to Topic-06 which will be performed later in time. See for example shot # 29816 (Presented by T. Eich in the GPM) which is at even higher power (8 MW) or # 25740 which is actually in DN (see proposal from J. Vicente). If we choose for this we could actually compare with the priority 3 of L-Mode contingency
4. Reverse B_t operation. In this case the L-H threshold is different and we might end by careful adjusting the power into I-Mode scenario
5. Working at 2T in H-Mode would require additional development
6. Given that the upper divertor is less diagnosed then the lower one we prefer eventually to operate with reverse B_ϕ



- ☒ Midplane Manipulator
- ☐ Li-Beam. *Are fluctuations and profiles available simultaneously*
- ☐ RFA #2
- ☐ Divertor probes
- ☒ Neutral profiles
- ☐ Infrared for probe head monitoring. *Are Target infrared measurements available/useful?*
- ☐ GPI
- ☒ Reflectometer. *The operation at 2T can be obtained during the q_{95} scan*
- ☒ Fast probes on the limiter
- ☐ Bolometer/AXUV in the divertor region



1. Check the shape modification during the current/ q_{95} scan
2. Probe conditioning?
3. Check the status of the diagnostics including GPI (issue regarding the puffing)
4. Methodology (Λ_{div} computation and profile) λ_n filaments properties etc.
5. Code preparation for analysis and visualization. *GITHUB repository?*
6. Optimization of the effort: please provide us a more detailed plan of your analysis in order to limit superposition or work duplication