



SOL Filamentary transport: update from joint AUG-TCV MSTI experiment

presented by N. Vianello

29 January 2018



This work has been carried out within the framework of the EUROfusion Consortium and has received funding from the Euratom research and training programme 2014-2018 under grant agreement No 633053. The views and opinions expressed herein do not necessarily reflect those of the European Commission.



Volker Naulin, Jiri Adamek, Matteo Agostini, Diogo Aguiam, Scott Allan, Matthias Bernert, Daniel Carralero Ortiz, Stefan Costea, Istvan Cziegler, Hugo De Oliveira, Joaquin Galdon-Quiroga, Gustavo Grenfell, Antti Hakola, Codrina Ionita-Schrittwieser, Heinz Isliker, Alexander Karpushov, Jernej Kovacic, Benoît Labit, Florian Laggner, Jens Madsen, Roberto Maurizio, Ken McClements, Fulvio Militello, Jeppe Miki Busk Olsen, Jens Juul Rasmussen, Timo Ravensbergen, Bernd Sebastian Schneider, Roman Schrittwieser, Jakub Seidl, Monica Spolaore, Christian Theiler, Cedric Kar-Wai Tsui, Kevin Verhaegh, Jose Vicente, Nickolas Walkden, Zhang Wei, Elisabeth Wolfrum, W. Vijvers j



- ✓ Relation between downstream divertor conditions and up-stream SOL profiles is not well understood. Influence of SOL blob structures on shoulder formation and divertor conditions is key element towards predictive capabilities. Joint effort within the EUROfusion framework to address this issue on all the MSTI devices (AUG, TCV and MAST-U)



- ✓ Relation between downstream divertor conditions and up-stream SOL profiles is not well understood. Influence of SOL blob structures on shoulder formation and divertor conditions is key element towards predictive capabilities. Joint effort within the EUROfusion framework to address this issue on all the MSTI devices (AUG, TCV and MAST-U)

A series of deliverables are foreseen for 2017-2018 program

1. Cross-machine L-Mode shoulder dependence on current both at constant B_t and at constant q_{95} . Rationale: disentangle the effect of current and parallel connection length
2. Establish robust scenario for density shoulder profile in H-Mode and establish dependence on fuelling/neutral profiles/divertor condition
3. Fluctuations measurement on AUG to study filamentary transport under high-power H-Mode conditions and under different plasma configurations (SN, DN)
4. Study the role of ELM regimes, neutral compression and particle density in filamentary transport and related shoulder formation
5. Identify the contribution of collisionality and seeding on filamentary transport and related shoulder formation
6. Determine the effect of filaments and shoulder formation on target heat loads in different H-mode plasmas




- ✓ Relation between downstream divertor conditions and up-stream SOL profiles is not well understood. Influence of SOL blob structures on shoulder formation and divertor conditions is key element towards predictive capabilities. Joint effort within the EUROfusion framework to address this issue on all the MSTI devices (AUG, TCV and MAST-U)


A series of deliverables are foreseen for 2017-2018 program

1. Cross-machine L-Mode shoulder dependence on current both at constant B_t and at constant q_{95} .
Rationale: disentangle the effect of current and parallel connection length
2. Establish robust scenario for density shoulder profile in H-Mode and establish dependence on fuelling/neutral profiles/divertor condition
3. Fluctuations measurement on AUG to study filamentary transport under high-power H-Mode conditions and under different plasma configurations (SN, DN)
4. Study the role of ELM regimes, neutral compression and particle density in filamentary transport and related shoulder formation
5. Identify the contribution of collisionality and seeding on filamentary transport and related shoulder formation
6. Determine the effect of filaments and shoulder formation on target heat loads in different H-mode plasmas

I will report only on few of the deliverables since part of them will be studied in forthcoming campaigns




- ✓ Shape matched in within the single scan done for each of the machine
- ✓ The scan implies a modification of the $L_{||}$. AUG exhibit a parallel connection length which is 5 times smaller then TCV




- ✓ AUG: Fueling reduced only at smaller current to avoid earlier disruption. Similar neutral pressure in the subdivertor region reached. NBI additional power added to keep power in the SOL approximately constant


Current scan at constant B_t



- ✓ TCV: Ohmic heating only.
- Similar neutral compression reached and D_α radiation from the floor.




- ✓ Divertor neutral density estimated starting from D_α calibrated camera and using electron density and temperature from LP data. Neutral density increases earlier in edge density at lower current




- ✓ Neutrals behavior reconciled whenever comparison considered as a function of Greenwald fraction


Current scan at constant B_t




- ✓ For both AUG and TCV flattening of normalized upstream profile reached **earlier in density at lower current**. For both the machine the increase of λ_n reached for larger values of Λ_{div}



- ✓ Quantifying profile evolution using the **shoulder amplitude metric** introduced by Wynn and Lipschultz for JET. **Amplitude is the difference between normalized upstream density profiles**



- ✓ Amplitude evolve faster in density at lower current



- ✓ Amplitude evolve faster in density at lower current but once evolution vs greenwald fraction is considered the evolution is equivalent between different current