

## Topic 21 Experiment and analysis

presented by N. Vianello on behalf of MST1-Topic 21 scientific team 17 May 2018



### Scientific team



Volker Naulin, Matteo Agostini, Diogo Aguiam, Scott Allan, Matthias Bernert,
Daniel Carralero Ortiz, Stefan Costea, Istvan Cziegler, Hugo De Oliveira, Joaquin
Galdon-Quiroga, Gustavo Grenfell, Antti Hakola, Codrina Ionita-Schrittwieser,
Heinz Isliker, Alexander Karpushov, Jernej Kovacic, Benoît Labit, Bruce Lipschultz,
Roberto Maurizio, Ken McClements, Fulvio Militello, Jeppe Miki Busk Olsen, Jens
Juul Rasmussen, Timo Ravensbergen, Bernd Sebastian Schneider, Roman
Schrittwieser, Jakub Seidl, Monica Spolaore, Christian Theiler, Cedric Kar-Wai Tsui,
Kevin Verhaegh, Jose Vicente, Nickolas Walkden, Zhang Wei, Elisabeth Wolfrum,
W. Vijvers j

#### Motivation and deliverables



✓ Relation between downstream divertor conditions and up-stream SOL profiles is not well understood. Influence of SOL blob structures on shoulder formation and divertor conditions is key element towards predictive capabilities. Joint effort within the EUROfusion framework to address this issue on all the MSTI devices (AUG, TCV and MAST-U)

#### Motivation and deliverables



✓ Relation between downstream divertor conditions and up-stream SOL profiles is not well
understood. Influence of SOL blob structures on shoulder formation and divertor conditions is key
element towards predictive capabilities. Joint effort within the EUROfusion framework to address
this issue on all the MSTI devices (AUG, TCV and MAST-U)

#### A series of deliverables were foreseen by 2017 program

- Cross-machine L-Mode shoulder dependence on current both at constant B<sub>t</sub> and at constant q<sub>95</sub>.
  Rationale: disentangle the effect of current and parallel connection length
- 2. Establish robust scenario for density shoulder profile in H-Mode and establish dependence on fuelling/neutral profiles/divertor condition
- 3. Fluctuations mesurement on AUG to study filamentary transport under high-power H-Mode conditions and under different plasma configurations (SN, DN)
- 4. Study the role of ELM regimes, neutral compression and particle density in filamentary transport and related shoulder formation
- Identify the contribution of collisionality and seeding on filamentary transport and related shoulder formation
- Determine the effect of filaments and shoulder formation on target heat loads in different H-mode plasmas

#### Motivation and deliverables




✓ Relation between downstream divertor conditions and up-stream SOL profiles is not well
understood. Influence of SOL blob structures on shoulder formation and divertor conditions is key
element towards predictive capabilities. Joint effort within the EUROfusion framework to address
this issue on all the MSTI devices (AUG, TCV and MAST-U)

#### A series of deliverables were foreseen by 2017 program

- Cross-machine L-Mode shoulder dependence on current both at constant B<sub>t</sub> and at constant q<sub>95</sub>.
  Rationale: disentangle the effect of current and parallel connection length
- 2. Establish robust scenario for density shoulder profile in H-Mode and establish dependence on fuelling/neutral profiles/divertor condition
- 3. Fluctuations mesurement on AUG to study filamentary transport under high-power H-Mode conditions and under different plasma configurations (SN, DN)
- 4. Study the role of ELM regimes, neutral compression and particle density in filamentary transport and related shoulder formation
- Identify the contribution of collisionality and seeding on filamentary transport and related shoulder formation
- 6. Determine the effect of filaments and shoulder formation on target heat loads in different H-mode plasmas


Remember this is still a work in progress






- √ Shape matched in within the single scan done for each of the machine
- √ The scan implies a modification of the L<sub>||</sub>. There is a factor of 5 difference between the two machines due to the very long outer divertor leg of TCV






✓ AUG: Fueling reduced only at lower Ip to avoid earlier disruption. Similar neutral pressure in the subdivertor region reached. NBI additional power added to keep power in the SOL approximately constant






 $\checkmark$  TCV: Ohmic heating only. Similar neutral compression reached and  $D_{\alpha}$  radiation from the floor. Ion flux rollover reached in all the three current, although marginally at 330 kA






✓ In both the machines both the peak target density and the radiation close to divertor target exhibit rollover at increasing density with increasing current






✓ Whenever considered as a a function of Greenwald fraction the behaviors at different currents almost reconciled for AUG but not for TCV






✓ We now consider the Target and upstream profiles at the same level of densities






- √ We now consider the Target and upstream profiles at the same level of densities
- $\checkmark$  For both AUG and TCV flattening of normalized upstream profile reached earlier in density at lower current. For both the machine the increase of  $\lambda_n$  reached for larger values of  $\Lambda_{div}$






- ✓ Quantifying profile evolution using the shoulder amplitude metric introduce by Wynn and Lipschultz for JET (Wynn et al. 2018).
- ✓ Amplitude is the difference between normalized upstream density profiles
- ✓ Distinguishing behavior on the near and far SOL






✓ Amplitude evolve faster in density at lower current in the far SOL





- ✓ Amplitude evolve faster in density at lower current in the far SOL but once evolution vs greenwald fraction is considered the evolution is equivalent between different current.
- ✓ Still some inconsistency at lower current in agreement with different detachment evolution





 $\checkmark$  Amplitude evolution still reconciled in AUG if considered as a function of local evolution of  $\Lambda_{\text{div}}$