

R Markdown - PDF & Word Output

Nick Rohrbaugh

9/15/2020

Anatomy of Rmd

This is an R Markdown document which can be rendered as a PDF or Word doc. R Markdown documents are files that end in `.Rmd` and include a few different parts:

The YAML header

The YAML header is the section at the very top of our file between the `---` symbols. This text doesn't show up directly in our output, but it tells R Markdown how to render our document.

We can specify multiple output formats in our YAML header, like `html_document`, `pdf_document`, and `word_document`. We can also specify settings for these output formats, to do things like add a floating table of contents. And we can add things like a title, author, and date which may be automatically rendered depending on our output format.

Code chunks

The most important part of our R Markdown document - our code! - lives in “chunks” throughout our document. These are the sections that start and end with three tick marks (````) and have a dark gray background in RStudio.

The first line of a code chunk also includes information in curly braces about the code and how its output should be displayed:

- The first and always required item is the language the code is in, e.g. `{r}` or `{python}`
- After the language comes an optional chunk label, e.g. `{r setup}`
- Finally and separated by a comma come any chunk options. These control the output of our code. A few useful ones include:
 - `eval`: whether to run the code
 - `echo`: whether to print the code (or just the output)
 - `warning`, `message`, `error`: whether to print any warnings, messages, or errors generated by our code
 - many more

Markdown

Markdown is how we do all of our other formatting. It was written in 2004 by Jon Gruber and Aaron Swartz¹ as a way to turn plain text into rich formatted HTML. Markdown syntax is easy to learn, and elements of Markdown are supported in many places (Reddit, Slack, discussion boards).

¹<http://www.aaronsw.com/weblog/001189>

As you can see throughout this document, you can do a lot of things with Markdown, including:

- *Italicize* text by surrounding it with single underscores (`_text_`) or asterisks (`*text*`)
- **Bold** text by surrounding it with double asterisks (`**text**`)
- Insert links with `[some text](https://www.rstudio.com/)`
- Render text as inline code with single tick marks


* Render text as code blocks with triple tick marks

- Create section headings with `#` (and subheadings with `##`, `###`, `####`, ...)
- Create ordered lists with `1.`, `2.`, `3.`, ... and unordered lists with `*`, `-`, or `+`
- Create footnotes with `^[]2`
- Create math equations with LaTeX syntax: $f(k) = \binom{n}{k} p^k (1-p)^{n-k}$

We can even run code inline with single tick marks like this: The sum of 2 and 2 is 4.


House Price Index

HPI over time



²this is a footnote

Distributions of monthly changes



Analysis details

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.