


Table of Contents	
2	Notes
3	KEA MCU
4	OpenSDA
5	Power Supply/CAN/LIN
6	I/O Headers
7	Headers Multiple Functions

Revisions			
Rev	Description	Date	Approved
X1	Original Release	DEC-17-2014	O. Romero
X2	Second Release	JAN-30-2015	O. Romero
A	Production Release	FEB-03-2015	O. Romero
B	2nd Production Release *J1-9 Connected to 3V instead of 5V_VDDA_pwr *J1-3 Connect to VDD instead of 3V3 *Added U107 *Replaced R70L *Placed C48 and C47 after D9 and D13 *Replaced C18 with 10 uF cap. *Placed U14 *Changed net name RS-WY to V18 *Relocate PTMG channels *Relocate signals on C202 to C212 *Place R11 and CMP R94 *Changed C84 and tin header with right angle headers *Place R105 by default and leave R104 DNP *V11 pin J connected to VREF *Replaced R80 with two 2K resistors in parallel *Removed L3 *Removed C14 *Placed D84 button, R118, R116 and C46 *Placed U18 *Button resistors changed to pulldown *Changed J1 voltage regulator *Changed Q1 translator *Replaced D15, D13 and D6 *Replaced C15 and C18	JUL-06-2015	J.Romero J.Sanchez

FREEDOM+ KEA





Automotive Processing Product Line
6501 William Cannon Drive West
Austin, TX 78735-8598

This document contains information proprietary for NXP Semiconductors and shall now be used for engineering design, procurement or manufacture in whole or in part without the express written permission of NXP Semiconductors.


Designer: Oswaldo Romero	Drawing Title: FRDM+KEA		
Drawn by: Oswaldo Romero	Page Title: TITLE PAGE		
Approved: J.Romero - J.Sanchez	Size C	Document Number SCH-28696 PDF: SPF-28696	Rev B
Date: Monday, July 06, 2015		Sheet 1 of 7	

- Unless Otherwise Specified:
All resistors are in ohms, 1% and 5 %
All capacitors are in uF, 10% , 20 % and 5%
All voltages are DC
All polarized capacitors are aluminum electrolytic
- Interrupted lines coded with the same letter or letter combinations are electrically connected.
- Device type number is for reference only. The number varies with the manufacturer.
- Special signal usage:
_B Denotes - Active-Low Signal
<> or [] Denotes - Vectored Signals
- Interpret diagram in accordance with American National Standards Institute specifications, current revision, with the exception of logic block symbology.







Populated with KEA32




OpenSDA Interface







OpenSDA INTERFACE JTAG CONNECTOR



PWR SWITCH
(To enable Ex-f



SDA_SPI0_RST_B R41 0 SDA_SPI0_EN
SDA_SPI0_CS R38 0 SDA_SPI0_OE
{For enablement purposes only}



NXP			
ICAP Classification: FCP: FIUO: X PUB:			
Drawing Title: FRDM+KEA			
Page Title: Power Supply/SWD/Reset			
Size C	Document Number SCH-28696 PDF: SPF-28696	Rev B	
Date: Monday, July 06, 2015	Sheet 5	of 7	

